


Retroreflective sensor

ML100-55/103/115




- Miniature design
- Easy to use
- Clearly visible LEDs for Power ON, switching state and weak signal indication
- Full metal thread mounting
- Very bright, highly visible light spot
- Not sensitive to ambient light

Retroreflective sensor with polarization filter, plastic housing, 5 m detection range, red light, sensitivity adjuster, light/dark on, DC version, PNP output, fixed cable

Function

The optical sensors of this series are suitable for both standard and demanding applications.
The series features a miniature housing design, two M3 metal-threaded mounting holes and a highly visible LED status indicator.
Each device is equipped with a sensitivity adjuster and a light-on/dark-on changeover switch for increased flexibility.
A wide variety of versions are available in both infrared light and red light with PowerBeam for easy alignment.
Special versions with BlueBeam are suitable for challenging applications like those in the solar and battery industries.

Dimensions



Release date: 2023-03-28 Date of issue: 2023-03-28 Filename: 210545_eng.pdf

Technical Data


General specifications		
Effective detection range		0 ... 5 m
Reflector distance		0.01 ... 5 m
Threshold detection range		7 m
Reference target		H50 reflector
Light source		LED
Light type		modulated visible red light
Polarization filter		yes
Diameter of the light spot		approx. 500 mm at a distance of 7 m
Opening angle		approx. 4 °
Optical face		frontal
Ambient light limit		EN 60947-5-2:2007+A1:2012
Functional safety related parameters		
$MTTF_d$		860 a
Mission Time (T_M)		20 a
Diagnostic Coverage (DC)		0 %
Indicators/operating means		
Operation indicator		LED green: power on
Function indicator		LED yellow: lights up when receiving the light beam ; flashes when falling short of the operating reserve; OFF when light beam is interrupted
Control elements		sensitivity adjustment
Control elements		Light-on/dark-on changeover switch
Electrical specifications		
Operating voltage	U_B	10 ... 30 V DC
Ripple		max. 10 %
No-load supply current	I_0	< 20 mA
Output		
Switching type		The switching type of the sensor is adjustable. The default setting is: light-on
Signal output		1 PNP output, short-circuit protected, reverse polarity protected, open collector
Switching voltage		max. 30 V DC
Switching current		max. 100 mA , resistive load
Voltage drop	U_d	≤ 1.5 V DC
Switching frequency	f	1000 Hz
Response time		0.5 ms
Conformity		
Product standard		EN 60947-5-2
Approvals and certificates		
UL approval		cULus Listed, Class 2 Power Source or listed Power Supply with a limited voltage output with (maybe integrated) fuse (max. 3.3 A according UL248), Type 1 enclosure
CCC approval		CCC approval / marking not required for products rated ≤36 V
Ambient conditions		
Ambient temperature		-30 ... 60 °C (-22 ... 140 °F)
Storage temperature		-40 ... 70 °C (-40 ... 158 °F)
Mechanical specifications		
Housing width		11 mm
Housing height		31 mm
Housing depth		20 mm
Degree of protection		IP67
Connection		2 m fixed cable
Material		
Housing		PC (Polycarbonate)
Optical face		PMMA
Mass		approx. 50 g
Tightening torque, fastening screws		0.6 Nm

Release date: 2023-03-28 Date of issue: 2023-03-28 Filename: 210545_eng.pdf


Technical Data

Cable length		2 m

Connection




Assembly



1	Light-Dark-switching	
2	Sensitivity adjuster	
3	Signal display	yellow
4	Operating display	green


Characteristic Curve



Release date: 2023-03-28 Date of issue: 2023-03-28 Filename: 210545_eng.pdf

Characteristic Curve

Relative received light strength (typical)



Accessories

	**OMH-ML100-09**	Mounting aid for round steel ø 12 mm or sheet 1.5 mm ... 3 mm
	**OMH-F10-ML100**	Mounting aid for ML100 series
	**OMH-ML100-01**	Mounting aid for ML100 series, mounting bracket
	**OMH-ML100-02**	Mounting aid for ML100 series, mounting bracket
	**OMH-ML100-03**	Mounting aid for round steel ø 12 mm or sheet 1.5 mm ... 3 mm
	**OMH-ML100-04**	Mounting aid for ML100 series, mounting bracket
	**OMH-ML100-05**	Mounting aid for ML100 series, mounting bracket
	**OMH-10**	Mounting aid for ML100 series
	**REF-C110-2**	Reflector, round ø 84 mm, central mounting hole
	**REF-H60-2**	Reflector with mounting holes
	**REF-H33**	Reflector with screw fixing

Release date: 2023-03-28 Date of issue: 2023-03-28 Filename: 210545_eng.pdf

Accessories

	**OFR-70-2**	Reflective tape 70 mm x 70 mm
	**REF-MH23-2**	Reflector with Micro-structure, rectangular 23 mm x 14 mm, diagonal mounting hole
	**OMH-ML100-S1**	Mounting bracket
	**OMH-ML100-08**	Mounting aid for ML100 series, Snap-in
	**REF-H85-2**	Reflector, rectangular 84.5 mm x 84.5 mm, mounting holes
	**REF-H50**	Reflector, rectangular 51 mm x 61 mm, mounting holes, fixing strap
	**OFR-100/100**	Reflective tape 100 mm x 100 mm

Release date: 2023-03-28 Date of issue: 2023-03-28 Filename: 210545_eng.pdf

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

PEPPERL+FUCHS:

NBB0.8-5GM25-E2 NBB2-8GM40-E0-V1 OQT150-R101-2EP-IO-V31 GLV30-8-2500/47/73C MLV41-8-H-350-RT/59/92/136 NBB1-4GM22-E2 NBN40-U1-E3 S1SD-1AI-1U.1 134130 214916 NBB5-18GM50-A0 NBB5-18GM50-E2 NCB40-FP-A2-P1 UB2000-F42-E6-V15 UB4000-F42-E6-V15 Z954 NBB2-12GM50-A2-V1 NBB3-V3-Z4 NBB4-12GM50-A2-V1 OQT150-R100-2EP-IO-V31-L V15-W-10M-PUR UB400-F77-E2-V31 114642 134143 OBD450-18GK40A-E2 OBR2500-12GM40-E5 UBE800-F77-SE2-V31 RL28-8-H-2000-IR/105/110 SJ10-E2 CCN15-30GS60-E2-V1