

TECHNICAL DATA SHEET

35-0010-B30-R

Battery Signal Switch

Technical Data

CASE MATERIAL	PA GF Black
SWITCH LEVER MATERIAL	PA GF Red
DIELECTRIC WITHSTAND VOLTAGE	700 VDC, 2 sec.
VOLTAGE	Up to 32 VDC
DUTY RATING	Max. 4 A
SEALING	IP 67 / IEC 529
VIBRATION	4G / 50-2000 Hz
SHOCK G-LEVEL	6G / 11 msec
WEIGHT	160 g
TEMPERATURE RANGE	-40°C to +85°C
MOUNTING POSITION	Optional
SWITCH LEVER	Removeable

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TE Connectivity:

2-32562-2 3430B2F51RTDF 1-794222-0 1488167-1 2-292161-3 650075-000 SMW73R0JT 1969656-1 2-520128-2 352116RFT 35402K7FT CRGCQ0805F150R 2377783-2 3-1393225-0 640174-1 CRGCQ2010J3K3 1-1743284-2 292230-8 1743455-2 36161 917696-1 936348-1 141991-2 1MM-HU-D10-VS-00-F-TBP 281990-2 1393431-1 2-520103-2 2834055-1 917790-2 SMV3W5M6JT