TE Connectivity: Every Connection Counts
© 2016 TE Connectivity Ltd. family of companies. All Rights Reserved

HARNESSING

HEAT SHRINK BOOTS



✔ Active

**TE CONNECTIVITY (TE)**

# 202D121-12-60-0

Raychem | CAP , CRPS

202D121-12-60-0
TE Internal Number: 825837-000
Alias ID: 6-1196450-5

EU RoHS Compliant
EU ELV Compliant

**Lipped** Yes

**Operating Temperature Range (°C)** -55 – 200

**Fluid/Chemical Resistance** Suitable for long term fluid immersion & elevated temperatures including fuel

**Adhesive Options** S1125 Separate Adhesive, -75°C – 150°C (-103°F – 302°F), S1255-04 Separate Adhesive, -55°C – 200°C (-67°F – 392°F)

**Material Systems Code** 200

**PRODUCT DRAWING**
English

## DOCUMENTATION

### Product Drawings

**Boot, Straight, With Lip**
PDF
**English**

**Boot, Straight, With Lips**
PDF
**English**

### Product Specifications

Product Specification

**Raychem Fluoro Elastomer Molded Components Flame-Retarded, Flexible, Heat-Shrinkable**
PDF
**English**

Downloaded from Arrow.com.

Product Environmental Compliance

Safety Data Sheet

**Heat-Shrinkable Fluoropolymer Products**

PDF

**English**

**Heat-Shrinkable Fluoropolymer Products**

PDF

**German**

**Heat-Shrinkable Fluoropolymer Products**

PDF

**French**

**Heat-Shrinkable Fluoropolymer Products**

PDF

**Dutch**

**Heat-Shrinkable Fluoropolymer Products**

PDF

**Italian**

**Heat-Shrinkable Fluoropolymer Products**

PDF

**Spanish**

**Heat-Shrinkable Fluoropolymer Products**

PDF

**Swedish**

## FEATURES

Please review product documents or contact us for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

**Molded Part Type** Molded Boot

Configuration Features

**Lipped** Yes

Body Features

**Material Systems Code** 200
**Adhesive Pre-Coat** No
**Entry Size (Braided or Magneform Adapter)** 4, 5, 6
**Entry Size (Solid or Fixed Adapter)** 4 – 6
**Material** Modified Fluoro-Elastomer
**Entry Size (Tinel-Lock Adapter)** 4, 5
**Entry Size (Spin Coupling Adapter)** 4 – 10

Dimensions

Downloaded from Arrow.com.

**Cable Diameter Range** 5.6 – 12.4 mm [ .22 – .488 in ]
**Wire/Cable Outside Diameter** .236 in, .276 in, .3 in, .31 in, .35 in, 6 mm, 7 mm, 8 mm, 9 mm

---

Usage Conditions

**Operating Temperature Range (°C)** -55 – 200

---

Operation/Application

**Power Cable Accessory** No

---

Industry Standards

**Government Qualified** No
**Approved Standards** BS-G-198-5-DD, DEF Std 59-97 Issue 3 Type DD, SAE AS I 81765/4

---

Other

**Fluid/Chemical Resistance** Suitable for long term fluid immersion & elevated temperatures including fuel
**Adhesive Options** S1125 Separate Adhesive, -75°C – 150°C (-103°F – 302°F), S1255-04 Separate Adhesive, -55°C – 200°C (-67°F – 392°F)
**Adhesive Type** Adhesive Purchased Separately

Statement of Compliance

**Statement of Compliance**
PDF

---

Downloaded from Arrow.com.