

MAPX	MODIFICATION	DATE







FRONT EDGE OF CONNECTOR
PCB LAYOUT


NOTES:
1. HOUSING: SEE NOTES,
TERMINAL: SEE NOTES.
SHELL: SEE NOTES.


SPECIFICATION:
1. ELECTRICAL CHARACTERISTIC:
CONTACT RESISTANCE: 30MΩ MAX
DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1MIN
INSULATION RESISTANCE: 1000MΩ MIN
2. MECHANICAL CHARACTERISTIC:
INSERTION FORCE: 35N(3.57KGF) MAX
EXTRACTION FORCE: 10~35N(1.02~3.57KGF)MIN
DURABILITY: 1500 CYCLES EXTRACTION FORCE:10~35N
3000 CYCLES MIN
5000 CYCLES EXTRACTION FORCE:3~35N
3. ENVIRONMENTAL:
OPERATING TEMPERATURE: -55℃+85℃
4. Contact finish:
01:Selective Gold Flash
02:Selective Gold 3U"
03:Selective Gold 5U"
04:Selective Gold 15U"
05:Selective Gold 30U"




SECTION A-A









产品图 PRODUCT CHART DWG			
公差一览表 TOLERANCE UNLESS OTHERMSE			
X.	±0.25	X.	±5.°
.X	±0.20	.X	±2.°
.XX	±0.15	.XX	±1.°
.XXX	±0.10	.XXX	±0.5°

深圳市精拓金电子有限公司

单位 UNITS	MM	制图 DRAWING	Z-Y-B	制图料号 PRODUCT PART NO.	910-461A1017Y10100
比例 SCALE	1:1	审核 CHKD		产品名称 PRODUCT NO.	AF10.0C款180度无脚无边铁壳 PBT白胶6.5无耳朵
日期 DATE	2012.06.15	核准 APPD		角法 VIEW	版本 VER A0

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Jing extension:

910-151A2021D10100 917-B88C201AH70201 917-P81A202ES60201 905-761A2032S10200
907-111A1022D10200 916-151A1022Y10200 918-418K2022Y40011 919-162A1012D10400
920-154A2021Y10110 920-A62A2021S10108 920-F52A2021S10105 904-232B2032S10100
918-318K2023C40005 918-468K2029Y50000 920-A62A2021S10104 920-C52A2021S10105
920-C62A2021S10103 904-232A2031S10100 908-351A1011D10100 912-112A2021S10100
920-A64A2091S101A3 904-331B2032S10200 906-262A1021D10200 906-552A1012D10200
907-312A1101Y10210 911-221A2021S10100 912-112A1011D10100 912-312A1012D10100
906-752B1114D10200 918-415K3028S40000