Pneumatic muffler
AMTE-M-LH-N14

Part number: 1206990





General operating condition

Data sheet

Feature	Value
Mounting position	Any
Pack size	20
Symbol	00991473
Operating pressure	0 MPa ... 1 MPa
Operating pressure	0 bar ... 10 bar
Flow rate with respect to atmosphere	3080 l/min
Operating medium	Compressed air as per ISO 8573-1:2010 [7:-:-]
Information on operating and pilot media	Operation with oil lubrication possible
Corrosion resistance class (CRC)	1 - Low corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L
Noise level	82 dB(A)
Ambient temperature	-40 °C ... 80 °C
Product weight	17 g
Pneumatic connection	1/4 NPT
Cushioning insert material	Bronze
Material of screwed plug	Brass
Note on materials	RoHS-compliant

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

153269 CRVZS-0.4 QSLL-G1/2-12 DSBC-80-20-D3-PPSA-N3 SGS-M10X1,25 HGL-1/8-QS-6 NPQP-Y-Q6-E-FD-P10 QSF-1/4-8-B SASC-P4-A-M8-A QSML-6 QSS-8-F QSY-6H-4 153031 153367 NPQH-T-Q14-E-P10 QSF-3/8-8-B 153307 NPQP-Y-R12-Q12-FD QS-1/2-16 VBQF-U-G14-E QS-1/8-8-I QS-10H-6 VABM-B10-25S-G38-6-P3 VABM-B10-25S-G38-10 NPQP-D-Q4-S8-FD-P10 NPQP-L-Q10-E-FD-P10 NPQP-LQ-R18-Q4-FD-P10 NPQP-LQ-R18-Q8-FD-P10 NPQP-T-Q8-E-FD-P10 153151