Your Expert Partner for **Human Machine Interfaces**

Actuator

Distribution by
DigiKey

46-
2234.31E0.000



https://digikey.eao.com/p/46-2234.31E0.000

Your product:



46-2234.31E0.000
Actuator

FRONT

Front form:	round
Front dimension:	Ø 29,5 mm
Front bezel colour:	Silver
Front bezel material:	Metal

MOUNTING

Design:	raised
Mounting cut-out:	Ø 22.3 mm

OPERATING-/INDICATION PART

Lens optics:	transparent
Lens shape:	flush
Lens illumination:	illuminative
Lens material:	Plastic
Lens colour:	Red

ELECTRICAL CHARACTERISTICS

Protection class:	II

MECHANICAL CHARATERISTIC

Mechanical lifetime:	500 000 cycles of operation
Weight:	0.033 kg

Tightening torque:	2 … 3 Nm (17.7 … 26.6 Lb-in)
Switching action:	Maintained

AMBIENT CONDITION

IK front protection:	IK03
IP front protection:	IP65
Shock resistance:	50g, 11ms (EN-IEC 60068-2-27)
Operating temperature:	– 25 °C … + 55 °C
Climate resistance:	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Vibration resistance:	5g f= 2…500Hz (EN-IEC 60068-2-6)


CERTIFICATE

Standards:	CSA C22-2, IEC EN 60947-1, IEC EN 60947-5-1, UL508
Conformities:	CE

OTHER

Housing material:	Plastic
Housing colour:	Black
max. number of switching elements:	6
Short Description:	Actuator, Ø 22.3 mm, Ø 29,5 mm, flush, illuminative, Red, Plastic, transparent, round, Silver, Metal, Maintained, IP65, IK03

Dimension drawings:



Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

eao:

10-1112.1279 45-290J.1000.111 51-423.036 704.403.0 45-1131.2190.000.101 704.042.418 82-4151.2133 82-5151.1134 82-6851.2000 10-2K12.1072 44-966.5 45-2134.1120.000 45-2530.1920.000 704.403.018 K14-131.221071 31-282.0252 61-1130.0 82-4151.1154 31-940 45-320.1E16 704.011.018 704.411.110KN 704.602.0 82-6551.1134 82-6561.1000 01-132.0252 17-030352 45-320.1E46 84-8511.5620 02-810.001