Push-in Y-connector
QSY-10

Part number: 153151



General operating condition

Data sheet

Feature	Value
Size	Standard
Nominal width	6.7 mm
Mounting position	Any
Design	Y-shape
Pack size	10
Structural design	Push-pull principle
Operating pressure for entire temperature range	-0.095 MPa ... 0.6 MPa
Operating pressure for entire temperature range	-0.95 bar ... 6 bar
Operating pressure for entire temperature range	-13.775 psi ... 87 psi
Temperature-dependent operating pressure	-0.095 MPa ... 1.4 MPa
Temperature-dependent operating pressure	-0.95 bar ... 14 bar
Temperature-dependent operating pressure	-13.775 psi ... 203 psi
Information on operating pressure	Water: max. 0.6 MPa at max. 50 °C
Operating medium	Compressed air as per ISO 8573-1:2010 [7:-:-] Water (liquid, ice-free)
Information on operating and pilot media	Operation with oil lubrication possible
Corrosion resistance class (CRC)	1 - Low corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	-10 °C ... 80 °C
Product weight	26 g
No. of outlets	2
No. of supply lines	1
Pneumatic connection 1	for pneumatic tubing outside diameter 10 mm
Pneumatic connection 2	for pneumatic tubing outside diameter 10 mm
Releasing ring color	Blue
Note on materials	RoHS-compliant
Housing material	PBT
Releasing ring material	POM
Material of tubing seal	NBR
Material of tube retaining claw	High-alloy stainless steel

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

DFM-63-100-P-A-KF NPQH-T-G38-Q8-P10 NPQP-D-Q4-S8-FD-P10 DSBC-50-20-D3-PPSA-N3 N-1/8-P-6 QSML-3 SPTE-V1R-Q3-V-2.5K VABM-L1-18W-G38-8-G DSBC-63-320-D3-PPVA-N3 PUN-H-4X0,75-TBL QS-1/2-16 NPQP-LQ-R18-Q8-FD-P10 QSLL-1/4-4 QSML-6 NPQP-LQ-R18-Q4-FD-P10 SNC-63 VBQF-U-G14-E DSBC-32-40-D3-PPVA-N3 DSBC-32-50-D3-PPVA-N3 DSBC-80-320-D3-PPVA-N3 NPQP-L-Q10-E-FD-P10 CRVZS-0.4 DSNU-12-60-P-A MSFW-110-50/60-DS NPQP-Y-R12-Q12-FD QH-1 1/2 DSBC-80-250-D3-PPSA-N3 NPQP-Y-Q6-E-FD-P10 QSLV-G1/4-6 QSS-8-F