


Item (Detail view)

2-conductor fuse disconnect terminal block with pivoting fuse holder; for 5 x 20 mm miniature metric fuse; 230 V; with blown fuse indication by LED







Item no.	2002-1611/1000-836	GTIN / EAN	4045454790042
Content	1 piece	Order unit	piece
Order quantity	50 piece	Increase in order quantity	(50, 100, 150, 200, ...)
Customer item no.		Customs Tariff no.	85369095990
Customs duty for the country of origin	CN	Available	-
List price	On request	Net price	On request
Availability	On request		

Note: Some items may not be available from your local WAGO company.
Please note that the quantities ordered in the shopping cart are rounded up to the PU (SPU).

RoHS ✓
Compliant

Articledetails | Approvals | Downloads/Certificates | Accessories

Description	2-conductor fuse disconnect terminal block with pivoting fuse holder; for 5 x 20 mm miniature metric fuse; 230 V; with blown fuse indication by LED
Remarks	**Safety information 1:** Electrical ratings are given by the fuse and blown fuse indication.

Item properties

Miscellaneous

Name	Value	Unit
Safety information 2	Leakage current in case of blown fuse: LED 2mA	
Packaging type	BOX	
Ratings per	IEC/EN 60947-7-3	
Rated voltage (III / 3) [V]	250	V
Rated impulse voltage (III / 3) [kV]	6	kV
Rated current [A]	6.3	A
Legend (ratings)	(III / 3) ≙ Overvoltage category III / Pollution degree 3	
Type of wiring	Front-entry wiring	
Total number of connection points	2	
Total number of potentials	1	
Number of levels	1	
Connection technology	Push-in CAGE CLAMP®	
Actuation type	Push-in	
Connectable conductor materials	Copper	
Nominal cross section	2.5 mm²	
Solid conductor	0.25 … 4 mm² / 22 … 12 AWG	
Solid conductor, push-in termination	0.75 … 4 mm² / 18 … 12 AWG	
Fine-stranded conductor	0.25 … 4 mm² / 22 … 12 AWG	
Fine-stranded conductor with ferrule, push-in termination, f	0.75 mm² / 18 AWG	
Strip length	10 … 12 mm / 0.39 … 0.47 Inch	
Width	6.2 mm / 0.244 Inch	
Height from upper-edge of DIN-35 rail	57.2 mm / 2.252 Inch	
Depth	66.1 mm / 2.602 Inch	
Design	horizontal	
Type of mounting	Carrier rail 35 x 15	
Marking level	Center/side marking	
Color	gray	
Insulating material	Polyamide 66 (PA 66)	
Fire load [MJ]	0.287	MJ
Weight [g]	13.65	g
Product Family	TOPJOB® S	
Main product function	Fuse term. block	
Product type	Function modules	

Upwards

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

WAGO:

859-798 2086-1107 2624-3502 855-3001/250-001 233-508 235-502 2606-3353 261-402 2787-2144 750-1405/040-000 750-638/025-000 759-302 236-506 859-354 769-131 769-428 2002-1207 2010-1205 236-424 260-105 852-1322 207-4301 2102-1204 2624-1312 2636-3108/020-000 751-9301 885-566 890-503 2636-1355 769-413