1-1586039-6 ✔ ACTIVE

VAL-U-LOK

TE Internal #: 1-1586039-6


Header, Plug, Wire-to-Board, 16 Position, 4.2 mm [.165 in] Centerline, Printed Circuit Board, UL 94V-2, Rectangular Power Connectors

View on TE.com >

Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors







Rectangular Power Connector Type: **Header**

Connector & Housing Type: **Plug**

Connector System: **Wire-to-Board**

Number of Positions: **16**

Centerline (Pitch): **4.2 mm [.165 in]**

Features

Product Type Features

Rectangular Power Connector Type	Header
Connector & Housing Type	Plug
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	16
PCB Mount Orientation	Vertical
Number of Power Positions	16
Number of Rows	2

Electrical Characteristics

Operating Voltage	600 VAC

Contact Features

Contact Layout	Inline, Matrix

Contact Mating Area Plating Material	Tin
Contact Current Rating (Max)	9 A
Contact Retention Within Housing	Without
Contact Type	Pin
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	2.03 µm[80 µin]

Termination Features

Termination Post & Tail Length	3.5 mm[.138 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Mating Alignment Type	Keyed
Mating Retention	With
Mating Alignment	With
PCB Mount Alignment	With
PCB Mount Retention	With
PCB Mount Retention Type	Boardlock
Mating Retention Type	Latch
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	4.2 mm[.165 in]
Housing Color	Natural
Housing Material	PA 66

Dimensions

Compatible Insulation Diameter (Max)	2.39 mm[2.39 in]
Connector Height	12.8 mm[.504 in]
PCB Thickness (Recommended)	.07 mm[1.78 in]
Product Width	9.75 mm[.384 in]
Product Length	34.8 mm[1.37 in]
Compatible Insulation Diameter Range	1.2 – 3.1 mm[.047 – .122 in]
Row-to-Row Spacing	4.2 mm[.165 in]

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]

Operation/Application

Circuit Application	Power

Identification Marking

Circuit Identification Feature	With

Industry Standards

CSA Rating	208567
UL Rating	Recognized
Compatible With Agency/Standards Products	CSA, UL
Compatible With Approved Standards Products	UL E28476
UL Flammability Rating	UL 94V-2
Glow Wire Rating	Standard Part - Not Glow Wire

Packaging Features

Packaging Quantity	135
Packaging Method	Box & Tray, Tray

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits

as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 1-794954-6
16P RCPT VAL-U-LOK V2




TE Part # 1-1969605-6
16P PM PLUG VAL-U-LOK PM GW



TE Part # 1-1969604-6
16P FH PLUG VAL-U-LOK FH GW

Customers Also Bought



TE Part #3-644695-6
06P MTA100 STR HDR RETENTIVE




TE Part #640900-1
05P UMNL PIN HDR ASSY 94VO



TE Part #3-1419108-6
RTD34012F




TE Part #1-794606-2
MICRO MNL RPT CNT STRP 30AU LF



TE Part #534998-5
10 MODIV VRT DR CE 100/125



TE Part #5-1879338-7
CPF 0603 102K 1% 50PPM 1K RL



TE Part #5-2176371-1
RQ 0603 15K4 0.1% 10PPM 5K RL



TE Part #9-146257-0
80 MODII HDR DRST B/A .100CL LF



TE Part #ANT-433-PW-QW
Antenna 1/4 Wave Whip 433MHz RG174

Documents

Product Drawings

16P VAL-U-LOK VRT HDR W/P V2

English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_1-1586039-6_B.3d_igs.zip

English

Customer View Model

ENG_CVM_1-1586039-6_B.3d_stp.zip

English

Customer View Model

ENG_CVM_1-1586039-6_B.2d_dxf.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TE Connectivity:

1393431-1 2005330-1 2377783-2 917696-1 CPF0402B37K4E1 CRGCQ2010J3K3 1-794222-0 141991-2 SBCHE154R7K U5254-000005-030PA 1-962915-1 1743455-2 175977-2 2-292161-3 2380312-2 936348-1 3631B101LL SMW73R0JT 3430B2F51RTDF MPT100C18RF SBCHE64R7K 3-1393225-0 650075-000 RH73H2A40MKTN ROX05SJ18R 2310537-1 2834055-1 TE50BR39J 1903112-2 1969656-1