

2071556-6 ✔ ACTIVE

TE Internal #: 2071556-6

General Purpose Power Relay, Monostable, .2 W Coil, 125 ohm Coil Resistance, UL Coil Insulation Class F, 5 VDC Coil Voltage, Power Relays

View on TE.com >

Relays & Contactors > Relays > Power Relays




Relay Type: **General Purpose Power Relay**

Coil Magnetic System: **Monostable**

Coil Power Rating DC: **.2 W**

Coil Resistance: **125 Ω**

Coil Special Features: **UL Coil Insulation Class F**

Features

Product Type Features

Relay Type	General Purpose Power Relay

Configuration Features

Coil Special Features	UL Coil Insulation Class F
Contact Arrangement	1 Form A SPST-NO
Contact Number of Poles	1

Electrical Characteristics

Coil Current	.04 A
Insulation Initial Dielectric Between Open Contacts	750 Vrms
Contact Limiting Making Current	10 A
Contact Limiting Short-Time Current	10 A
Contact Limiting Continuous Current	10 A
Insulation Initial Dielectric Between Adjacent Contacts	750 Vrms
Insulation Initial Dielectric Between Contacts & Coil	4000 Vrms
Insulation Initial Resistance	1000 MΩ

Contact Limiting Breaking Current	10 A
Coil Power Rating DC	.2 W
Coil Resistance	125 Ω
Coil Voltage Rating	5 VDC
Contact Current Rating	10 A
Contact Switching Load (Min)	100mA @ 5V
Contact Switching Voltage (Max)	250 VAC
Contact Voltage Rating	250 VAC

Body Features

Enclosure Type	Plastic Dust Cover
Primary Product Color	Black
Product Weight	5.8 g

Contact Features

Contact Plating Material	AgSnO
Contact Material	AgSnOInO

Termination Features

Relay Connection Type	PCB Termination
Terminal Configuration	Solder Pins

Mechanical Attachment

Product Mount Type	Printed Circuit Board

Dimensions

Insulation Clearance Between Contact & Coil	7 mm[.28 in]
Insulation Creepage Between Contact & Coil	11 mm[.43 in]
Product Width	10.2 mm[.401 in]
Product Length	18.2 mm[.716 in]
Product Height	14.8 mm[.582 in]

Usage Conditions

Environmental Category of Protection	RTII
Environmental Ambient Temperature (Max)	85 °C[185 °F]
Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]

Operation/Application

Current Type	DC

Coil Magnetic System	Monostable

Packaging Features

Packaging Method	Tray/Box

Other

Length Class (Mechanical)	16 – 20 mm
Environmental Ambient Temperature Class	70 – 85 °C
Height Class (Mechanical)	14 – 15 mm
Coil Power Rating Class	.15 – .2 W
Width Class (Mechanical)	10 – 12 mm
Contact Current Class	10 A

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 2071556-9
OJS-SH-105HMF,00000

Customers Also Bought



TE Part #T4141012041-000
M12,REAR MOUNTING,FEMALE,A CODE,4P



TE Part #3-1437559-7
MTL206N=(MSTL) SW TOG LOCKING



TE Part #9-1415029-1
PB114024



TE Part #350786-1
02P UMNL HDR ASSY 94VO




TE Part #1623232-1
CRG0805 1% 470R



TE Part #1623158-1
CRG0805 1% 22R



TE Part #3-2176337-4
CRGCQ 0402 5K6 1%



TE Part #2071556-2
OJS-SS-124HEF,00000

Documents

CAD Files

3D PDF

3D

Customer View Model
ENG_CVM_CVM_2071556-6_A1.2d_dxf.zip

English

Customer View Model
ENG_CVM_CVM_2071556-6_A1.3d_igs.zip

English

Customer View Model
ENG_CVM_CVM_2071556-6_A1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages

OJS_10A/16A.STD

English

OJS Power Miniature PCB 10A / 16A Relays

English

Product Specifications

Definitions General Purpose Relays

English

Agency Approvals

UL

English

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TE Connectivity:

2834055-1 CPF0402B37K4E1 SBCHE64R7K U5254-000005-030PA 2380312-2 936348-1 SBCHE154R7K 175977-2 2-292161-3 2005330-1 1903112-2 SMW73R0JT 141991-2 2377783-2 917696-1 CRGCQ2010J3K3 TE50BR39J 1-794222-0 1-962915-1 3-1393225-0 3430B2F51RTDF 3631B101LL 2310537-1 1393431-1 1969656-1 650075-000 MPT100C18RF RH73H2A40MKTN ROX05SJ18R 1743455-2