CUI Devices is now Same Sky! Learn More

MODEL: UJC-H-G-SMT-P6-TR | DESCRIPTION: USB RECEPTACLE

FEATURES

- USB Type C receptacle
- power only
- reflow solder compatible
- tape & reel packaging



RoHS


SPECIFICATIONS

parameter	conditions/description	min	typ	max	units
USB standard	power only				
rated input voltage				30	Vdc
rated input current	as per EIA-364-70, Method B power pins collectively (A1, A4, A9, A12, B1, B4, B9, B12) VCONN pins individually (A5, B5) all other signal pins individually			 3.0 1.50 0.25	 A A A
contact resistance[1]	between terminals and mating plug			40	mΩ
insulation resistance	at 100 Vdc between adjacent contacts	100			MΩ
voltage withstand	between adjacent contacts for 1 minute	100			Vac
insertion force	at a rate of 30 cycles/min	5		20	N
withdrawal force	at a rate of 30 cycles/min	8		20	N
life	at a rate of 500 cycles per hour		10,000		cycles
operating temperature		-25		85	°C
flammability rating	UL94V-0				
RoHS	yes				

Note: 1. When measured at 20 mV / 100 mA.


SOLDERABILITY

parameter	conditions/description	min	typ	max	units
reel storage	at 20~30°C, 40~75% humidity				
reflow soldering	see reflow profile			260	°C




MECHANICAL DRAWING

units: mm
tolerance:
X.X ±0.30 mm
X.XX ±0.20 mm
X.XXX ±0.10 mm
unless otherwise specified




DESCRIPTION	MATERIAL	PLATING/COLOR
housing	PA9T (UL94V-0)	black
contact	C2680	contact area: 1 µ" gold over 50 µ" nickel solder area: 1 µ" gold over 50 µ" nickel
mid plate	SUS301	clear
front shell	SUS304	nickel



MECHANICAL DRAWING (CONTINUED)

units: mm
PCB tolerance: ±0.05 mm

PIN CONNECTIONS			
PIN	SIGNAL NAME	PIN	SIGNAL NAME
A5	CC1	B12	GND
A9	VBUS	B9	VBUS
A12	GND	B5	CC2





Recommended PCB Layout
Top View


PACKAGING

units: mm

Reel Size: Ø330
Reel QTY: 1,000 pcs per reel
Carton Size: 330 x 330 x 320 mm
Carton QTY: 14,000 pcs







REVISION HISTORY

rev.	description	date
1.0	initial release	07/29/2024
1.01	CUI Devices rebranded to Same Sky	09/12/2024

The revision history provided is for informational purposes only and is believed to be accurate.

Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Same Sky:

CFM-A238BF-270-651 TBL004V-508-02BE-2GY SJ1-3535N TB007-508-02BE CMC-5042PF-AC CPM-2H DS04-254-2-02BK-SMT PJ-047BH CBT-09427-SMT-TR CMM-2718AT-42316-TR CPI-1375IC-80T SJ-2523-SMT-TR SJ-43516-SMT-TR-PI CDM1222-12A-FW-F16-050-67 CMI-9653S-SMT-TR CMP-5247TF-K CPT-1117-83-SMT-TR PJ-067B CFM-2507CF-0140-313 DS01C-254-S-03BE PR4-5V-450-1A TBP01R1-508-14BE CFM-6015V-239-292-20 CMA-4544PF-W HSE-B20350-NP PJ-202AH UJ32-C-H-G-L1-MSMT-TR CFM-2510B-0130-275 PJ-058AH TBP02P1-381-10BE