RH100-38.400-15-F-2030-EXT-TR-NS1


SPECIFICATIONS

PARAMETER	VALUE
NOMINAL FREQUENCY	38.400 MHz
MODE OF OSCILLATION	Fundamental
FREQUENCY TOLERANCE AT 25°C	±20 ppm max
FREQUENCY STABILITY OVER TEMPERATURE	±30 ppm max
OPERATING TEMPERATURE RANGE	-40°C to +85°C
STORAGE TEMPERATURE RANGE	-55°C TO +125°C
AGING	±2 ppm first year max
LOAD CAPACITANCE	15 pF
EQUIVALENT SERIES RESISTANCE	40 Ω max
SHUNT CAPACITANCE	3.5 pF max
DRIVE LEVEL	300 µW max
INSULATION RESISTANCE	500 MΩ min




Photo is not actual part

MECHANICAL SPECIFICATION



Notes:
- Pins 2 and 4 are connected-together and to the metal cover for Case GND.
- According to ceramic base availability the Chamfer location could be on a different pin. However, the Chamfer's location does not influence the electrical performance of the crystal.

CARRIER TAPE DIMENSIONS




NOTE: REFER TO EIA-481 FOR DIMENSIONS

PACKAGING

178 mm REEL DIAMETER
8 mm TAPE WIDTH, 4 mm PITCH
QUANTITY: 3000 PIECES PER REEL

IN ACCORDANCE WITH EIA-481

REFLOW PROFILE



Reflow profile		
Temperature Min Preheat	T_{SMIN}	125°C
Temperature Max Preheat	T_{SMAX}	150°C
Time (T_{SMIN} to T_{SMAX})	t_S	30-180 sec.
Temperature	T_L	217°C
Peak Temperature	T_P	260°C
Ramp-up rate	R_{UP}	3°C/sec max.
Ramp-down rate	R_{DOWN}	6°C/sec max.
Time within 5°C of Peak Temperature	t_P	10 sec.
Time t[25°C] to Peak Temperature	t[25°C] to Peak	480 sec.
Time	t_L	60-150 sec.

ENVIRONMENTAL

PARAMETER	VALUE
MOISTURE SENSITIVITY LEVEL	1
RoHS	Compliant
REACH SVHC	Compliant
HALOGEN-FREE	Compliant
ESD CLASSIFICATION LEVEL	N/A
TERMINATION FINISH	Au

MARKING

R38.40
xxNDyw

x – Internal Production ID code
y – Year code
w – Week code

YEAR CODE	
Year	Code
2019	9
2020	0
2021	1
2022	2
2023	3
2024	4
2025	5
2026	6
2027	7
2029	8
2029	9

ALPHA WEEK CODE TABLE					
Week	Code	Week	Code	Week	Code
1	a	19	s	37	K
2	b	20	t	38	L
3	c	21	u	39	M
4	d	22	v	40	N
5	e	23	w	41	O
6	f	24	x	42	P
7	g	25	y	43	Q
8	h	26	z	44	R
9	i	27	A	45	S
10	j	28	B	46	T
11	k	29	C	47	U
12	l	30	D	48	V
13	m	31	E	49	W
14	n	32	F	50	X
15	o	33	G	51	Y
16	p	34	H	52	Z
17	q	35	I		
18	r	36	J		

APPROVAL

DRAWN BY	CP, August 14, 2017
APPROVED BY	JI, August 14, 2017
REVISION	A, Initial Release
	B, AR, January 14, 2022 Updated the Current Revision Levels

Raltron Electronics / RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided only for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.

Copyright © 2016, Raltron Electronics / RAMI Technology USA, LLC. All rights reserved. No part of this document may be reproduced in any form without the prior written permission of Raltron Electronics / RAMI Technology USA, LLC.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Raltron Electronics:

CO4305-20.000-EXT-T-TR AS-20.000-20 AS-20.000-20-SMD-TR H130A-25.000-18-F-2030-EXT-TR
RH100-16.384-16-2020-EXT-TR-NS1 AS-10.000-18-SMD CL2520-156.250-1.8-20-X-T-TR-N1
RH100-40.000-10-F-2020-EXT-TR RTXE-104ED333-C-12.800-TR AS-24.000-18 AS-3.6864-18-SMD
H130A-24.000-18-2030-EXT-TR H130A-8.000-8-2030-TR RH100-12.000-18-2020-TR
CO4605-125.000-EXT-T-TR H130B-16.000-18-3030-EXT-TR RH100-40.000-18-F-2030-EXT-TR-NS1
AS-14.7456-20-SMD-TR CO4305-10.000-EXT-T-TR CO4605-66.000-EXT-T-TR H130B-12.000-18-3030-TR
RH100-16.000-16-5050-TR RH100-48.000-8-F-1015-EXT-TR TT-SMDC-3.6864-S-TR
R2016-48.000-7-F-1020-TR-NS1 AS-27.000-20-F AS-8.000-18 R2520-16.384-10-2030-EXT-TR-NS1
RH100-20.000-18-2020-TR RH100-48.000-10-F-1015-EXT-TR