Rittal – The System.

Faster – better – everywhere.



SK 3120.200
Speed Control

State: 10/4/2024 (Source: rittal.com/us-en)

SK 3120.200 - Speed Control For filter fans and air-air heat exchangers

Temperature-dependent speed control to reduce noise and save energy in part-load operation.

Features

Model No.	SK 3120.200
Product description	Temperature-dependent speed control for noise reduction and energy conservation in part-load operation.
Technical specifications	For mounting on a 35 mm support rail EN 50 022 Phase cross-over with microcontroller Maximum fan output 300 W or 2 A
Supply includes	Speed Control NTC sensor, length 1.80 m
Speed	100 %
Note	Only suitable for use with single-phase AC motors and equipment Not suitable for EC motors
Dimensions	Width: 105 mm Height: 90.5 mm Depth: 60.2 mm Width: 4.13 ″ Height: 3.56 ″ Depth: 2.37 ″
Setting range	20 °C...55 °C 68 °F...131 °F
Rated operating voltage	100 V - 230 V
Packaging unit	1 pc(s).
Weight/packaging unit	0.36 kg 0.8 lb.
Net weight	0.359
Gross weight	0.39

Features

Customs tariff number	90321020
EAN	4028177631441
E-Number Sweden	E7239754
ETIM 8	EC000256
ETIM 7.0	EC000256
ECLASS 8.0	27142320

Approvals

Approvals	UR
Certificates	EAC
Explanations	Declaration of conformity Declaration of conformity UK

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

RITTAL:

2092500 2589000 7220600 1936200 2482600 7115000 7856025 2464000 4945000 2473010 3212230
6002000 7119140 1540000 2388650 2410111 3144000 7152035 1564800 2433510 2541235 3177000
8619330 2500650 3201300 3684900 7030090 8617800 2533000 3685271