


Jul.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window


	△数 COUNT	訂正事項 DESCRIPTION OF REVISIONS	擔當 BY	檢圖 CHKD	年月日 DATE
1	1	RE-6-1150	K.I.Y	L.S.M	18. 07. 04
2	6	RE-6-1435	K.Y.H	L.S.M	19. 06. 19
3	1	RE-6-1579	K.I.Y	L.S.M	20. 01. 23

HRS DRAWING FOR REFERENCE












RECOMMENDED LAND PATTERN (FREE)


(PCB THICKNESS t=1.6mm)





ENGAGEMENT FIGURE (2:1)





NOTE 1. 1PACK CONTAINS 330PCS.

2. ( )DIMENSIONS ARE ONLY REFERENCE.

△3 3. UL(File No. E132750) AUTHORIZATION ARTICLE.
C-UL(File No. E132750) AUTHORIZATION ARTICLE.

NO.	MATERIAL	FINISH,REMARKS
1	PBT	UL94V-0, BLACK
2	BRASS	TIN PLATING 1μm MIN, OVER NICKEL 0.5μm MIN

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
	CHOI 18.03.02 J.S	CHOI 18.03.02 J.S	LIM 18.03.02 S.M	KANG 18.03.02 T.S	ENG 20. 02. 12 DEPT

SCALE	DRAWING NO.	PART NO.
4:1	EDC3-632472	DF51KB-3P-2DS(800)
UNITS mm	HRS HIROSE KOREA CO.,LTD.	CODE NO CL 6652-0062-6-800 1/1

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Hirose Electric:

DF17(3.0)-40DS-0.5V(57) DF57AH-5S-1.2C DF62C-4S-2.2C FH35C-19S-0.3SHW(50) FX18-60S-0.8SH HDE-CTH(10) RM15TP-2PA(81) DF33C-4S-3.3C DF40C-50DP-0.4V(51) DF52-4P-0.8C ZE05-24DP-2H DF65-4P-1.7V(21) FH41-50S-0.5SH(28) RM15TRH-10PH(81) ZE05H-4P-2V(A) RM12BRD-2PH(81) FH41-30S-0.5SH(05) DF59M-2224PCF FH72-21S-0.3SHW ZH05-20DP-HU(B) BM29B0.6-4DS/2-0.35V(51) DF36A-25P-SHL FX18-80S-0.8SH DF19A-3032SCFA(41) DF22A-1416SCFA FX8-120S-SV(22) GT8E-6S-HU ZE05H-12DP-2H ZE064W-8DP-HU/R(A) DF11-16DP-2DSA(24)