TECH PUBLIC
台舟电子

TPESD5V0LS-SFYL

Ultra-Low Capacitance 1-Line ESD Protection

www.sot23.com.tw

Features

- Ultra small package: 0.6x0.3x0.3mm
- Ultra low capacitance:0.3pF typical
- Ultra low leakage: nA level
- Low operating voltage: ±5V
- Low clamping voltage
- 2-pin leadless package
- Complies with following standards:
- – IEC 61000-4-2 (ESD) immunity test
  Air discharge: ±20kV
  Contact discharge: ±15kV
- – IEC61000-4-5 (Lightning)3.8A (8/20μs)
- RoHS Compliant
- Lead Finish: NiPdAu

Reference:PESD5V0LS-SFYL


Mechanical Characteristics

- Package: DFN0603-2 (0201)
- Lead Finish: Matte Tin
- Case Material: “Green” Molding Compound.
- Moisture Sensitivity: Level 3 per J-STD-020
- Terminal Connections: See Diagram Below
- Shipping Qty :15000pcs Or 10000/7Inch Tape & Reel

Applications

- Cellular Handsets & Accessories
- Digital Visual Interface (DVI)
- Display Port
- MDDI Ports
- USB Ports

Dimensions and Pin Configuration



Marking: Q

Absolute Maximum Ratings (Tamb=25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20μs)	Ppk	70	W
Peak Pulse Current (8/20μs)	Ipp	3.8	A
ESD per IEC 61000−4−2 (Air) ESD per IEC 61000−4−2 (Contact)	V_{ESD}	±20 ±15	kV
Operating Temperature Range	T_J	−55 to +125	°C
Storage Temperature Range	Tstg	−55 to +150	°C

Electrical Characteristics (TA=25°C unless otherwise specified)

Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	V_{RWM}			5	V	
Breakdown Voltage	V_{BR}	6.5	7.5	9.0	V	I_T = 1mA
Reverse Leakage Current	I_R			0.08	uA	V_{RWM} = 5V
Clamping Voltage	V_C			14	V	Ipp=1A(8x 20us pulse)
	V_C		16	20	V	Ipp=4A(8x 20us pulse)
Junction Capacitance	C_J		0.3		pF	VR = 0V, f = 1MHz

Typical Performance Characteristics (T_A=25°C unless otherwise Specified)

Fig1. 8/20μs Pulse Waveform




Fig2. ESD Pulse Waveform (according to IEC 61000-4-2)






Fig3. Power Derating Curve




DFN0603-2 Package Outline Drawing (0201)



SYM	DIMENSIONS		
	MILLIMETERS		
	MIN	NOM	MAX
A	0.230	0.300	0.330
A1	0.000	0.020	0.050
b	0.215	0.245	0.275
c	0.120	0.150	0.180
D	0.550	0.600	0.650
e	0.355 BSC		
E	0.250	0.300	0.350
L	0.160	0.190	0.220
h	0.079 BSC		

Suggested Land Pattern



SYM	DIMENSIONS	
	MILLIMETERS	INCHES
X	0.30	0.012
Y1	0.25	0.010
Y2	0.15	0.006
Y3	0.40	0.016
Z	0.65	0.026

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TECH PUBLIC:

ESD5B5.0ST1G-P FDC6301N-TP TPADM809LAKSZ TPADM809SAKSZ TPDMG6602SVT DDTA143ZCA IRFR2405TRPBF-TP QM3003J-TP TPSPX3819M5-L-3-3 DMP6350S TPS3809L30DBVR-TP TPS7B6950DBVR-TP LTH7 TPAPX809S-31SA TPB1A30-123 TPGC12C-1 BV15C TPESD0402G08V TPESD0504S6-A TPWSB5557Z FDMS7670AS-TP SN7002W TPB05A40-323 TPESD5311N SI3932DV TPZVN3320FTA TPZXMP3A13FTA BSN20W TPD1213A-02SM TPFMMT493