Push-in fitting
CQ-1/2-15H

Part number: 177708



General operating condition

Data sheet

Feature	Value
Nominal width	10 mm
Type of seal on screwed plug	Sealing ring
Mounting position	Any
Pack size	1
Structural design	Push-pull principle
Operating pressure for entire temperature range	-0.95 bar ... 7 bar
Temperature-dependent operating pressure	-0.95 bar ... 15 bar
Operating medium	Compressed air as per ISO 8573-1:2010 [7:-:-]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364 zone III
For use in the food industry	See supplementary material information
Ambient temperature	-25 °C ... 70 °C
Nominal tightening torque	2.5 Nm
Tolerance for nominal tightening torque	± 10%
Product weight	14 g
Pneumatic connection 1	External thread G1/2
Pneumatic connection 2	Push-in sleeve CQ-15
Note on materials	RoHS-compliant
Housing material	POM
Releasing ring material	POM

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

NPQP-LQ-R18-Q8-FD-P10 NPQP-Y-R12-Q12-FD VABM-B10-25S-G38-10 VABM-B10-25S-G38-6-P3 DSBC-80-20-D3-PPSA-N3 QS-1/2-16 QS-10H-6 QSY-6H-4 153307 NPQH-T-Q14-E-P10 NPQP-LQ-R18-Q4-FD-P10 QSF-1/4-8-B QS-1/8-8-I QSF-3/8-8-B QSS-8-F VBQF-U-G14-E 153367 NPQP-Y-Q6-E-FD-P10 QSLL-G1/2-12 153031 153151 SASC-P4-A-M8-A 153269 NPQP-D-Q4-S8-FD-P10 QSML-6 HGL-1/8-QS-6 NPQP-L-Q10-E-FD-P10 NPQP-T-Q8-E-FD-P10 SGS-M10X1,25 CRVZS-0.4