

NC6MP-BAG

6 pole male receptacle, solder contacts, black metal housing, silver contacts

Smallest available traditional style metal panel mount connector with large solder cups for ease hard wiring.

Features & Benefits

- Smallest available hard wiring receptacles with large solder cups
- Compatible with Cannon XLB2*31, XLB2*32

All rights reserved / 07.08.2024

NEUTRIK

Technical Information

Product	
Title	NC6MP-BAG
Connection Type	XLR
Gender	male

Electrical	
Capacitance between contacts	≤ 7 pF
Contact resistance	≤ 5 mΩ
Dielectric strength	1,5 kVdc
Insulation resistance	> 10 GΩ (initial)
Rated current per contact	7,5 A
Rated voltage	< 50 V

Mechanical	
Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Wiresize	max. 1.0 mm²
Wiresize	max. 18 AWG
Wiring	Solder contacts
Locking device	Latch lock
Mounting direction	Front mounting
Chassis shape	P

All rights reserved / 07.08.2024

NEUTRIK

Material

Contact plating	2 µm Ag over 2 µm Ni
Contacts	Brass (CuZn39Pb3)
Insert	Polyamide (PA 6.6 30 % GR)
Locking element	Steel Ck67
Shell	Zinc diecast (ZnAl4Cu1)
Shell coating	Black KTL

Environmental

Flammability	UL 94 HB
Standard compliance	IEC 61076-2-103
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C

All rights reserved / 07.08.2024

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

NEUTRIK:

NAOBO NC5FAH NE8FBH-C5-LED NBB75DFGX NC10MXX-14-B NE8FBH NYS373-2 NP3RX-BAG MC8 NC3FAH-1 NCJ6FI-H-0 NC4FP-1 NKTT-1BL NRJ-NUT-R NA3MP NC3FD-LX NC3MXX-14-D XXR-9 NADB9FF NBNC75BFG7X NC4FX-TOP NC5MBV NCJ6FI-V NKE6S-3-WOC NC3FD-LX-HA NC3FDM3-H NE8FDV-Y110-B NE8FDY-C6 NF2D-2 NC3FAV2-0