
Inductive sensor

NBB10-30GM40-Z0



- 10 mm flush
- 2-wire DC

Dimensions



Technical Data


General specifications		
Switching function		Normally open (NO)
Output type		Two-wire
Rated operating distance	s_n	10 mm
Installation		flush
Output polarity		DC
Assured operating distance	s_a	0 ... 8.1 mm
Actual operating distance	s_r	9 ... 11 mm typ.
Reduction factor r_{Al}		0.3
Reduction factor r_{Cu}		0.25
Reduction factor r_{304}		0.7
Output type		2-wire
Nominal ratings		
Operating voltage	U_B	5 ... 60 V
Switching frequency	f	0 ... 150 Hz
Hysteresis	H	1 ... 10 typ. 5 %
Reverse polarity protection		reverse polarity tolerant

Release date: 2024-05-27 Date of issue: 2024-05-28 Filename: 088210_eng.pdf

Technical Data

Short-circuit protection		pulsing
Voltage drop	U_d	≤ 5 V
Operating current	I_L	2 ... 100 mA
Lowest operating current	I_m	2 mA
Off-state current	I_r	0 ... 0.5 mA typ.
Time delay before availability	t_v	≤
Switching state indicator		all direction LED, yellow
Functional safety related parameters		
$MTTF_d$		1710 a
Mission Time (T_M)		20 a
Diagnostic Coverage (DC)		0 %
Compliance with standards and directives		
Standard conformity		
Standards		EN IEC 60947-5-2
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CCC approval		Certified by China Compulsory Certification (CCC)
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Connection type		cable PVC , 2 m
Core cross section		0.34 mm^2
Housing material		brass, nickel-plated
Sensing face		PBT
Degree of protection		IP67
Cable		
Cable diameter		4.8 mm ± 0.2 mm
Bending radius		> 10 x cable diameter
Dimensions		
Length		40 mm
Diameter		30 mm

Connection



Release date: 2024-05-27 Date of issue: 2024-05-28 Filename: 088210_eng.pdf

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

PEPPERL+FUCHS:

24772 CCN15-30GS60-E2-V1 NBB1-4GM22-E2 34441 NBB4-12GM50-A2-V1 NBB5-18GM50-A0
OBR2500-12GM40-E5 OBR5000-18GK40A-E2 OBR12M-R100-2EP-IO-V31-L OQT150-R100-2EP-IO-V31-L
WCS3-MH1 UB2000-F42-E6-V15 KLR-C02-2,2-2,0-K70 NBB2-12GM50-E2 NBB5-18GM50-E2
UBE800-F77-SE2-V31 NBB2-8GM40-E0-V1 NBB2-12GM50-A2-V1 GLV30-8-2500/47/73C MH4-2057
NBB0.8-5GM25-E2 134143 NBB0.8-4M25-E0 BF18 NBB8-18GM50-E0 OBD450-18GK40A-E2
OQT150-R101-2EP-IO-V31 S1SD-1AI-1U.1 UB800-18GM40-I-V1 114642