Plastic tubing
PUN-H-6X1-TGE

Part number: 8048689



General operating condition

Data sheet

Feature	Value
Outside diameter	6 mm
Bending radius relevant for flow rate	26 mm
Inside diameter	4 mm
Min. bending radius	10 mm
Application note	TPE-U Ether based
Tubing characteristics	Suitable for energy chains
Operating pressure for entire temperature range	-0.095 MPa ... 0.6 MPa
Operating pressure for entire temperature range	-0.95 bar ... 6 bar
Operating pressure for entire temperature range	-13.775 psi ... 87 psi
Temperature-dependent operating pressure	-0.095 MPa ... 1 MPa
Temperature-dependent operating pressure	-0.95 bar ... 10 bar
Temperature-dependent operating pressure	-13.775 psi ... 145 psi
Information on operating pressure	Water: temperature-dependent operating pressure, see diagram, max. 0.3 MPa at 0 - 60 °C
Certification	German Technical Control Board (TÜV)
Certificate issuing authority	B 013277 0506 00
Operating medium	Compressed air as per ISO 8573-1:2010 [7:-:-] Water (liquid, ice-free)
Material fire test	UL94 HB
LABS (PWIS) conformity	VDMA24364-B2-L
Suitability for the production of Li-ion batteries	Metals with more than 1% by mass of copper, zinc or nickel by mass are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils
Cleanroom class	Statically installed element, no meaningful evaluation possible according to ISO 14644-1
For use in the food industry	See supplementary material information
Ambient temperature	-35 °C ... 60 °C
Product weight by length	0.0183 kg/m
Pneumatic connection	For plug connection outside diameter 6 mm For barbed fitting, inside diameter 4 mm, with union nut
Color	Translucent yellow
Shore hardness	D 52 +/-3
Note on materials	RoHS-compliant
Material of pneumatic tubing	TPE-U(PU)

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

DSBC-32-40-D3-PPVA-N3 NPQH-D-Q12-Q8-P10 NPQP-D-R38-Q10-FD-P10 QSL-12 QSLV-G1/4-6
SPTW-P16R-G14-A-M12 NPQP-D-R14-Q10-FD-P10 VABM-B10-25S-G38-6 QSL-1/4-4 SEA-3GS-M8-S
VABM-L1-14W-G14-4-GR 153034 DFM-63-100-P-A-KF DSBC-40-160-D3-PPSA-N3
DSBC-63-320-D3-PPVA-N3 HGL-1/8-B QS-G1/8-6-I QS-G3/8-12 QSLV-G1/2-12-I
DSBC-32-50-D3-PPVA-N3 NPQH-D-Q14-E-P10 NPQH-D-S14-Q8-P10 NPQH-T-G38-Q8-P10
VABM-B10-25S-G38-4-P3 VABM-L1-10HW-G18-4-GR VABM-B10-20S-G14-6 VABM-L1-18S-G38-10
DSBC-40-50-D3-PPSA-N3 DSBC-50-20-D3-PPSA-N3 QSLV-G1/8-8