YASMEEN-35-W

~36° spot beam



SPECIFICATION:

Dimensions	Ø 35.0 mm
Height	18 mm
Fastening	socket
ROHS compliant	yes

MATERIALS:

Component	Type	Material	Colour	Finish	Length (mm)
YASMEEN-35-W	Single lens	PMMA	clear	gloss	
YASMEEN-35-HLD-B	Holder B	PC	black		
YASMEEN-35-HLD-B-WHT	Holder B	PC	white		


LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


ORDERING INFORMATION:


Component	Qty in box	MOQ	MPQ	Box weight (kg)
C18520_YASMEEN-35-W	840	120	60	8.5
Assembly				
CP19222_YASMEEN-35-W-B-WHT	780	120	60	9.6
CP18525_YASMEEN-35-W-B	780	120	60	10.1

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

CP18525_YASMEEN-35-W-B
CP19222_YASMEEN-35-W-B-WHT







INDEX	PART	TYPE	QTY	MATERIAL	COLOUR/COATING	ASSEMBLY CODES
1	C18520_YASMEEN-35-W	LENS	1	PMMA	CLEAR	
2	HOLDER B	HOLDER	1			
	C18522_YASMEEN-35-HLD-B			PC	BLACK	CP18525_YASMEEN-35-W-B
	C19219_YASMEEN-35-HLD-B-WHT			PC	WHITE	CP19222_YASMEEN-35-W-B-WHT

MECHANICAL DRAWING

PRODUCT YASMEEN-35-W

LEDiL

Plastic moulding general tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing. Silicone moulding general tolerances according to ISO 3302-1 Class M3 and applies if not otherwise shown in the drawing.


FIRST ANGLE PROJECTION:


This drawing is the property of LEDiL Oy. It may not be copied or otherwise distributed without prior written permission from LEDiL Oy.


SCALE 2:1 | WEIGHT - | A3 | SHEET 1/1


Notes

PCB or heatsink level.
LED location
Ensure LED fitting from a product specific 3D model available from www.ledil.com
For more details about installation please see LEDiL Installation Guide on www.ledil.com









PART	TYPE	MATERIAL	COLOR / COATING
C18520_YASMEEN-35-W	LENS	PMMA	CLEAR

MECHANICAL DRAWING

PRODUCT YASMEEN-35-W

LEDiL

Plastic moulding general tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing. Silicone moulding general tolerances according to ISO 3302-1 Class M3 and applies if not otherwise shown in the drawing.

FIRST ANGLE PROJECTION:

This drawing is the property of LEDiL Oy. It may not be copied or otherwise distributed without prior written permission from LEDiL Oy.

SCALE 2:1 | WEIGHT - | A3 | SHEET 1/1

Notes

PCB or heatsink level.
LED location
Ensure LED fitting from a product specific 3D model available from www.ledil.com
For more details about installation please see LEDiL Installation Guide on www.ledil.com

See also our general installation guide: www.ledil.com/installation_guide


LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

CITIZEN

LED	CLU7L3
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	32.0° / 46.0°
Efficiency	90 %
Peak intensity	3.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
C19425_SOCKET-B-35-N	






Light distribution files

CITIZEN

LED	CLU7R3
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	34.0° / 52.0°
Efficiency	91 %
Peak intensity	2.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
C19424_SOCKET-B-35-M	






Light distribution files

CITIZEN

LED	CLU7S3
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	34.0° / 50.0°
Efficiency	91 %
Peak intensity	2.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
C19425_SOCKET-B-35-N	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):


SAMSUNG

LED	LC010C G2
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	29.0° / 49.0°
Efficiency	85 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:

BJB: 47.360.1020






Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

bridgelux

LED	V10 Gen 8-9
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	38.0° / 61.0°
Efficiency	87 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




Bender Wirth: 634b Bayonet35L

Light distribution files

bridgelux

LED	V6 HD Gen 8
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	37.0° / 56.0°
Efficiency	91 %
Peak intensity	2.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




Bender Wirth: 634c Bayonet35L

Light distribution files

bridgelux

LED	Vesta DTW 6mm
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	36.0° / 56.0°
Efficiency	89 %
Peak intensity	2.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Bender Wirth: 652b Bayonet35L


Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

bridgelux

LED	Vesta DTW 9mm (4W/6W/12W)
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	35.0° / 58.0°
Efficiency	89 %
Peak intensity	2.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




Bender Wirth: 652b Bayonet35L

Light distribution files

CITIZEN

LED	CLL02x/CLU02x (LES10)
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	36.0° / 59.0°
Efficiency	85 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




BJB: 47.360.1020

Light distribution files

CITIZEN

LED	CLU700/701/702/703
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	36.0° / 54.0°
Efficiency	86 %
Peak intensity	2.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



BJB: 47.360.1020

Light distribution files


LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

CITIZEN

LED	CLU7A2/7A3
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	34.0° / 48.0°
Efficiency	89 %
Peak intensity	3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

BJB: 47.360.1020




Light distribution files

CITIZEN

LED	CLU7B2
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	34.0° / 48.0°
Efficiency	89 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	


BJB: 47.360.1020



Light distribution files

CITIZEN

LED	CLU7L3
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	33.0° / 46.0°
Efficiency	88 %
Peak intensity	3.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
C19425_SOCKET-B-35-N	




Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

CITIZEN


LED	CLU7S3
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	32.0° / 48.0°
Efficiency	88 %
Peak intensity	3.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
C19425_SOCKET-B-35-N	



Light distribution files

CREE LEDs


LED	CHA0304
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	34.0° / 48.0°
Efficiency	89 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
BJB: 47.360.1020	



Light distribution files

CREE LEDs

LED	CHA0410
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	33.0° / 48.0°
Efficiency	89 %
Peak intensity	3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
BJB: 47.360.1020	




Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

CREE LEDs

LED	CHA0612
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	34.0° / 52.0°
Efficiency	88 %
Peak intensity	2.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





BJB: 47.360.1020

Light distribution files

CREE LEDs

LED	XM-L RGBW (XMLDCL HD)
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	26.0° / 45.0°
Efficiency	90 %
Peak intensity	4.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	






BJB: 47.360.1010

Light distribution files

LUMILEDS

LED	LUXEON CX Plus CoB - HD S01H4
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	36.0° / 52.0°
Efficiency	91 %
Peak intensity	2.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Bender Wirth: 634c Bayonet35L


Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

LUMILEDS

LED	LUXEON CX Plus CoB - HD S02H6
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	37.0° / 56.0°
Efficiency	90 %
Peak intensity	2.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




Bender Wirth: 634c Bayonet35L

Light distribution files

LUMILEDS

LED	LUXEON CX Plus CoB - HD S04H9
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	36.0° / 60.0°
Efficiency	88 %
Peak intensity	2.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




Bender Wirth: 634a Bayonet35L

Light distribution files

LUMILEDS

LED	LUXEON CX Plus CoB L04 / L05 (Gen2)
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	39.0° / 62.0°
Efficiency	78 %
Peak intensity	1.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



BJB: 47.360.1040


Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

LUMILEDS

LED	LUXEON CX Plus CoB S01 (Gen2)
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	36.0° / 54.0°
Efficiency	91 %
Peak intensity	2.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




Bender Wirth: 634c Bayonet35L

Light distribution files

LUMINUS

LED	CXM-3
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	35.0° / 48.0°
Efficiency	91 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




Bender Wirth: 634a Bayonet35L

Light distribution files

LUMINUS

LED	CXM-3
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	35.0° / 48.0°
Efficiency	91 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Bender Wirth: 634a Bayonet35L


Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

LUMINUS

LED	CXM-4
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	34.0° / 50.0°
Efficiency	91 %
Peak intensity	2.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




Bender Wirth: 634a Bayonet35L

Light distribution files

LUMINUS

LED	CxM-6 (13.5x13.5)
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	32.0° / 50.0°
Efficiency	89 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




BJB: 47.360.1020

Light distribution files

LUMINUS

LED	CxM-6 (13.5x13.5)
Ordering code	CP19222_YASMEEN-35-W-B-WHT
FWHM / FWTM	28.0° / 46.0°
Efficiency	94 %
Peak intensity	3.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Bender Wirth: 634a Bayonet35L


Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

NICHIA

LED	COB S-Type (LES 6)
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	36.0° / 54.0°
Efficiency	91 %
Peak intensity	2.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




Bender Wirth: 652a Bayonet35L

Light distribution files

NICHIA

LED	COB S-Type (LES 7)
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	36.0° / 56.0°
Efficiency	90 %
Peak intensity	2.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




Bender Wirth: 652a Bayonet35L

Light distribution files

NICHIA

LED	COB T-Type
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	36.0° / 54.0°
Efficiency	90 %
Peak intensity	2.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Bender Wirth: 652a Bayonet35L


Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

SAMSUNG

LED	LC003D / LC006D / LC009D / LC013D
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	36.0° / 58.0°
Efficiency	86 %
Peak intensity	2.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




BJB: 47.360.1020

Light distribution files

SAMSUNG

LED	LC010C G2
Ordering code	CP18525_YASMEEN-35-W-B
FWHM / FWTM	34.0° / 52.0°
Efficiency	89 %
Peak intensity	2.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



BJB: 47.360.1020

Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Poznan, Poland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

LEDiL:

C11347_REGINA C12948_LENA-WAS C14146_LENA-STD-BASE-CXA18 CA18107_TINA-Y-O
C13301_STRADA-2X2-T3 CA18093_LEILA-Y-WW FP13031_LISA2-W-CLIP FCN15499_RONDA-W
FP13029_LISA2-WW-CLIP C16906_ALISE-70-WW C17247_ELLA-30-M CA12816_LXP2-RS2
F14686_G2-ROSE-UV-M F15541_JENNY-60 FCN13552_CRYSTAL-RS C11716_ANNA-40-7-S
C12692_LENA-STD-BASE-CLL040 CA11391_EMILY-M2 F14534_ANGELETTE-WW
FN15973_RONDA-REC-60-C FP18205_LISA3CSP-WW-CLIP16 LURR3000G3 C13118_STRADA-SQ-A-T
C18429_ADELIA-75-W CA15584_ZORYA-MINI-TAPE FCN15621_RONDA-W C11679_ANNA-50-7-M
FA10751_LO2-RS C11191_TUIJA-3-W CA18090_LEILA-Y-SS