

Vacuum generator
CPV10-M1H-V70-M7

Part number: 185862





General operating condition

Data sheet

Feature	Value
Nominal width of Laval nozzle	0.7 mm
Mounting position	Any
Ejector characteristics	High vacuum
Symbol	00991560
Operating pressure	3 bar ... 8 bar
Max. vacuum	85 %
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	1 - Low corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Temperature of medium	0 °C ... 50 °C
Ambient temperature	0 °C ... 50 °C
Product weight	25 g
Electrical connection	Plug
Type of mounting	With through-hole
Pneumatic connection 1	Sub-base
Pneumatic connection 3	Sub-base
Vacuum connection	M7
Note on materials	RoHS-compliant
Housing material	Die-cast aluminum

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

NPQP-LQ-R18-Q8-FD-P10 SGS-M10X1,25 NPQH-T-Q14-E-P10 NPQP-Y-Q6-E-FD-P10 QS-1/8-8-I QSF-1/4-8-B VABM-B10-25S-G38-6-P3 153269 DSBC-80-20-D3-PPSA-N3 NPQP-Y-R12-Q12-FD QSML-6 QSY-6H-4 153031 153307 HGL-1/8-QS-6 NPQP-D-Q4-S8-FD-P10 QSLL-G1/2-12 153367 NPQP-T-Q8-E-FD-P10 CRVZS-0.4 NPQP-L-Q10-E-FD-P10 QS-10H-6 QSS-8-F VBQF-U-G14-E NPQP-LQ-R18-Q4-FD-P10 QSF-3/8-8-B 153151 QS-1/2-16 SASC-P4-A-M8-A VABM-B10-25S-G38-10