Push-in connector
NPQP-D-Q4-E-FD-P10

Part number: 133091



General operating condition

Data sheet

Feature	Value
Size	Standard
Nominal width	2.8 mm
Design	Straight design
Pack size	10
Structural design	Push-pull principle
Temperature-dependent operating pressure	-0.95 bar ... 10 bar
Operating medium	Compressed air as per ISO 8573-1:2010 [7:-:-]
Information on operating and pilot media	Operation with oil lubrication possible
Corrosion resistance class (CRC)	4 - Particularly high corrosion stress
LABS (PWIS) conformity	VDMA24364 zone III
For use in the food industry	See supplementary material information
Ambient temperature	-20 °C ... 60 °C
Product weight	4 g
Pneumatic connection 1	for pneumatic tubing outside diameter 4 mm
Pneumatic connection 2	for pneumatic tubing outside diameter 4 mm
Note on materials	RoHS-compliant
Housing material	PP
Material of tube retaining claw	High-alloy stainless steel

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

VABM-B10-25S-G38-6-P3 NPQH-T-Q14-E-P10 NPQP-Y-Q6-E-FD-P10 NPQP-Y-R12-Q12-FD QSY-6H-4 QS-10H-6 QSF-1/4-8-B HGL-1/8-QS-6 NPQP-D-Q4-S8-FD-P10 153031 153367 NPQP-L-Q10-E-FD-P10 NPQP-LQ-R18-Q4-FD-P10 CRVZS-0.4 QS-1/2-16 NPQP-LQ-R18-Q8-FD-P10 QS-1/8-8-I QSLL-G1/2-12 QSML-6 QSS-8-F SGS-M10X1,25 VBQF-U-G14-E VABM-B10-25S-G38-10 NPQP-T-Q8-E-FD-P10 153151 153269 153307 DSBC-80-20-D3-PPSA-N3 QSF-3/8-8-B SASC-P4-A-M8-A