
Compact air cylinder
ADVU-16-20-P-A

Part number: 156510





General operating condition

Data sheet

Feature	Value
Stroke	20 mm
Piston diameter	16 mm
Cushioning	Elastic cushioning rings/pads at both ends
Mounting position	Any
Mode of operation	Double-acting
Piston rod end	Internal thread
Structural design	Piston Piston rod
Position sensing	For proximity sensor
Symbol	00991217
Variants	Piston rod at one end
Operating pressure	0.12 MPa ... 1 MPa
Operating pressure	1.2 bar ... 10 bar
Operating pressure	17.4 psi ... 145 psi
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	-20 °C ... 80 °C
Impact energy in the end positions	0.1 J
Theoretical force at 6 bar, retracting	90 N
Theoretical force at 6 bar, advancing	121 N
Moving mass at 0 mm stroke	12 g
Additional moving mass per 10 mm stroke	4 g
Basic weight with 0 mm stroke	89 g
Additional weight per 10 mm stroke	15 g
Type of mounting	Optionally: With through-hole With accessories
Pneumatic connection	M5
Flange screws material	High-alloy stainless steel
Cover material	Wrought aluminum alloy
Material of dynamic seals	NBR TPE-U(PU)
Piston rod material	High-alloy stainless steel
Material of cylinder barrel	Wrought aluminum alloy

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

DSBC-50-125-D3-PPSA-N3 QS-1/8-8-I QSY-8-4 SPAW-B11R-G12M-2PA-M12 HGL-1/8-QS-6
HGL-1/8-1/8-B QS-3/8-8-I DSBC-63-160-D3-PPSA-N3 QS-10H-6 QST-3/8-16 QSY-12-8
VABM-B10-30S-G12-8 NPQH-BK-G38-P10 153109 153151 HGL-1/4-B QSF-1/8-8-B
DSBC-80-25-D3-PPVA-N3 QSL-12 QST-6-4 153106 153154 153475 DSNU-20-80-PPV-A VBQF-U-G14-E
QS-1/2-12-I QSML-3 QSML-6 QSF-3/8-8-B QSSF-1/8-8-B