Your Expert Partner for **Human Machine Interfaces**

Actuator

Distribution by
DigiKey

46-
2134.3150.000



https://digikey.eao.com/p/46-2134.3150.000

Your product:



46-2134.3150.000
Actuator

FRONT

Front dimension:	Ø 29,5 mm
Front bezel material:	Metal
Front form:	round
Front bezel colour:	Silver

MOUNTING

Design:	raised
Mounting cut-out:	Ø 22.3 mm

OPERATING-/INDICATION PART

Lens illumination:	non illuminative
Lens material:	Plastic
Lens colour:	Green
Lens shape:	flush
Lens optics:	opaque

ELECTRICAL CHARACTERISTICS

Protection class:	II

MECHANICAL CHARATERISTIC

Switching action:	Maintained
Mechanical lifetime:	500 000 cycles of operation

Weight:	0.033 kg
Tightening torque:	2 … 3 Nm (17.7 … 26.6 Lb-in)

AMBIENT CONDITION

Operating temperature:	– 25 °C … + 55 °C
Shock resistance:	50g, 11ms (EN-IEC 60068-2-27)
Vibration resistance:	5g f= 2…500Hz (EN-IEC 60068-2-6)
IK front protection:	IK03
IP front protection:	IP65
Climate resistance:	+25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)

CERTIFICATE

Conformities:	CE
Standards:	CSA C22-2, IEC EN 60947-1, IEC EN 60947-5-1, UL508

OTHER

max. number of switching elements:	6
Short Description:	Actuator, Ø 22.3 mm, Ø 29,5 mm, flush, non illuminative, Green, Plastic, opaque, round, Silver, Metal, Maintained, IP65, IK03
Housing material:	Plastic
Housing colour:	Black
Dimension drawings:	

