1-826646-3 ✔ ACTIVE


AMPMODU | AMPMODU Headers

TE Internal #: 1-826646-3

PCB Mount Header, Vertical, Board-to-Board, 13 Position, 2.54 mm [.1 in] Centerline, Breakaway, AMPMODU Headers

View on TE.com >

Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Assembly Type: **PCB Mount Header**

PCB Mount Orientation: **Vertical**

Connector System: **Board-to-Board**

Number of Positions: **13**

Number of Rows: **1**

Features

Product Type Features

PCB Connector Assembly Type	PCB Mount Header
Connector System	Board-to-Board
Header Type	Breakaway
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Connector Contact Load Condition	Fully Loaded
PCB Mount Orientation	Vertical
Number of Positions	13
Number of Rows	1
Board-to-Board Configuration	Parallel

Electrical Characteristics

Insulation Resistance	5000 MΩ
Dielectric Withstanding Voltage (Max)	750 Vrms

Body Features

Primary Product Color	Green

Contact Features

Mating Square Post Dimension	.63 mm[.025 in]

PCB Contact Termination Area Plating Material Thickness	3 µm
Contact Shape & Form	Square
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Mating Area Plating Material	Gold or Gold Flash over Palladium Nickel
Contact Mating Area Plating Material Thickness	.8 µm[31.5 µin]
Contact Type	Pin
Contact Current Rating (Max)	5 A

Termination Features

Square Termination Post & Tail Dimension	.63 mm[.025 in]
Termination Post & Tail Length	3.2 mm[.126 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Mating Alignment	Without
PCB Mount Retention	Without
PCB Mount Alignment	Without
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	2.54 mm[.1 in]
Housing Material	PBT

Dimensions

PCB Thickness (Recommended)	1.57 mm[.062 in]

Usage Conditions

Housing Temperature Rating	Standard
Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]

Operation/Application

Circuit Application	Signal

Industry Standards

UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	500

Packaging Method	Box

Product Compliance


For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 240°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 1-215297-3
13P HV100 REC CON. TE, 7.0MM


Also in the Series | AMPMODU Headers



Connector Contacts(60)



Connector Hardware(1)




PCB Headers & Receptacles(1629)



Wire-to-Board Connector Assemblies & Housings(5)


Customers Also Bought



TE Part #6-1879233-6
SMD Power Resistor: 7 Watt, 0.10-500 Ohm




TE Part #4-644456-0
10P MTA100 HDR ASSY (NARROW)



TE Part #1-794066-1
12P MINI UMNL HDR W/DH AU LF



TE Part #5-103672-3
04 MTE HDR SRRA LATCH W/HLDWN




TE Part #6651712-1
284-0162-03003=TA CONN,SKT




TE Part #2337822-1
DISCR.ETH.MAG. 10/100 SINGLE SMT



TE Part #1-2176308-6
RP 1E 0.1W 191K 0.1% 25PPM 5K RL



TE Part #1586768-6
6P VERT HDR VAL-U-LOK GW



TE Part #2-2176484-3
RA73F 2A 10K 0.1% 5K RL

Documents

Product Drawings

13P AMPMODU II STIFT LEI

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-826646-3_P.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-826646-3_P.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-826646-3_P.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Agency Approvals

UL Report

English

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TE Connectivity:

1-962915-1 1393431-1 3430B2F51RTDF 1-794222-0 2834055-1 MPT100C18RF ROX05SJ18R SMW73R0JT 2380312-2 175977-2 1969656-1 2377783-2 650075-000 CPF0402B37K4E1 1743455-2 3631B101LL 2-292161-3 936348-1 CRGCQ2010J3K3 TE50BR39J U5254-000005-030PA 141991-2 2310537-1 3-1393225-0 1903112-2 2005330-1 917696-1 RH73H2A40MKTN SBCHE154R7K SBCHE64R7K