DYMO® Industrial Labels

Label it fast, label it once, label it right.












Tough, jobsite-tested labels for industrial applications.



Rely on DYMO® Industrial Labels.

DYMO® Industrial labels are tough – jobsite tested and UL recognized. Thermal transfer printing means labels won't smudge, smear or fade. Choose up to a 24 mm label width in a broad assortment of materials and colours that meet OSHA, ANSI, and ISO standards.
All DYMO® Industrial labels are distributed from an easy-to-load cartridge, and with a split-back design, peeling and applying is quick and easy.

DYMO® Industrial labels help you get labelling jobs done fast, and done right – the first time.



DYMO® Industrial Labels are available in:

Flexible Nylon
Permanent Polyester
Indoor/Outdoor Vinyl
Heat-Shrink Tube
Non-Adhesive Tag
Self-Laminating

IND

DYMO® Industrial Label Benefits:

1. Industrial-strength adhesives resist moisture, extreme temperatures, UV light and more – so labels won't curl or fall off
2. Available in a range of UL recognized materials for virtually every industrial labelling application; heat-shrink tubes tested to SAE, ASTM and military specifications
3. Thermal transfer printing technology – label text won't smudge, smear, or fade
4. Choose from 6, 9, 12, 19, and 24 mm label widths in a broad colour assortment that meet OSHA, ANSI, and ISO standards
5. Easy-to-peel split back design makes applying labels quick and easy

The right label for virtually every situation and surface.

Indoor/Outdoor Vinyl
For general labelling or extreme conditions. Vinyl labels offer moisture, chemical and UV resistance, making them ideal for labelling both indoors and outdoors. Available in the widest range of colours that adhere to OSHA, ANSI and ISO colour standards.

UL recognized as a component to UL 969

Flexible Nylon
For labelling wires, cables and rounded surfaces. Flexible Nylon labels conform and stick tightly to wires, cables, curved and textured surfaces. Tear-proof material resists damage when pulled through tight spaces or conduits.

UL recognized as a component to UL 969

Permanent Polyester
For labelling panels, blocks, faceplates, shelves, bins, beams and more. Permanent Polyester labels have a polished finish that leaves your work looking professional. Available in smaller widths that fit most patch panels, blocks and other distribution panels.

UL recognized as a component to UL 969

Heat-Shrink Tube
For high-end cable identification. A 3:1 shrink ratio helps ensure a secure fit on wires and cables. Print directly on Heat-Shrink Tubes with any DYMO® Industrial labelling tool.

Meets MIL-M-81531, MIL-STD-202G, SAE-DTL- 23053/5 (Class 1 & 3)
UL recognized as a component to UL 224

Non-Adhesive Tag
For sliding into racks or faceplates that do not require adhesive. Made from polyester for increased durability.

Self-Laminating
Self-Laminating labels protect your printed area from exposure to oil, solvents, water and abrasion when applied to wires and cables.

All DYMO® Industrial labels are RoHS compliant.


For technical specifications on all DYMO® Industrial label types, please visit our website at:
www.dymo.com/industrial

How to choose the right DYMO® Industrial label:

ENVIRONMENT / SURFACE	Heat/Cold Resistant	UV Light Resistant	Oil Resistant	Water Resistant	Chemical Resistant	Colour Coding
Cable/Wire	**Flexible Nylon** Heat-Shrink Tube	**Indoor/Outdoor Vinyl** Heat-Shrink Tube	**Indoor/Outdoor Vinyl** Heat-Shrink Tube	**Indoor/Outdoor Vinyl** Heat-Shrink Tube	**Indoor/Outdoor Vinyl** Heat-Shrink Tube	**Indoor/Outdoor Vinyl**
Curved Surface	**Flexible Nylon** Indoor/Outdoor Vinyl	**Indoor/Outdoor Vinyl** Flexible Nylon	**Indoor/Outdoor Vinyl**	**Indoor/Outdoor Vinyl** Flexible Nylon	**Indoor/Outdoor Vinyl**	**Indoor/Outdoor Vinyl**
Flat Surface	**Permanent Polyester** Flexible Nylon	**Permanent Polyester** Indoor/Outdoor Vinyl	**Permanent Polyester** Indoor/Outdoor Vinyl	**Permanent Polyester** Indoor/Outdoor Vinyl	**Permanent Polyester** Indoor/Outdoor Vinyl	**Indoor/Outdoor Vinyl**
Textured Surface	**Permanent Polyester** Flexible Nylon	**Indoor/Outdoor Vinyl** Permanent Polyester	**Indoor/Outdoor Vinyl** Permanent Polyester	**Indoor/Outdoor Vinyl** Permanent Polyester	**Indoor/Outdoor Vinyl** Permanent Polyester	**Indoor/Outdoor Vinyl**

Top = Best Option Bottom = Alternate Option

Available DYMO® Industrial label widths and colours:

IND LABEL APPLICATIONS	LABEL COLOUR	6 mm	9 mm	12 mm	19 mm	24 mm
Labels that stick and stay stuck. DYMO® Industrial labels are tough– jobsite tested and UL recognized. Labels won't smear or fade and are built with industrial-strength adhesives to resist moisture, UV light and extreme temperatures. Whether you are labelling to OSHA, ISO and ANSI colour standards or labelling in harsh conditions, DYMO® Industrial labels have you covered. DYMO® Industrial labels are designed to work exclusively with Rhino™ printers and to perform on a variety of surfaces. LEARN MORE: www.dymo.com/industrial	BLACK ON WHITE	–	18443 *S0718580*	18444 *S0718600*	18445 *S0718620*	1805430
	BLACK ON YELLOW	–	–	18432 *S0718450*	18433 *S0718470*	1805431
	BLACK ON ORANGE	–	–	18435 *S0718490*	18436 *S0718500*	1805427
	BLACK ON GREY	–	–	1805413	1805419	1805425
	WHITE ON RED	–	–	1805416	1805422	1805429
	WHITE ON BLACK	–	1805437	1805435	1805436	1805432
	WHITE ON GREEN	–	–	1805414	1805420	1805426
VINYL - UL Recognized Component to UL969 - RoHS compliant Length 5.5 m 	WHITE ON BLUE	–	–	1805243	1805417	1805423
	WHITE ON PURPLE	–	–	1805415	1805421	1805428
	WHITE ON BROWN	–	–	1805412	1805418	1805424
PERMANENT POLYESTER - UL Recognized Component to UL969 - RoHS compliant Length 5.5 m 	BLACK ON WHITE	1805442	18482 *S0718240*	18483 *S0718210*	18484 *S0718220*	1734523 *S0773830*
	BLACK ON CLEAR	1805440	18508DMO *S0718160*	622289	622290	1805433
	BLACK ON METALLIC	1805441	18485 *S0718170*	18486 *S0718180*	18487 *S0718200*	1805434
HEAT SHRINK TUBES - UL Recognized Component to UL224 - Meets MIL-STD-202G, MIL-M-81531 & SAE-DTL 23053/5 (Class 1 & 3) - RoHS compliant Length 1.5 m 	BLACK ON WHITE	18051 *S0718260*	18053 *S0718280*	18055 *S0718300*	18057 *S0718330*	1805443
	BLACK ON YELLOW	18052 *S0718270*	18054 *S0718290*	18056 *S0718310*	18058 *S0718340*	1805444
FLEXIBLE NYLON - UL Recognized Component to UL969 - RoHS compliant Length 3.5 m 	BLACK ON WHITE	–	–	18488 *S0718100*	18489 *S0718120*	1734524 *S0773840*
	BLACK ON YELLOW	–	–	18490 *S0718080*	18491 *S0718090*	1734525 *S0773850*
NON-ADHESIVE TAG - RoHS compliant Length 5.5 m 	BLACK ON WHITE	18111 *S0718350*	–	18113 *S0718380*	–	–
SELF-LAMINATING - RoHS compliant Length 5.5 m 	BLACK ON WHITE	–	–	–	–	1734821 *S0773860*

For more information or to find out your nearest distributor, please visit www.dymo.com/industrial or call us at +44 (0) 20 7341 5529.

DYMO
Newell Rubbermaid
Brands That Matter

©2011 DYMO®
DYMO bvba, Industriepark-Noord 30
B9100 Sint-Niklaas, Belgium
www.dymo.com/industrial

S0972150

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

DYMO:

18056 S0722440 1734821 18432 18435 S0721730 18057 18482 18485 1805442 S0720500 1978367 2093097 45018 S0720170 S0722520 S0722530 S0883990 18488 1868753 2093091 18484 2112290 2136595 40916 1805243 18445 18483 S0722550 16959