CUDEVICES

MODEL: PJ-083H | **DESCRIPTION:** DC POWER JACK

FEATURES

- 1.65 mm center pin
- 5 A rating
- shielded
- through hole
- 1 switch



RoHS


SPECIFICATIONS

parameter	conditions/description	min	typ	max	units
rated input voltage			24		Vdc
rated input current				5.0	A
contact resistance	between terminal and mating plug between terminal in a closed circuit			50 30	mΩ mΩ
insulation resistance	at 500 Vdc	100			MΩ
voltage withstand	for 1 minute			500	Vac
insertion/withdrawal force		0.5		2	kg
operating temperature		-25		85	°C
life	at a rate of 10~20 cycles		5,000		cycles
flammability rating	UL94V-0				
RoHS	yes				

SOLDERABILITY

parameter	conditions/description	min	typ	max	units
reel storage	10~30°C, <70% humidity				°C
reflow soldering[1]	see reflow profile	255	260		°C
drying conditions[2]	parts in reel: bake at 110°C for 4 hours parts removed from reel: bake at 110°C for 4 hours				


Note:
1. CUI Devices recommends to solder within 72 hours from opening vacuum packaging at a temperature <30°C & relative humidity <60%.
2. When exceeding floor life by >240 hours.




* Time 25°C to Peak Temp. ----- 8 Minutes Max.
* Time within 5°C of Actual Peak Temp. -- 20~40 Seconds


MECHANICAL DRAWING


units: mm
tolerance:
X.X ±0.20 mm
X.XX ±0.10 mm
X.XXX ±0.050 mm
PCB: ±0.05 mm





DESCRIPTION	MATERIAL	PLATING/COLOR
center pin	copper	nickel
terminal 1	brass	silver
terminal 2	brass	silver
terminal 3	brass	silver
shield A	brass	nickel
shield B	stainless steel	
insulator	PA10T (UL94V-0)	













Recommended PCB Layout
Top View




MATING PLUG
Jack Insertion Depth: 8.2 mm


SCHEMATIC	
Model	PJ-083H
Center Pin	Ø1.65 mm


PACKAGING

units: mm

Reel Size: Ø330 mm
Reel QTY: 400 pcs per reel







REVISION HISTORY

rev.	description	date
1.0	initial release	12/12/2018
1.01	brand update	10/25/2019
1.02	logo, datasheet style update	08/05/2022
1.03	product reengineered for improved manufacturability and production yield, see PCN for details	10/11/2023

The revision history provided is for informational purposes only and is believed to be accurate.

CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

cuidevices.com

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Same Sky:

CMM-2718AT-42316-TR SJ-43516-SMT-TR-PI UJ32-C-H-G-L1-MSMT-TR CFM-2510B-0130-275 DS01C-254-S-03BE PJ-202AH TBP02P1-381-10BE PJ-067B TBP01R1-508-14BE CPT-1117-83-SMT-TR CBT-09427-SMT-TR CFM-6015V-239-292-20 HSE-B20350-NP SJ1-3535N CPM-2H CDM1222-12A-FW-F16-050-67 CMI-9653S-SMT-TR TBL004V-508-02BE-2GY DS04-254-2-02BK-SMT PJ-058AH PR4-5V-450-1A PJ-047BH SJ-2523-SMT-TR TB007-508-02BE CMP-5247TF-K CFM-2507CF-0140-313 CFM-A238BF-270-651 CMA-4544PF-W CMC-5042PF-AC CPI-1375IC-80T