Electrostatic Discharged Protection Devices (ESD) Data Sheet

Description

Brightking's UFS08A2.8L04 component is designed to protect low voltage state-of-the-art CMOS semiconductors from transients caused by electrostatic discharge (ESD), cable discharge events (CDE), lightning and other induced voltage surges. The device provides low stand-off voltages with significant reductions in leakage currents and capacitance over silicon avalanche diode processes.
The UFS08A2.8L04 features integrated low capacitance compensation diodes that reduce the typical capacitance 5pF per line.
This combined with low leakage current, means signal integrity preserved in high-speed applications such as 10/100/1000 Ethernet.




Contact : ±8kV
Air : ±15kV



Features

- IEC61000-4-2 ESD 15KV Air, 8KV contact compliance
- SOIC-08 surface mount package
- Protects four I/O lines
- Peak power dissipation of 600W under 8/20μs waveform
- Working voltage: 2.8V
- Low leakage current
- Low operating and clamping voltages
- Solid-state silicon avalanche technology
- Lead Free/RoHS compliant
- Solder reflow temperature: Pure Tin-Sn, 260~270℃
- Flammability rating UL 94V-0
- Meets MSL level 1, per J-STD-020
- Marking: B SLVU2.8-4



Pin Configuration

Applications

- 10/100/1000 Ethernet
- WAN/LAN Equipment
- High current switching systems
- Desktops, Servers and Notebook
- Instrumentation
- Analog inputs
- Base stations

Maximum Ratings


Rating	Symbol	Value	Unit
Peak pulse power (tp=8/20μs waveform)	P_{PP}	600	W
ESD voltage (Contact discharge)	V_{ESD}	±8	kV
ESD voltage (Air discharge)		±15	
Storage & operating temperature range	T_{STG} ,T_J	-55~+150	℃

Electrical Characteristics (T_J=25℃)

Parameter	Symbol	Condition	Min.	Max.	Unit
Reverse stand-off voltage	V_{RWM}			2.8	V
Reverse breakdown voltage	V_{BR}	I_{BR}=1mA	3		V
Reverse leakage current	I_R	V_R=2.8V Each I/O pin		5	μA
Clamping voltage (tp=8/20μs)	V_C	I_{PP}=5A		8.5	V
Peak pulse current (tp=8/20μs)	I_{PP}			24	A
Off state junction capacitance	C_J	0Vdc,f=1MHz Between I/O pins and GND		3	pF
		0Vdc,f=1MHz Line to Line, two I/O pins connected together on each line (Note)		6	pF

Note: Ratings with two pins connected together per the recommended configuration (ie pin 1 connected to pin 8, pin 2 connected to pin 7, pin 3 connected to pin 6, pin 4 connected to pin 5).

Applications Information



Typical Characteristics Curves

Figure 1. Power Derating Curve




Figure 2. Pulse Waveforms




Figure 3. Non-Repetitive Peak Pulse vs. Pulse Time




Figure 4. Capacitance vs. Reverse Voltage






Figure 5. Clamping Voltage vs. Peak Pulse Current



Recommended Soldering Conditions


Reflow Soldering



Recommended Conditions

Profile Feature	Pb-Free Assembly
Average ramp-up rate (T_L to T_P)	3℃/second max.
Preheat -Temperature Min ($T_{S\ min}$) -Temperature Max ($T_{S\ max}$) -Time (min to max) (ts)	 150℃ 200℃ 60-180 seconds
$T_{S\ max}$ to T_L -Ramp-up Rate	 3℃/second max.
Time maintained above: -Temperature (T_L) -Time (t_L)	 217℃ 60-150 seconds
Peak Temperature (T_P)	260℃
Time within 5℃ of actual Peak Temperature (t_P)	20-40 seconds
Ramp-down Rate	6℃/second max.
Time 25℃ to Peak Temperature	8 minutes max.

Dimensions (SOIC-08)




Recommended Soldering Pad Layout

Symbol	Dimension			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	4.80	5.00	0.189	0.197
B	5.80	6.20	0.228	0.244
C	3.80	4.00	0.150	0.157
D	1.27		0.050	
E	0.33	0.51	0.013	0.020
F	0.40	1.27	0.016	0.050
G	0.19	0.25	0.007	0.010
H	1.35	1.75	0.053	0.069
H1	0.10	0.25	0.004	0.010
H2	1.45		0.057	


Packaging

Tape



Symbol	Dimension (mm)
W	12.00±0.30
P0	4.00±0.10
P1	8.00±0.10
P2	2.00±0.10
D0	Φ1.55±0.10
D1	Φ1.55±0.05
E	1.75±0.10
F	5.50±0.10
A	6.50±0.10
B	5.40±0.10
K	2.00±0.10
t	0.30±0.05

Reel



D	Φ330.0±3.0
D2	Φ13.0
W1	13.5
Quantity: 2500PCS	

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

BrightKing:

SMD1812B075TF 102KD10 3RM090L-8 UET26A05L05-IP38 390KD14 SMD1206B050TF/24 SBD52C05L01 SDD32A05L01 201KD14-TB 2RM090M-8 331KD14 561KD14J-F P2300SA SDD32C05L01 SDD32C18L01-AT SMAJ54CA/TR13 SMD1206B025TF 330KD14 5KP48CA/B SMD2920B300TF/30 2RK3600L-5/B 3RL090M-5-SS BK60-160-DZ 2RM230L-8/B BK60-050-DI-E0.5 BK60-090-DZ-E0.6 2RL150L-5/B 2RP600L-8/B 3RL075M-5-S BK16-300-SZ