711 Lidgerwood Avenue
Elizabeth, NJ 07207-0711 USA
1-908-925-8000
1-800-52 ALPHA
www.alphawire.com

FIT® Shelf Life Guide

Below you will find the shelf lives for all of our FIT Heat-Shrink Tubing products and select Wire Management products.

Products not listed below do not have a specified or documented shelf life.

Please Note: The storage temperature range for all of these products is **65°F-95°F**.

**Shelf lives are based upon manufacturer's recommendations*

Product Type	Shrink Ratio	Material Type	Shelf Life (Yrs)
FIT-105	2:1	PVC	1
FIT-221	2:1	Polyolefin	5
FIT-221B	2:1	Polyolefin	5
FIT-221V	2:1	Polyolefin	5
FIT-260	2:1	Polyolefin	25
FIT-295	2:1	Polyolefin	5
FIT-300	3:1	Polyolefin	3
FIT-321	3:1	Polyolefin	3
FIT-321V	3:1	Polyolefin	25
FIT-350	2:1	PVDF	5
FIT-375	2:01	PVDF, Modified	5
FIT-400	1.2:1	FEP	4
FIT-500	1.5:1	TFE	4
FIT-600	1.75:1	Neoprene	1
FIT-621	6:1	Polyolefin	25
FIT-650	2:1	Fluoroelastomer	2
FIT-700	3:1	Polyolefin	25
FIT-750	2:1	Polyolefin	3
FIT-CAP	2:1	Polyolefin	25
FIT-CRIMP	2:1	Nylon	25
FIT-FAB	2:1	Polyester	25
FIT-FLEX	1.7:1	Silicone	25
FIT-PRINT	3:1	Polyolefin	3
FIT-RP	3:1	Polyolefin	25
FIT-SLV-(12-16)	---	PVDF	25
FIT-SLV-(22-26)	---	PVDF	5
CST*	---	Cu & Adhesive	2
Lacing Cords*	---	Various	1yr after opening

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Alpha Wire:

5855 OR005 6822 BK005 7013 WH001 3050 BR001 6300/3 SL005 6710 BL001 F60011/2 BK008
1855 BK001 3051 SL001 461816 WH005 7130 BK005 1853 YL005 1855 WO005 2842/7 BL005
F221V1/8 BK103 F3001/2 BK056 5852 BL001 5854/7 YL001 6715 YL005 PF2001 NA005 1858/19 BR005
3252 YL005 782401 VI005 2842/19 SL005 3081 GR005 3252 VI005 F2213/8 GR065 1232 SV001
3075 VI005 6822 WH001