Features

- Transient protection for high-speed data lines
  - IEC 61000-4-2 (ESD) ±15kV (Air)
    ±8kV (Contact)
  - IEC 61000-4-4 (EFT) 40A (5/50 ns)
  - Cable Discharge Event (CDE)
- Package optimized for high-speed lines
- Ultra-small package (1.0mm×0.6mm×0.55mm)
- Protects one data, control or power line
- Low capacitance: 5.0 pF (Typical)
- Low leakage current: 10nA @ V_{RWM} (Typical)
- Low clamping voltage
- Each I/O pin can withstand over 1000 ESD strikes for ±8kV contact discharge
- ROHS compliant

Description

TT1201PBX is a low-capacitance Transient Voltage Suppressor (TVS) designed to provide electrostatic discharge (ESD) protection for high-speed data interfaces. With typical capacitance of 5.0pF only, TT1201PBX is designed to protect parasitic-sensitive systems against over-voltage and over-current transient events. It complies with IEC 61000-4-2 (ESD), Level 4 (±15kV air, ±8kV contact discharge), IEC 61000-4-4 (electrical fast transient - EFT) (40A, 5/50 ns), very fast charged device model (CDM) ESD and cable discharge event (CDE), etc.

TT1201PBX uses ultra-small uDFN-2L package. Each TT1201PBX device can protect one high-speed data line. It offers system designers flexibility to protect single data line where space is a premium concern. The combined features of low capacitance, ultra-small size and high ESD robustness make TT1201PBX ideal for high-speed data port and high-frequency line (e.g., USB 2.0 & antenna line) applications, such as cellular phones and HD visual devices.


Applications

- Serial ATA
- PCI Express
- Desktops, Servers and Notebooks
- Cellular Phones
- MDDI Ports
- USB2.0 Power and Data Line Protection
- Display Ports
- Digital Visual Interfaces (DVI)


Mechanical Characteristics

- uDFN-2L package
- Flammability Rating: UL 94V-0
- Marking: Part number
- Packaging: Tape and Reel

Circuit Diagram



Pin Configuration




DFN1006-2L
(Top View)

Absolute Maximum Rating

Symbol	Parameter	Value	Units
V_{ESD}	ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	±15 ±8	kV
T_{OPT}	Operating Temperature	-55/+125	°C
T_{STG}	Storage Temperature	-55/+150	°C

Electrical Characteristics (T = 25°C)


Symbol	Parameter
V_{RWM}	Nominal Reverse Working Voltage
I_R	Reverse Leakage Current @ V_{RWM}
V_{BR}	Reverse Breakdown Voltage @ I_T
I_T	Test Current for Reverse Breakdown
V_C	Clamping Voltage @ I_{PP}
I_{PP}	Peak Pulse Current
C_{ESD}	Parasitic Capacitance
V_R	Reverse Voltage
f	Small Signal Frequency




Bi-Directional TVS

Symbol	Test Condition	Minimum	Typical	Maximum	Units
V_{RWM}				12.0	V
I_R	V_{RWM} = 12V, T = 25°C Between I/O and I/O		0.01	0.1	μA
V_{BR}	I_T = 1mA Between I/O and I/O	14	16	18	V
V_C	I_{PP} = 1A, t_p = 8/20μs Between I/O and I/O		18	20	V
C_{ESD}	V_R = 0V, f = 1MHz Between I/O and I/O		5	7	pF

Voltage Sweeping of I/O to I/O




Insertion Loss S21 of I/O to I/O




Capacitance vs. Voltage of I/O to I/O (f = 1MHz)


Capacitance *vs.* Reverse Voltage




Normalized Capacitance *vs.* Reverse Voltage



ESD Clamping of I/O to I/O (+8kV Contact per IEC 61000-4-2)




ESD Clamping of I/O to I/O (-8kV Contact per IEC 61000-4-2)



Package Outline


- uDFN-2L package
- 2 leads, very small package
- MSL-1



Package Dimensions (Controlling dimensions are in millimeters)

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Minimum	Maximum	Minimum	Maximum
A	0.400	0.550	0.016	0.022
A1	0.000	0.050	0.000	0.002
A3	0.125 REF		0.005 REF	
D	0.950	1.050	0.037	0.041
E	0.550	0.650	0.022	0.026
b	0.200	0.300	0.008	0.012
e	0.650 BSC		0.026 BSC	
L	0.450	0.550	0.018	0.022

Tape and Reel Specification



Symbol	W	A0	B0	K0	E	F	P	P0	P2	T
Dimensions (mm)	8.00±0.1	0.7±0.05	1.15±0.05	0.55±0.05	1.75±0.1	3.5±0.05	2.0±0.1	4.0±0.1	2.0±0.05	0.2±0.05

Marking Codes

BB

Ordering Information

Part Number	Working Voltage	Quantity Per Reel	Reel Size
TT1201PBX	12V	10,000	7 Inch

Note:
(1) "BB" is part number.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

JY:

P0300SCX TL431 TP6063F-TDX TS0421LEX TT1501SBX JY1103-H390BX JY1117E50AX RCLAMP0524P SMCJ20AX TS0334PLX TT0201SAX TT0511TEX JY1103-H330QX JY9425X MMBT3906X TT0301MAX TT0514TLX B5819WX P3100SCX TNM01K20FX TS0512PMX TT0314TPX JY2126AX TS1811LD-CX JY2312X JY1106-180EX JY1106-ADJBX TS0321LEX TS2411LEX TT0401TBX