
DATASHEET

SMD ▪ MID Power LED
67-21S/KK7C-HXXXX34Z15/2T(GC)

Preliminary



Features

- PLCC-2 package
- Top view white LED
- High luminous intensity output
- Wide viewing angle
- Pb-free
- RoHS compliant
- ANSI Binning

Description

The Everlight 67-21S package has high efficacy, high CRI, low power consumption, wide viewing angle and a compact form factor. These features make this package an ideal LED for all lighting applications.

Applications

- General lighting
- Decorative and Entertainment Lighting
- Indicators
- Illumination
- Switch lights

Copyright © 2017, Everlight All Rights Reserved. Release Date: 23.Jan. 2017. Issue No:VP2
Issue No:DSE-00

Product Number Explanation

67–21S / K K 7 C – H XX XX XX Z15 / 2T




Table of Color Rendering Index

Symbol	Description
M	CRI(Min.) : 60
N	CRI(Min.) : 65
L	CRI(Min.) : 70
Q	CRI(Min.) : 75
K	CRI(Min.) : 80
P	CRI(Min.) : 85
H	CRI(Min.) : 90

Note:
Tolerance of Color Rendering Index: ±2

Table of Forward Current Index

Symbol	Description
Z15	I_F:150mA

Example:
67-21S/KK7C-H407034Z15/2T(GC)

CRI	80(Min.)
CCT	4000K
Flux	70lm min
V_F	3.4V max
I_F	150mA

Copyright © 2017, Everlight All Rights Reserved. Release Date: 20.Feb. 2017. Issue No:VP2
Issue No:DSE-00

Mass Production List

Product	CRI Min.(1)	CCT(K)	Φ(lm) Min. (2)
67-21S/KK7C-H306534Z15/2T(GC)	80	3000K	65
67-21S/KK7C-H356534Z15/2T(GC)	80	3500K	65
67-21S/KK7C-H407034Z15/2T(GC)	80	4000K	70
67-21S/KK7C-H507034Z15/2T(GC)	80	5000K	70

Notes:
1. Tolerance of Color Rendering Index: ±2
2. Tolerance of Luminous flux: ±11%.

Copyright © 2017, Everlight All Rights Reserved. Release Date: 20.Feb. 2017. Issue No:VP2
Issue No:DSE-00

Device Selection Guide

Chip Materials	Emitted Color	Resin Color
InGaN	Cool White Neutral White Warm White	Water Clear

Absolute Maximum Ratings ($T_{Soldering}$=25℃)

Parameter	Symbol	Rating	Unit
Forward Current	I_F	180	mA
Peak Forward Current (Duty 1/10 @10ms)	I_{FP}	300	mA
Power Dissipation	P_d	612	mW
Operating Temperature	T_{opr}	-40 ~ +85	℃
Storage Temperature	T_{stg}	-40 ~ +100	℃
Thermal Resistance (Junction / Soldering point)	$R_{th\ J\text{-}S}$	21	℃/W
Junction Temperature	T_j	115	℃
Soldering Temperature	T_{sol}	Reflow Soldering : 260 ℃ for 10 sec. Hand Soldering : 350 ℃ for 3 sec.	

Note:
The products are sensitive to static electricity and must be carefully taken when handling products

Electro-Optical Characteristics ($T_{Soldering}$=25℃)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Flux(1)	Φ	65	-----	-----	lm	I_F=150mA
Forward Voltage(2)	V_F	-----	-----	3.4	V	I_F=150mA
Color Rendering Index(3)	Ra	80	-----	-----		I_F=150mA
Viewing Angle	$2\theta_{1/2}$	-----	120	-----	deg	I_F=150mA
Reverse Current	IR	-----	-----	50		V_R =5V

Notes:
1. Tolerance of Luminous flux: ±11%.
2. Tolerance of Forward Voltage: ±0.1V.
3. Tolerance of Color Rendering Index: ±2

Copyright © 2017, Everlight All Rights Reserved. Release Date: 20.Feb. 2017. Issue No:VP2
Issue No:DSE-00

Bin Range of Luminous Flux

Bin Code	Min.	Max.	Unit	Condition
R4	65	70	lm	I_F=150mA
R5	70	76		
R6	76	83		
R7	83	90		

Note:
Tolerance of Luminous flux: ±11%.


Bin Range of Forward Voltage

Group	Bin Code	Min.	Max.	Unit	Condition
2834	35	2.8	2.9	V	I_F=150mA
	36	2.9	3.0		
	37	3.0	3.1		
	38	3.1	3.2		
	39	3.2	3.3		
	40	3.3	3.4		

Note:
Tolerance of Forward Voltage: ±0.1V.

Copyright © 2017, Everlight All Rights Reserved. Release Date: 20.Feb. 2017. Issue No:VP2
Issue No:DSE-00

The C.I.E. 1931 Chromaticity Diagram




CCT	Bin Code	CIE_x	CIE_y	Bin Code	CIE_x	CIE_y
3000K	30K-A	0.4562	0.4260	30K-D	0.4465	0.4071
		0.4430	0.4212		0.4388	0.4043
		0.4375	0.4096		0.4355	0.3977
		0.4422	0.4113		0.4311	0.3962
		0.4388	0.4043		0.4259	0.3853
		0.4465	0.4071		0.4373	0.3893
	Reference Range:2870K~3000K					
	30K-B	0.4430	0.4212	30K-C	0.4221	0.3984
		0.4299	0.4165		0.4147	0.3814
		0.4221	0.3984		0.4259	0.3853
		0.4297	0.4011		0.4311	0.3962
		0.4328	0.4079		0.4267	0.3946
		0.4375	0.4096		0.4297	0.4011
	Reference Range:3000K~3220K					
	30K-F	0.4422	0.4113	30K-G	0.4388	0.4043
		0.4328	0.4079		0.4297	0.4011
		0.4297	0.4011		0.4267	0.3946
		0.4388	0.4043		0.4355	0.3977
	Reference Range:2960K~3080K					

Copyright © 2017, Everlight All Rights Reserved. Release Date: 20.Feb. 2017. Issue No:VP2
Issue No:DSE-00

CCT	Bin Code	CIE_x	CIE_y	Bin Code	CIE_x	CIE_y
3500K	35K-A	0.4299	0.4165	35K-D	0.4221	0.3984
		0.4148	0.4090		0.4134	0.3943
		0.4106	0.3981		0.4108	0.3878
		0.4159	0.4007		0.4057	0.3853
		0.4134	0.3943		0.4018	0.3752
		0.4221	0.3984		0.4147	0.3814
	Reference Range:3220K~3500K					
	35K-B	0.4148	0.4090	35K-C	0.3943	0.3853
		0.3996	0.4015		0.3889	0.3690
		0.3943	0.3853		0.4018	0.3752
		0.4029	0.3893		0.4057	0.3853
		0.4051	0.3954		0.4006	0.3829
		0.4106	0.3981		0.4029	0.3893
	Reference Range:3500K~3710K					
	35K-F	0.4159	0.4007	35K-G	0.4134	0.3943
		0.4051	0.3954		0.4029	0.3893
		0.4029	0.3893		0.4006	0.3829
		0.4134	0.3943		0.4108	0.3878
	Reference Range:3360K~3540K					

Copyright © 2017, Everlight All Rights Reserved. Release Date: 20.Feb. 2017. Issue No:VP2
Issue No:DSE-00

The C.I.E. 1931 Chromaticity Diagram




Bin Range of Chromaticity Coordinates

CCT	Bin Code	CIE_x	CIE_y	Bin Code	CIE_x	CIE_y
4000K	40K-A	0.4006	0.4044	40K-D	0.3952	0.3880
		0.3871	0.3959		0.3873	0.3831
		0.3843	0.3858		0.3854	0.3768
		0.3890	0.3887		0.3810	0.3741
		0.3873	0.3831		0.3784	0.3647
		0.3952	0.3880		0.3898	0.3716
	Reference Range:3700K~3970K					
	40K-B	0.3871	0.3959	40K-C	0.3703	0.3726
		0.3736	0.3874		0.3670	0.3578
		0.3703	0.3726		0.3784	0.3647
		0.3779	0.3773		0.3810	0.3741
		0.3793	0.3828		0.3764	0.3713
		0.3843	0.3858		0.3779	0.3773
	Reference Range:3970K~4270K					
	40K-F	0.3890	0.3887	40K-G	0.3873	0.3831
		0.3793	0.3828		0.3779	0.3773
		0.3779	0.3773		0.3764	0.3713
		0.3873	0.3831		0.3854	0.3768
	Reference Range:3870K~4080K					

Copyright © 2017, Everlight All Rights Reserved. Release Date: 20.Feb. 2017. Issue No:VP2
Issue No:DSE-00

The C.I.E. 1931 Chromaticity Diagram




Bin Range of Chromaticity Coordinates

CCT	Bin Code	CIE_x	CIE_y	Bin Code	CIE_x	CIE_y
5000K	50K-A	0.3551	0.3760	50K-D	0.3533	0.3624
		0.3464	0.3688		0.3482	0.3583
		0.3456	0.3604		0.3477	0.3530
		0.3487	0.3629		0.3448	0.3507
		0.3482	0.3583		0.3441	0.3428
		0.3533	0.3624		0.3515	0.3487
	Reference Range:4745K~5000K					
	50K-B	0.3464	0.3688	50K-C	0.3371	0.3493
		0.3376	0.3616		0.3366	0.3369
		0.3371	0.3493		0.3441	0.3428
		0.3422	0.3533		0.3448	0.3507
		0.3425	0.3579		0.3418	0.3483
		0.3456	0.3604		0.3422	0.3533
	Reference Range:5000K~5310K					
	50K-F	0.3487	0.3629	50K-G	0.3482	0.3583
		0.3425	0.3579		0.3422	0.3533
		0.3422	0.3533		0.3418	0.3483
		0.3482	0.3583		0.3477	0.3530
	Reference Range:4910K~5120K					

Notes:
1. The value is based on driving current by 150mA.
2. Tolerance of Chromaticity Coordinates: ±0.01.

Copyright © 2017, Everlight All Rights Reserved. Release Date: 20.Feb. 2017. Issue No:VP2
Issue No:DSE-00

Spectrum Distribution



Typical Electro-Optical Characteristics Curves

Fig.1 – Forward Voltage Shift vs. Junction Temperature





Fig.2 - Relative Luminous Intensity vs. Forward Current



Copyright © 2017, Everlight All Rights Reserved. Release Date: 20.Feb. 2017. Issue No:VP2
Issue No:DSE-00

Typical Electro-Optical Characteristics Curves

Fig.3 - Relative Luminous Intensity vs. Junction Temperature




Fig.4 - Forward Current vs. Forward Voltage




Fig.5 – Max. Driving Forward Current vs. Soldering Temperature

Rth j-s=21 ° C/W






Fig.6 – Radiation Diagram



Copyright © 2017, Everlight All Rights Reserved. Release Date: 20.Feb. 2017. Issue No:VP2
Issue No:DSE-00

Package Dimension




Note:
Tolerance unless mentioned is ±0.15 mm; Unit = mm

Copyright © 2017, Everlight All Rights Reserved. Release Date: 20.Feb. 2017. Issue No:VP2
Issue No:DSE-00


Moisture Resistant Packing Materials

Label Explanation



- CPN: Customer's Product Number
- P/N: Product Number
- QTY: Packing Quantity
- CAT: Luminous Intensity Rank
- HUE: Dom. Wavelength Rank
- REF: Forward Voltage Rank
- LOT No: Lot Number


Reel Dimensions



Note:
Tolerances unless mentioned ±0.1mm. Unit = mm


Copyright © 2017, Everlight All Rights Reserved. Release Date: 20.Feb. 2017. Issue No:VP2
Issue No:DSE-00

Carrier Tape Dimensions: Loaded Quantity 16000 pcs Per Reel



Note:
Tolerance unless mentioned is ±0.1mm; Unit = mm

Moisture Resistant Packing Process



Copyright © 2017, Everlight All Rights Reserved. Release Date: 20.Feb. 2017. Issue No:VP2
Issue No:DSE-00

Reliability Test Items and Conditions


The reliability of products shall be satisfied with items listed below.
Confidence level：90%
LTPD：10%

No.	Items	Test Condition	Test Hours/Cycles	Sample Size	Ac/Re
1	Reflow Soldering	Temp. : 260℃ /10sec.	6 Min.	22 PCS.	0/1
2	Thermal Shock	H : +100℃ 20min ∫ 10 sec L : -10℃ 20min	200 Cycles	22 PCS.	0/1
3	Temperature Cycle	H : +100℃ 30min ∫ 5 min L : -40℃ 30min	200 Cycles	22 PCS.	0/1
4	High Temperature/Humidity Reverse Bias	Ta=85℃,85%RH	1000 Hrs.	22 PCS.	0/1
5	High Temperature/Humidity Operation	Ta=85℃,85%RH, I_F = 100 mA	1000 Hrs.	22 PCS.	0/1
6	Low Temperature Storage	Ta=-40℃	1000 Hrs.	22 PCS.	0/1
7	High Temperature Storage	Ta=85℃	1000 Hrs.	22 PCS.	0/1
8	Low Temperature Operation Life	Ta=-40℃, I_F = 180 mA	1000 Hrs.	22 PCS.	0/1
9	High Temperature Operation/ Life#1	Ta=25℃, I_F = 180 mA	1000 Hrs.	22 PCS.	0/1
10	High Temperature Operation/ Life#2	Ta=55℃, I_F =180 mA	1000 Hrs.	22 PCS.	0/1
11	High Temperature Operation/ Life#3	Ta=85℃, I_F = 100 mA	1000 Hrs.	22 PCS.	0/1


Copyright © 2017, Everlight All Rights Reserved. Release Date: 20.Feb. 2017. Issue No:VP2
Issue No:DSE-00

Precautions for Use

1. Over-current-proof
   Customer must apply resistors for protection; otherwise slight voltage shift will cause big current change (Burn out will happen).
2. Storage
   2.1 Do not open moisture proof bag before the products are ready to use.
   2.2 Before opening the package: The LEDs should be kept at 30℃ or less and 90%RH or less.
   2.3 After opening the package: The LED's floor life is 168 Hrs under 30℃ or less and 60% RH or less. If unused LEDs remain, it should be stored in moisture proof packages.
   2.4 If the moisture absorbent material (silica gel) has faded away or the LEDs have exceeded the storage time, baking treatment should be performed using the following conditions.
   Baking treatment: 60±5℃ for 24 hours.
3. Soldering Condition
   3.1 Pb-free solder temperature profile



   3.2 Reflow soldering should not be done more than two times.
   3.3 When soldering, do not put stress on the LEDs during heating.
   3.4 After soldering, do not warp the circuit board.
4. Soldering Iron
   Each terminal is to go to the tip of soldering iron temperature less than 350℃ for 3 seconds within once in less than the soldering iron capacity 25W. Leave two seconds and more intervals, and do soldering of each terminal. Be careful because the damage of the product is often started at the time of the hand solder.
5. Repairing
   Repair should not be done after the LEDs have been soldered. When repairing is unavoidable, a double-head soldering iron should be used (as below figure). It should be confirmed beforehand whether the characteristics of the LEDs will or will not be damaged by repairing.



Copyright © 2017, Everlight All Rights Reserved. Release Date: 20.Feb. 2017. Issue No:VP2

DISCLAIMER

1. EVERLIGHT reserves the right(s) on the adjustment of product material mix for the specification.

2. The product meets EVERLIGHT published specification for a period of twelve (12) months from date of shipment.

3. The graphs shown in this datasheet are representing typical data only and do not show guaranteed values.

4. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from the use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.

5. These specification sheets include materials protected under copyright of EVERLIGHT. Reproduction in any form is prohibited without obtaining EVERLIGHT's prior consent.

6. This product is not intended to be used for military, aircraft, automotive, medical,

Copyright © 2017, Everlight All Rights Reserved. Release Date: 20.Feb. 2017. Issue No:VP2
Issue No:DSE-00

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

EVERLIGHT:

ALS-PDT243-3C/L451 EL357N(A)(TA)-G PT334-6B EL0631(TA) IR928-6C(6-2) IR968-8P(X1-X4)XBY PD204-6B/L3 19-213/Y2C-CQ2R2L/3T(CY) ELM440A(TA)(BMS)-VG IR204C-A 19-21SURC/S530-A2/4T 27-21/GHC-YR1S2M/3C 45-21UMC/404589E/TR8-T 95-21SUGC/S400-A4/TR7 IR908-7C-F(E6) IR26-21C/L110/CT IR383-A IRM-3638JF EL3083 ELM3052(TA)-V ELM406A(TA)-G 103UYD/S530-A3 EL3H7(A)(TA)-G EL817S2(C)(TU)-FG 11-21SURC/S530-A2/3T ITR-20001/T ITR1205ST11A/TR 12-21SURC/S530-A2/TR8 15-21/BHC-AP1Q2/3T 6N137S(TA)