
Technical Data
Data Sheet N1175, Rev. A

RoHS

185NQ015/R-1 SCHOTTKY RECTIFIER



PRM1-1(HALF PAK Module)

Features

- 125℃ T_J operation
- Unique high power, Half-Pak module
- Replaces three parallel DO-5’S
- Easier to mount and lower profile than DO-5’S
- High purity, high temperature epoxy encapsulation for enhanced
- mechanical strength and moisture resistance
- Low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability
- Baseplate: Nickel plated; Terminals: Nickel plated
- This is a Pb − Free Device
- All SMC parts are traceable to the wafer lot
- Additional testing can be offered upon request

Circuit Diagram



185NQ015-1　　185NQ015R-1

Applications

- Switching power supply
- Converters
- Free-Wheeling diodes
- Reverse battery protection

Maximum Ratings:

Characteristics	Symbol	Condition	Max.	Units
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_R	-	15	V
Average Forward Current	$I_{F(AV)}$	50% duty cycle @T_C =66°C, rectangular wave form	180	A
Peak One Cycle Non-Repetitive Surge Current	I_{FSM}	8.3 ms, half Sine pulse	2700	A
Non-Repetitive Avalanche Energy	E_{AS}	T_J=25℃,I_{AS}=2A,L=4.5mH	9	mJ
Repetitive Avalanche Current	I_{AR}	Current decaying linearly to zero in 1 μsec Frequency limited by T_J max. V_A=3×V_R typical	2	A

Technical Data
Data Sheet N1175, Rev. A

RoHS

Electrical Characteristics:

Characteristics	Symbol	Condition	Typ.	Max.	Units
Forward Voltage Drop*	V_{F1}	@ 180A, Pulse, T_J = 25 °C @ 360A, Pulse, T_J = 25 °C	0.35 -	0.40 0.51	V
	V_{F2}	@ 180A, Pulse, T_J = 75 °C @ 360A, Pulse, T_J = 75 °C	0.30 -	0.34 0.45	V
Reverse Current*	I_{R1}	@V_R = rated V_R T_J = 25 °C	15	60	mA
	I_{R2}	@V_R = rated V_R T_J = 100 °C	1500	3000	mA
	I_{R3}	@V_R = 12V, T_J = 100 °C	1100	2670	mA
	I_{R4}	@V_R = 5V, T_J = 100 °C	700	1620	mA
Junction Capacitance	C_T	@V_R = 5V, T_C = 25 °C f_{SIG} = 1MHz	10000	12300	pF
Voltage Rate of Change	dv/dt	-	-	10,000	V/µs

* Pulse width < 300 µs, duty cycle < 2%

Thermal-Mechanical Specifications:


Characteristics	Symbol	Condition	Specification		Units
Junction Temperature	T_J	-	-55 to +125		°C
Storage Temperature	T_{stg}	-	-55 to +125		°C
Typical Thermal Resistance Junction to Case	$R_{\theta JC}$	DC operation	0.30		°C/W
Typical Thermal Resistance, case to Heat Sink	$R_{\theta cs}$	Mounting surface, smooth and greased	0.15		°C/W
Mounting Torque	T_M	Non-lubricated threads	Mounting Torque	23(min) 29(max)	Kg-cm
			Terminal Torque	35(min) 46(max)	
Approximate Weight	wt	-	25.6		g
Case Style	PRM1-1				

Technical Data
Data Sheet N1175, Rev. A


RoHS

Ratings and Characteristics Curves


Typical Forward Characteristics



Typical Reverse Characteristics



Typical Junction Capacitance




Ordering Information

Device	Package	Shipping
185NQ015-1	PRM1-1(Pb-Free)	27pcs/ box

For information on tape and reel specifications, including part orientation and tape sizes, please refer to our tape and reel packaging specification.

Marking Diagram




Where XXXX is YYWW

1st row SS YYWW
2nd row 185NQ015-1
SS = SS
YY = Year
WW = Week

Cautions: Molding resin
Epoxy resin UL:94V-0

Mechanical Dimensions PRM1-1 (Inches/Millimeters)



Technical Data
Data Sheet N1175, Rev. A

DISCLAIMER:
1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the SMC Diode Solutions sales department for the latest version of the datasheet(s).
2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment , and safety equipment) , safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement .
3- In no event shall SMC Diode Solutions be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). SMC Diode Solution assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
4- In no event shall SMC Diode Solutions be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
5- No license is granted by the datasheet(s) under any patents or other rights of any third party or SMC Diode Solutions.
6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of SMC Diode Solutions.
7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations..

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

SMC:

UG2KB100 MBR1550S SDURB860A SST24A-800BW MBRB10200CT SMBJ33CATR 5.0SMCJ33A MBR60150CT SDUR1040 STB60100C 151CMQ045 MBR30100 MBR4080CT MMSZ5261B CESD24VD5 MB6F SCT825B 3.0SMCJ22CA MBRF10100CT SDURD1030 STD20100CE 5.0SMCJ60CA MBR40200WT 183NQ100R-1 83CNQ080 BZT52B5V1S MBRF2060CT S2M0120120K S8ULCC36-2 SF14G