PMEG4010CEH
SCHOTTKY RECTIFIER DIODES

Features
- Average Forward Current:$I_{F(AV)}$=1A
- Polarity: Color band denotes cathode



SOD-123FL



Package Marking and Ordering Information

Product ID	Pack	Marking	Qty(PCS)
PMEG4010CEH	SOD-123FL	K14	3000

Maximum Ratings (Ta=25°C unless otherwise noted)

Single phase, half wave, 60Hz resistive or inductive load,
for capacitive load, derate by 20 %

Type Number		Limit	Units
Maximum Recurrent Peak Reverse Voltage		40	V
Maximum RMS Voltage		28	V
Maximum DC Blocking Voltage		40	V
Maximum Average Forward Rectified Current See Fig. 1		1.0	A
Peak Forward Surge Current, 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)		30	A
Maximum Instantaneous Forward Voltage at 1.0A		0.55	V
Maximum DC Reverse Current at Rated DC Blocking Voltage	Ta=25℃ Ta=100℃	0.2 10	mA mA
Typical Junction Capacitance (Note1)		110	pF
Typical Thermal Resistance RqJA (Note 2)		80	℃/W
Operating Temperature Range T_J		-65 —+125	℃
Storage Temperature Range T_{STG}		-65 — +150	℃

Notes:

1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.
2. Thermal Resistance Junction to Ambient.

Typical Characteristics

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-TYPICAL FORWARD CHARACTERISTICS




FIG.3-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.4-TYPICAL JUNCTION CAPACITANCE






FIG.5 - TYPICAL REVERSE CHARACTERISTICS



SOD-123FL Package Outline Dimensions



Attention

■ Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.

■ HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.

■ Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.

■ HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could
give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.

■ In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

■ No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.

■ Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

■ Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

HXY MOSFET:

60N06 AZ4007-01H ESD5LM5.0C-HXY HACPDQC5V0-HF PESDNC2XD5VBL BV05C-H HSEN3611D3 TPSMB100CA-VR HESDSLC3V3D3B HSTS521050B331 ESD5L5.0C-HXY LM393DR-HXY RLSD32A121V TPSMB28A-VR AQ15C-01FTG HAZ4007-01H HESD36VD3B HRCLAMP3371ZCTFT PJSD24CW_R1 HLY323BC1524L HCEZ36V,L3F PESDNC2XD5VBF PESDSC2FD5VU PJEC5V0M1FN2 AZ4836-01L HPTVSUC3D5VB HSD15C.TCT HSEN2411D3 HSG3D15B3.3MA PESDLC2FD3V3BH