# Push-in T-connector
# NPQM-T-Q4-E-P10

Part number: 558786



General operating condition

## Data sheet

| Feature | Value |
|---|---|
| Size | Standard |
| Nominal width | 3 mm |
| Design | T-shape |
| Pack size | 10 |
| Structural design | Push-pull principle |
| Operating pressure for entire temperature range | -0.095 MPa ... 1.6 MPa |
| Operating pressure for entire temperature range | -0.95 bar ... 16 bar |
| Operating pressure for entire temperature range | -13.775 psi ... 232 psi |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:-:-] |
| Information on operating and pilot media | Operation with oil lubrication possible |
| Corrosion resistance class (CRC) | 1 - Low corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Ambient temperature | -20 °C ... 70 °C |
| Product weight | 12.5 g |
| Pneumatic connection 1 | for pneumatic tubing outside diameter 4 mm |
| Pneumatic connection 2 | for pneumatic tubing outside diameter 4 mm |
| Note on materials | RoHS-compliant |
| Housing material | Brass, nickel-plated |
| Material of tubing seal | NBR |

# Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

## FESTO:

153031 153151 153307 HGL-1/8-QS-6 NPQP-Y-R12-Q12-FD QS-1/2-16 QS-10H-6 CRVZS-0.4 QSY-6H-4 SGS-M10X1,25 NPQP-T-Q8-E-FD-P10 QSLL-G1/2-12 QSML-6 QSS-8-F VABM-B10-25S-G38-10 153269 DSBC-80-20-D3-PPSA-N3 NPQP-LQ-R18-Q4-FD-P10 VBQF-U-G14-E NPQP-D-Q4-S8-FD-P10 VABM-B10-25S-G38-6-P3 NPQP-LQ-R18-Q8-FD-P10 NPQP-Y-Q6-E-FD-P10 SASC-P4-A-M8-A QS-1/8-8-I 153367 NPQH-T-Q14-E-P10 NPQP-L-Q10-E-FD-P10 QSF-1/4-8-B QSF-3/8-8-B