



目錄 MAPX	设变内容 MODIFICATION	日期 DATE









NOTES:
Housing: Thermoplastics,UL94V-0
Contact: Copper Alloy
Shell: Copper Alloy/Steel
Voltage Current Rating: 1.5 AMP. 30V AC
Insulation Resistance: 1000MΩ Min.
Contact Resistance: 30 MΩ Max.
Dielectric Withstanding Voltage: 500W AC
Temperature Range: -35℃ to +85℃
Insulator color: Black/White
Plastic material: PBT/LCP/Others
Shell finish: Nickel plated/Tin-Lead plated
Mechanical:
Mating Force: 3.5KG MAX
Unmating Force: 0.7 KG MIN.
Contact finish:
01: Selective Gold Flash
02: Selective Gold 3U"
03: Selective Gold 5U"
04: Selective Gold 15U"
05: Selective Gold 30U"

产品图
PRODUCT CHART DWG

公差一览表
TOLERANCE UNLESS OTHERWISE

X.	±0.25	X°.	±5°
.X	±0.20	.X°	±2°
.XX	±0.15	.XX°	±1°
.XXX	±0.10	.XXX°	±0.5°

深圳市精拓金电子有限公司

单位 UNITS	MM	制图 DRAWING	尹先华	产品料号 PRODUCT PART NO.	905-551A2021S10201
比例 SCALE	1:1	审核 CHKD	郭治富	产品名称 PRODUCT NO.	AF5.5超薄全贴有边铁壳LCP黑胶有柱
日期 DATE	2021-04-14	核准 APPD	黄国荣	角法 VIEW	版本 VER: A0

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Jing extension:

908-351A1011D10100 912-312A1012D10100 918-318K2023C40005 920-F52A2021S10105
904-232B2032S10100 906-262A1021D10200 906-752B1114D10200 912-112A1011D10100
912-112A2021S10100 919-162A1012D10400 906-552A1012D10200 907-312A1101Y10210
910-151A2021D10100 917-B88C201AH70201 920-A64A2091S101A3 907-111A1022D10200
916-151A1022Y10200 918-468K2029Y50000 920-154A2021Y10110 911-221A2021S10100
918-415K3028S40000 920-A62A2021S10104 920-C62A2021S10103 917-P81A202ES60201
920-C52A2021S10105 905-761A2032S10200 918-418K2022Y40011 920-A62A2021S10108
904-232A2031S10100 904-331B2032S10200