Rod eye
CRSGS-M16X1,5

Part number: 195584



General operating condition

Data sheet

Feature	Value
Size	M16x1.5
Corrosion resistance class (CRC)	3 - High corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L
Suitability for the production of Li-ion batteries	Metals with more than 5% by mass of copper, zinc or nickel by mass are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils
Ambient temperature	-40 °C ... 150 °C
Product weight	265 g
Note on materials	RoHS-compliant
Material of outer ring	High-alloy steel
Housing material	High-alloy steel
Inner raceway material	High-alloy steel
Nut material	High-alloy steel

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

NPQP-Y-R12-Q12-FD QS-10H-6 153307 NPQP-LQ-R18-Q8-FD-P10 QSF-3/8-8-B QSS-8-F VABM-B10-25S-G38-10 153031 CRVZS-0.4 QSF-1/4-8-B DSBC-80-20-D3-PPSA-N3 NPQP-Y-Q6-E-FD-P10 153151 QS-1/8-8-I QSLL-G1/2-12 NPQP-LQ-R18-Q4-FD-P10 VABM-B10-25S-G38-6-P3 SGS-M10X1,25 NPQH-T-Q14-E-P10 NPQP-D-Q4-S8-FD-P10 NPQP-L-Q10-E-FD-P10 QS-1/2-16 QSY-6H-4 VBQF-U-G14-E 153269 153367 HGL-1/8-QS-6 NPQP-T-Q8-E-FD-P10 QSML-6 SASC-P4-A-M8-A