IMZ120R220M1H

SiC Power MOSFET N-Channel Enhancement Mode

Features

- 3rd generation SiC MOSFET technology
- Optimized package with separate driver source pin
- High blocking voltage with low on-resistance
- High-speed switching with low capacitances
- Fast intrinsic diode with low reverse recovery (Q_{rr})
- Halogen free, RoHS compliant

Benefits


- Reduce switching losses and minimize gate ringing
- Higher system efficiency
- Reduce cooling requirements
- Increase power density
- Increase system switching frequency

Applications

- Motor Control
- EV Battery Chargers
- High Voltage DC/DC Converters



TO247-4L
Package



Ordering Part Number	Package	Qty(PCS)
IMZ120R220M1H	TO247-4L(TO-247-4)	30

Maximum Ratings (T_C = 25 ˚C unless otherwise specified)

Symbol	Parameter		Value	Unit	Note
V_{DSmax}	Drain - Source Voltage		1200	V	
V_{GSmax}	Gate - Source Voltage		-8/+19	V	Note: 1
I_D	Continuous Drain Current, V_{GS} = 15 V	T_C = 25˚C	17.9	A	Fig. 19 Note: 2
		T_C = 100˚C	13.5		
$I_{D(pulse)}$	Pulsed Drain Current, Pulse width t_P limited by T_{jmax}		34	A	Fig. 22
P_D	Power Dissipation, T_C=25˚C, T_J = 175 ˚C		103	W	Fig. 20 Note: 2
T_J , T_{stg}	Operating Junction and Storage Temperature		-55 to +175	˚C	
T_L	Solder Temperature, 1.6mm (0.063”) from case for 10s		260	˚C	
M_d	Mounting Torque , M3 or 6-32 screw		1 8.8	Nm lbf-in	

Note (1): Recommended turn off / turn on gate voltage V_{GS} - 4V...0V / +15V Note (2): Verified by design

Electrical Characteristics (T_C = 25˚C unless otherwise specified)

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions	Note
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	1200			V	V_{GS} = 0 V, I_D = 100 µA	
$V_{GS(th)}$	Gate Threshold Voltage	1.8	2.8	3.6	V	V_{DS} = V_{GS}, I_D = 2.33 mA	Fig. 11
			2.2		V	V_{DS} = V_{GS}, I_D = 2.33 mA, T_J = 175ºC	
I_{DSS}	Zero Gate Voltage Drain Current		1	50	µA	V_{DS} = 1200 V, V_{GS} = 0 V	
I_{GSS}	Gate-Source Leakage Current		10	250	nA	V_{GS} = 15 V, V_{DS} = 0 V	
$R_{DS(on)}$	Drain-Source On-State Resistance		159	208	mΩ	V_{GS} = 15 V, I_D = 8.5 A	Fig. 4, 5, 6
			280			V_{GS} = 15 V, I_D = 8.5 A, T_J = 175ºC	
g_{fs}	Transconductance		4.9		S	V_{DS}= 20 V, I_{DS}= 8.5 A	Fig. 7
			4.6			V_{DS}= 20 V, I_{DS}= 8.5 A, T_J = 175ºC	
C_{iss}	Input Capacitance		730		pF	V_{GS} = 0 V, V_{DS} = 0V to 1000 V F = 1 MHz V_{AC} = 25 mV	Fig. 17, 18
C_{oss}	Output Capacitance		31				
C_{rss}	Reverse Transfer Capacitance		2				
E_{oss}	C_{oss} Stored Energy		17		µJ		Fig. 16
$C_{o(er)}$	Effective Output Capacitance (Energy Related)		36		pF	V_{GS} = 0 V, V_{DS} = 0... 800V	Note: 3
$C_{o(tr)}$	Effective Output Capacitance (Time Related)		55		pF		
E_{ON}	Turn-On Switching Energy (External Diode)		81		µJ	V_{DS}= 800 V, V_{GS}= -4 V/15 V, I_D= 8.5 A, $R_{G(ext)}$ = 2.5 Ω, L= 404 µH, T_J = 175ºC FWD = External SiC DIODE	Fig. 26, 28
E_{OFF}	Turn Off Switching Energy (External Diode)		16				
E_{ON}	Turn-On Switching Energy (Body Diode FWD)		134		µJ	V_{DS}= 800 V, V_{GS}= -4 V/15 V, I_D= 8.5 A, $R_{G(ext)}$ = 2.5 Ω, L= 404 µH, T_J = 175ºC FWD = Internal Body Diode	Fig. 26, 28
E_{OFF}	Turn-Off Switching Energy (Body Diode FWD)		15				
$t_{d(on)}$	Turn-On Delay Time		8		ns	V_{DD} = 800 V, V_{GS} = -4 V/15 V I_D = 8.5 A, $R_{G(ext)}$ = 2.5 Ω, Timing relative to V_{DS} Inductive load	Fig. 27, 28
t_r	Rise Time		9				
$t_{d(off)}$	Turn-Off Delay Time		13				
t_f	Fall Time		12				
$R_{G(int)}$	Internal Gate Resistance		6.5		Ω	f = 1 MHz, V_{AC} = 25 mV	
Q_{gs}	Gate to Source Charge		10		nC	V_{DS} = 800 V, V_{GS} = -4 V/15 V I_D = 8.5 A Per IEC60747-8-4 pg 21	Fig. 12
Q_{gd}	Gate to Drain Charge		12				
Q_g	Total Gate Charge		32				

Note (3): $C_{o(er)}$, a lumped capacitance that gives same stored energy as Coss while Vds is rising from 0 to 800V
$C_{o(tr)}$, a lumped capacitance that gives same charging time as Coss while Vds is rising from 0 to 800V

Reverse Diode Characteristics (T_C = 25˚C unless otherwise specified)

Symbol	Parameter	Typ.	Max.	Unit	Test Conditions	Note
V_{SD}	Diode Forward Voltage	4.8		V	V_{GS} = -4 V, I_{SD} = 4.25 A, T_J = 25 °C	Fig. 8, 9, 10
		4.2		V	V_{GS} = -4 V, I_{SD} = 4.25 A, T_J = 175 °C	
I_S	Continuous Diode Forward Current		17	A	V_{GS} = -4 V, T_C = 25˚C	
$I_{S,\ pulse}$	Diode pulse Current		34	A	V_{GS} = -4 V, pulse width t_P limited by T_{jmax}	
t_{rr}	Reverse Recover time	9		ns	V_{GS} = -4 V, I_{SD} = 8.5 A, V_R = 800 V dif/dt = 6080 A/μs, T_J = 175 °C	
Q_{rr}	Reverse Recovery Charge	169		nC		
I_{rrm}	Peak Reverse Recovery Current	27		A		
t_{rr}	Reverse Recover time	23		ns	V_{GS} = -4 V, I_{SD} = 8.5 A, V_R = 800 V dif/dt = 1850 A/μs, T_J = 175 °C	
Q_{rr}	Reverse Recovery Charge	147		nC		
I_{rrm}	Peak Reverse Recovery Current	11		A		

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Unit	Test Conditions	Note
$R_{\theta JC}$	Thermal Resistance from Junction to Case	1.13	1.45	°C/W		Fig. 21

Typical Performance




Figure 1. Output Characteristics T_J = -55 ºC




Figure 2. Output Characteristics T_J = 25 ºC




Figure 3. Output Characteristics T_J = 175 ºC




Figure 4. Normalized On-Resistance vs. Temperature




Figure 5. On-Resistance vs. Drain Current
For Various Temperatures




Figure 6. On-Resistance vs. Temperature
For Various Gate Voltage

Typical Performance




Figure 7. Transfer Characteristic for Various Junction Temperatures




Figure 8. Body Diode Characteristic at -55 ºC




Figure 9. Body Diode Characteristic at 25 ºC




Figure 10. Body Diode Characteristic at 175 ºC




Figure 11. Threshold Voltage vs. Temperature




Figure 12. Gate Charge Characteristics

Typical Performance




Figure 13. 3rd Quadrant Characteristic at -55 ºC




Figure 14. 3rd Quadrant Characteristic at 25 ºC




Figure 15. 3rd Quadrant Characteristic at 175 ºC




Figure 16. Output Capacitor Stored Energy




Figure 17. Capacitances vs. Drain-Source Voltage (0 - 200V)




Figure 18. Capacitances vs. Drain-Source Voltage (0 - 1200V)

Typical Performance




Figure 19. Continuous Drain Current Derating vs. Case Temperature




Figure 20. Maximum Power Dissipation Derating vs. Case Temperature




Figure 21. Transient Thermal Impedance (Junction - Case)




Figure 22. Safe Operating Area




Figure 23. Clamped Inductive Switching Energy vs. Drain Current (V_{DD} = 600V)




Figure 24. Clamped Inductive Switching Energy vs. Drain Current (V_{DD} = 800V)

Typical Performance




Figure 25. Clamped Inductive Switching Energy vs. $R_{G(ext)}$




Figure 26. Clamped Inductive Switching Energy vs. Temperature




Figure 27. Switching Times vs. $R_{G(ext)}$




Figure 28. Switching Times Definition

Test Circuit Schematic






Figure 29. Clamped Inductive Switching Waveform Test Circuit

Package Dimensions

Package TO247-4L(TO-247-4)





SECTION "F-F", "G-G" AND "H-H"
SCALE: NONE


Package Dimensions

Package TO247-4L(TO-247-4)

NOTE ;
1. ALL METAL SURFACES: TIN PLATED, EXCEPT AREA OF CUT
2. DIMENSIONING & TOLERANCEING CONFIRM TO ASME Y14.5M-1994.
3. ALL DIMENSIONS ARE IN MILLIMETERS. ANGLES ARE IN DEGREES.
4. 'N' IS THE NUMBER OF TERMINAL POSITIONS

SYM	MILLIMETERS	
	MIN	MAX
A	4.83	5.21
A1	2.29	2.54
A2	1.91	2.16
b`	1.07	1.28
b	1.07	1.33
b1	2.39	2.94
b2	2.39	2.84
b3	1.07	1.60
b4	1.07	1.50
b5	2.39	2.69
b6	2.39	2.64
b7	1.30	1.70
c`	0.55	0.65
c	0.55	0.68
D	23.30	23.60
D1	16.25	17.65
D2	0.95	1.25
E	15.75	16.13

SYM	MILLIMETERS	
	MIN	MAX
E1	13.10	14.15
E2	3.68	5.10
E3	1.00	1.90
E4	12.38	13.43
e	2.54 BSC	
e1	5.08 BSC	
N*	4	
L	17.31	17.82
L1	3.97	4.37
L2	2.35	2.65
Ø P	3.51	3.65
Q	5.49	6.00
S	6.04	6.30
T	17.5° REF.	
W	3.5° REF.	
X	4° REF.	



Attention

■ Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.

■ HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.

■ Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.

■ HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could
give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.

■ In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

■ No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.

■ Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

■ Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

HXY MOSFET:

TLV74318PDBVR-HXY BD237STU C3M0040120D IDL10G65C5XUMA2 ISL28133FHZ-T7 DMPH6250SQ-13 DSC06065 TPD1E0B04DPYR HBAS40-05LT1G IRLML2244TRPBF-HXY MJD127G S4D15120H Si2323DS-T1-E3-HXY SS5150 C6D06065Q-TR CH440G E4D10120A ISL28233FUZ-T7 MUR1040FCT S3D08065E SGM3798YG/TR 2N7002-HXY C4D08120E-TR MSC040SMA120B4 SG3525-HXY 1SMB5930BT3G AOD403-HXY PTVSHC3D5VU 1SMB5934B TPS7A0533PDBZR-HXY