
REVISIONS		
LTR	DESCRIPTION	DATE
R	REVISED PER ECO-11-003178	02/14/2011
S	REVISED DWG PER ECO-11-014498	07/13/2011
T	ADDED -87 TO TABLE PER ECO-14-004606	03/26/2014



AS SUPPLIED

AFTER UNRESTRICTED RECOVERY

NOTES:

1. ALL DIMENSIONS ARE IN INCHES
2. DIMENSIONS APPEARING IN TABLE ARE AS FOLLOWS:
   - a _ AS SUPPLIED
   - b – AFTER UNRESTRICTED RECOVERY
3. ADD DASH NUMBER AS SUFFIX TO BASE PART NUMBER TO SPECIFY ID AND LENGTH REQUIRED
4. ORDERING INFORMATION:

RT-1145-OX -XX -0

BASE PART NUMBER

DASH NUMBER

(MATERIAL PER RW-3037(200) SPECIFICATION EXCLUDING LONGITUDINAL CHANGE)

COLOR DESIGNATOR (-0: BLACK, STANDARD)

5. RT-1145-OX-100-0 HAS ADHESIVE S-1337 LINED ON INSIDE OF TUBING

TABLE OF DIMENSIONS

PART DESCRIPTION	D MIN a	D MAX b	P REF b	W b
RT-1145-0X-7-0	2.67	.75	2.50	.055 – .095
RT-1145-0X-9-0	2.67	.75	1.50	.055 – .095
RT-1145-0X-11-0	2.37	.63	6.00	.050 – .090
RT-1145-0X-12-0	2.37	.63	2.50	.050 – .090
RT-1145-0X-14-0	2.37	.63	1.50	.050 – .090
RT-1145-0X-15-0	2.37	.63	1.00	.050 – .090
RT-1145-0X-16-0	1.37	.38	3.00	.042 – .066
RT-1145-0X-17-0	1.37	.38	2.50	.042 – .066
RT-1145-0X-18-0	1.37	.38	2.00	.042 – .066
RT-1145-0X-19-0	1.37	.38	1.50	.042 – .066
RT-1145-0X-20-0	1.37	.38	1.00	.042 – .066
RT-1145-0X-22-0	1.25	.31	2.50	.035 – .059
RT-1145-0X-24-0	1.25	.31	1.50	.035 – .059
RT-1145-0X-25-0	1.25	.31	1.00	.035 – .059
RT-1145-0X-26-0	1.00	.25	3.00	.033 – .053
RT-1145-0X-27-0	1.00	.25	2.50	.033 – .053
RT-1145-0X-29-0	1.00	.25	1.50	.033 – .053
RT-1145-0X-30-0	1.00	.25	1.00	.033 – .053
RT-1145-0X-32-0	2.00	.50	2.50	.045 – .085
RT-1145-0X-34-0	2.00	.50	1.50	.045 – .085
RT-1145-0X-35-0	2.00	.50	1.00	.045 – .085
RT-1145-0X-36-0	2.67	.75	4.00	.055 – .095
RT-1145-0X-37-0	2.37	.63	4.00	.050 – .090
RT-1145-0X-38-0	2.00	.50	4.00	.045 – .085
RT-1145-0X-39-0	1.37	.38	4.00	.042 – .066
RT-1145-0X-40-0	1.25	.31	4.00	.035 – .059
RT-1145-0X-41-0	1.00	.25	4.00	.033 – .053
RT-1145-0X-75-0	1.50	.38	6.00	.042 – .066
RT-1145-0X-76-0	1.25	.31	6.00	.035 – .059
RT-1145-0X-87-0	2.00	.50	18.00	.045 – .085
RT-1145-0X-97-0	1.75	.38	6.00	.042 – .066
RT-1145-0X-98-0	2.00	.50	10.00	.045 – .085
RT-1145-0X-100-0 (SEE 5)	3.00	1.00	4.00	.090 – .130
RT-1145-0X-132	0.38	0.13	2.00	.028 – .042
RT-1145-0X-133	0.50	0.19	2.00	.028 – .042

Raychem Molded Parts

CUSTOMER DRAWING

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE INCHES. METRIC DIMENSIONS ARE IN BRACKETS.

DECIMAL TOLERANCES

.XXX ± 0.005 [0.13 mm]
.XX ± 0.01 [0.25 mm]
.X ± 0.1 [0.50 mm]

ANGLE TOLERANCE

.X ± 1 DEG.

TYCO ELECTRONICS RESERVES THE RIGHT TO AMEND THIS DRAWING AT ANY TIME. USERS SHOULD EVALUATE THE SUITABILITY OF THE PRODUCT FOR THEIR APPLICATION.

REVISED UNGUYEN

APPROVED JKUSTER

THIRD ANGLE PROJECTION

TE Connectivity

TITLE: TUBING, SHRINK OVER-EXPANDED

SIZE	CODE IDENT. NO.	DWG. NO.
B	06090	RT-1145-0X-XX-0

© 2005-2014 Tyco Electronics Corporation. All rights reserved.

DO NOT SCALE THIS DRAWING

SHEET 1 OF 1

If this document is printed it becomes uncontrolled. Check for the latest revision

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TE Connectivity:

HSHC4508K2J RH73H2A40MKTN 1897725-2 2005330-1 3-1447221-5 2098557-4 MPT100C18RF 170376-2 175977-2 2-520263-2 2310537-1 292206-2 SBCHE154R7K HT-CT-50M-1-OUT-0 1-962915-1 1903112-2 ROX05SJ18R SBCHE64R7K T4133012081-000 1393454-9 2380312-2 282680-1 3631B101LL U5254-000005-030PA 917688-1 SMV1W220KJT TE50BR39J 2-521104-2 354022KFT CPF0402B37K4E1