
Anti-surge chip resistors

ESR series

Datasheet

●Features

1) Exclusive resistive element pattern and laser trimming technology results in significantly improved surge resistance characteristics.
2) 2kV to 5kV electrostatic discharge resistance.
3) Superior power ratings.
4) ROHM resistors have obtained ISO9001 / ISO / TS16949 certification.
5) Corresponds to AEC-Q200.



●Products list

Part No.	Size (mm)	Size (inch)	Rated power (70℃) (W)	Limiting element voltage (V)	Temperature coefficient (ppm/℃)	Resistance tolerance (%)	Resistance range (Ω)	Operating temperature range (℃)	Automotive grade available
ESR01	1005	0402	0.20	50	±100	F (±1%)	10≦R≦976k (E24/96 series)	-55 ～ +155	Yes
					±100	F (±1%)	1M≦R≦2.2M (E24 series)		
					+500/-250	J (±5%)	1≦R≦9.1 (E24 series)		
					±200	J (±5%)	10≦R≦10M (E24 series)		
ESR03	1608	0603	0.25	150	±100	D (±0.5%)	10≦R≦1M (E24/96 series)	-55 ～ +155	Yes
					±200	F (±1%)	1≦R<10 (E24/96 series)		
					±100	F (±1%)	10≦R≦10M (E24/96 series)		
					±200	J (±5%)	1≦R≦10M (E24 series)		
ESR10	2012	0805	0.40	150	±100	D (±0.5%)	10≦R≦1M (E24/96 series)	-55 ～ +155	Yes
					±100	F (±1%)	1≦R≦10M (E24/96 series)		
					±200	J (±5%)	1≦R≦10M (E24 series)		
ESR18	3216	1206	0.5	200	±100	D (±0.5%)	10≦R≦1M (E24/96 series)	-55 ～ +155	Yes
					±100	F (±1%)	1≦R≦10M (E24/96 series)		
					±200	J (±5%)	1≦R≦10M (E24 series)		
ESR25	3225	1210	0.66	200	±100	D (±0.5%)	10≦R≦1M (E24/96 series)	-55 ～ +155	Yes
					±100	F (±1%)	1≦R≦10M (E24/96 series)		
					±200	J (±5%)	1≦R≦10M (E24 series)		

* E24 : Standard products, E96 : Custom products.

●Part Number Description

E	S	R	1	0	E	Z	P	J	1	0	0

Part No.

ESR
(Anti-surge chip resistors)

Size (mm [inch])

01 (1005 [0402])
03 (1608 [0603])
10 (2012 [0805])
18 (3216 [1206])
25 (3225 [1210])

Packaging specifications code

Part No.	Code	Packaging specifications	Quantity / Reel
ESR01	MZP	Paper tape (4mm Pitch)	10,000
ESR03	EZP	Paper tape (4mm Pitch)	5,000
ESR10	EZP	Paper tape (4mm Pitch)	5,000
ESR18	EZP	Paper tape (4mm Pitch)	5,000
ESR25	JZP	Embossed tape (4mm Pitch)	4,000

Resistance tolerance

D (±0.5%)
F (±1%)
J (±5%)

Nominal resistance

Resistance code, 3 or 4 digits.
000 denotes jumper type.


Resistance tolerance		Resistance code
D,F	:	4 digits
J	:	3 digits

EX.)
1Ω = 1R00 (±1%)
1R0 (±5%)
10Ω = 10R0 (±0.5%,±1%)
100 (±5%)
1MΩ = 1004 (±0.5%,± 1%)
105 (±5%)


©2016 ROHM Co., Ltd. All rights reserved.

●Chip resistor dimensions and markings

■ESR01/03



■ESR10/18/25




<Marking method>
There are three or four digits used for the calculation number according to IEC code and "R" is used for the decimal point.

(Unit:mm)

Part No.	(mm)	(inch)	L	W	t	a	b	Marking existence
ESR01	1005	0402	1.00±0.05	0.50±0.05	0.35±0.05	0.20±0.10	$0.25^{+0.05}_{-0.10}$	No*
ESR03	1608	0603	1.60±0.10	0.80±0.10	0.45±0.10	0.30±0.20	0.30±0.20	No*
ESR10	2012	0805	2.00±0.10	1.25±0.10	0.55±0.10	0.30±0.20	0.40±0.20	Yes
ESR18	3216	1206	3.20±0.15	1.60±0.15	0.55±0.10	0.30±0.25	0.50±0.25	Yes
ESR25	3225	1210	3.20±0.15	2.50±0.15	0.55±0.10	0.30±0.25	0.50±0.25	Yes

*Only with spuare mark

●Land pattern example



(Unit:mm)


Dimensions / Part No.	A	B	C	D
ESR01	0.5	1.3	0.5	0.4
ESR03	1.0	2.0	0.8	0.5
ESR10	1.2	2.6	1.15	0.70
ESR18	2.2	4.0	1.5	0.9
ESR25	2.2	4.0	2.3	0.9

©2016 ROHM Co., Ltd. All rights reserved.

●Derating curve

When the ambient temperature exceeds 70°C, power dissipation must be adjusted according to the derating curves below.

■ESR01 / 03 / 10 / 18 / 25



●Characteristics

Test items	Guaranteed balue Resistor type	Test conditions
Resistance	See P.1	20°C
Variation of resistance with temperature	See P.1	Measurement: +25/-55, +25/+125°C
Overload	±(2.0%+0.1Ω)	Test voltage is the smaller one of ① or ② ①Rated voltage(current)×2.5,(ESR03/10/18/25) 2s Rated voltage(current)×2.0,(ESR01) 2s ②Maximum overload voltage ※
Solderability	A new uniform coating of minimum of 95% of the surface being immersed and no soldering damage.	Rosin-ethanol solution(25% weight) Soldering condition: 245±5°C Duration of immersion: 2.0±0.5s
Resistance to soldering heat	±(1.0%+0.05Ω) No remarkable abnormality on the appearance.	Soldering condition: 260±5°C Duration of immersion: 10±1s
Rapid change of temperature	±(1.0%+0.05Ω)	Test temp: -55°C～+125°C 5cycle
Damp heat, steady state	±(3.0%+0.1Ω)	40°C, 93%(Relative humidity) Test time: 1,000h
Endurance at 70°C	±(3.0%+0.1Ω)	Rated voltage(current),70°C 1.5h:ON−0.5h:OFF Test time: 1,000h
Endurance	±(3.0%+0.1Ω)	155°C Test time: 1000h
Resistance to solvent	±(1.0%+0.05Ω)	23±5°C _ED057 Solvent: 2-propanol
Bend strength of the end face plating	±(1.0%+0.05Ω) Without mechanical damage such as breaks.	-
Static electric characteristics	±(5.0%+0.05Ω)	EIAJ ED-4701/300 Test method 304 Voltage: 2kV(ESR01) 3kV(ESR03/10/18) 5kV(ESR25) C: 100pF R: 1.5kΩ Apply cycle: Times.

Compliance Standard(s) : IEC60115-8
JISC 5201-8


※Maximum overload voltage (Test voltage)

ESR01	ESR03	ESR10	ESR18	ESR25
100V	200V	200V	400V	400V

© 2016 ROHM Co., Ltd. All rights reserved.

●Tape dimensions

■Paper tape




(Unit : mm)

Part No.	W	F	E	A0	B0
ESR01	8.0±0.3	3.5±0.05	1.75±0.1	0.7±0.1	1.2±0.1
ESR03	8.0±0.3	3.5±0.05	1.75±0.1	1.1±0.1	1.9±0.1
ESR10	8.0±0.3	3.5±0.05	1.75±0.1	$1.65^{+0.2}_{-0.1}$	$2.4^{+0.2}_{-0.1}$
ESR18	8.0±0.3	3.5±0.05	1.75±0.1	$1.95^{+0.1}_{-0.05}$	$3.5^{+0.15}_{-0.05}$

Part No.	D0	P0	P1	P2	T2
ESR01	$\Phi1.5^{+0.1}_{0}$	4.0±0.1	2.0±0.05	2.0±0.05	MAX1.1
ESR03	$\Phi1.5^{+0.1}_{0}$	4.0±0.1	4.0±0.1	2.0±0.05	MAX1.1
ESR10	$\Phi1.5^{+0.1}_{0}$	4.0±0.1	4.0±0.1	2.0±0.05	MAX1.1
ESR18	$\Phi1.5^{+0.1}_{0}$	4.0±0.1	4.0±0.1	2.0±0.05	MAX1.1


■Embossed tape



(Unit : mm)

Part No.	W	F	E	A0	B0
ESR25	8.0±0.3	3.5±0.05	1.75±0.1	3.0±0.1	3.5±0.1
	D0	P0	P1	P2	T2
	$\Phi1.5^{+0.1}_{0}$	4.0±0.1	4.0±0.1	2.0±0.05	MAX1.1

●Reel dimensions



(Unit : mm)

Part No.	A	B	C	D
ESR01	$\Phi180^{0}_{-1.5}$	$\Phi60^{+1}_{0}$	$9^{+1.0}_{0}$	Φ13±0.2
ESR03				
ESR10				
ESR18				
ESR25				

©2016 ROHM Co., Ltd. All rights reserved.

Notice

Precaution on using ROHM Products

1. If you intend to use our Products in devices requiring extremely high reliability (such as medical equipment(Note 1), aircraft/spacecraft, nuclear power controllers, etc.) and whose malfunction or failure may cause loss of human life, bodily injury or serious damage to property ("Specific Applications"), please consult with the ROHM sales representative in advance. Unless otherwise agreed in writing by ROHM in advance, ROHM shall not be in any way responsible or liable for any damages, expenses or losses incurred by you or third parties arising from the use of any ROHM's Products for Specific Applications.

(Note1) Medical Equipment Classification of the Specific Applications

JAPAN	USA	EU	CHINA
CLASSⅢ	CLASSⅢ	CLASSⅡb	CLASSⅢ
CLASSⅣ		CLASSⅢ	

2. ROHM designs and manufactures its Products subject to strict quality control system. However, semiconductor products can fail or malfunction at a certain rate. Please be sure to implement, at your own responsibilities, adequate safety measures including but not limited to fail-safe design against the physical injury, damage to any property, which a failure or malfunction of our Products may cause. The following are examples of safety measures:
   [a] Installation of protection circuits or other protective devices to improve system safety
   [b] Installation of redundant circuits to reduce the impact of single or multiple circuit failure

3. Our Products are not designed under any special or extraordinary environments or conditions, as exemplified below. Accordingly, ROHM shall not be in any way responsible or liable for any damages, expenses or losses arising from the use of any ROHM's Products under any special or extraordinary environments or conditions. If you intend to use our Products under any special or extraordinary environments or conditions (as exemplified below), your independent verification and confirmation of product performance, reliability, etc, prior to use, must be necessary:
   [a] Use of our Products in any types of liquid, including water, oils, chemicals, and organic solvents
   [b] Use of our Products outdoors or in places where the Products are exposed to direct sunlight or dust
   [c] Use of our Products in places where the Products are exposed to sea wind or corrosive gases, including Cl2, H2S, NH3, SO2, and NO2
   [d] Use of our Products in places where the Products are exposed to static electricity or electromagnetic waves
   [e] Use of our Products in proximity to heat-producing components, plastic cords, or other flammable items
   [f] Sealing or coating our Products with resin or other coating materials
   [g] Use of our Products without cleaning residue of flux (even if you use no-clean type fluxes, cleaning residue of flux is recommended); or Washing our Products by using water or water-soluble cleaning agents for cleaning residue after soldering
   [h] Use of the Products in places subject to dew condensation

4. The Products are not subject to radiation-proof design.

5. Please verify and confirm characteristics of the final or mounted products in using the Products.

6. In particular, if a transient load (a large amount of load applied in a short period of time, such as pulse. is applied, confirmation of performance characteristics after on-board mounting is strongly recommended. Avoid applying power exceeding normal rated power; exceeding the power rating under steady-state loading condition may negatively affect product performance and reliability.

7. De-rate Power Dissipation (Pd) depending on Ambient temperature (Ta). When used in sealed area, confirm the actual ambient temperature.

8. Confirm that operation temperature is within the specified range described in the product specification.

9. ROHM shall not be in any way responsible or liable for failure induced under deviant condition from what is defined in this document.

Precaution for Mounting / Circuit board design

1. When a highly active halogenous (chlorine, bromine, etc.) flux is used, the residue of flux may negatively affect product performance and reliability.

2. In principle, the reflow soldering method must be used on a surface-mount products, the flow soldering method must be used on a through hole mount products. If the flow soldering method is preferred on a surface-mount products, please consult with the ROHM representative in advance.

For details, please refer to ROHM Mounting specification

© 2016 ROHM Co., Ltd. All rights reserved.

Precautions Regarding Application Examples and External Circuits

1. If change is made to the constant of an external circuit, please allow a sufficient margin considering variations of the characteristics of the Products and external components, including transient characteristics, as well as static characteristics.
2. You agree that application notes, reference designs, and associated data and information contained in this document are presented only as guidance for Products use. Therefore, in case you use such information, you are solely responsible for it and you must exercise your own independent verification and judgment in the use of such information contained in this document. ROHM shall not be in any way responsible or liable for any damages, expenses or losses incurred by you or third parties arising from the use of such information.

Precaution for Electrostatic

This Product is electrostatic sensitive product, which may be damaged due to electrostatic discharge. Please take proper caution in your manufacturing process and storage so that voltage exceeding the Products maximum rating will not be applied to Products. Please take special care under dry condition (e.g. Grounding of human body / equipment / solder iron, isolation from charged objects, setting of Ionizer, friction prevention and temperature / humidity control).

Precaution for Storage / Transportation

1. Product performance and soldered connections may deteriorate if the Products are stored in the places where:
   [a] the Products are exposed to sea winds or corrosive gases, including Cl2, H2S, NH3, SO2, and NO2
   [b] the temperature or humidity exceeds those recommended by ROHM
   [c] the Products are exposed to direct sunshine or condensation
   [d] the Products are exposed to high Electrostatic
2. Even under ROHM recommended storage condition, solderability of products out of recommended storage time period may be degraded. It is strongly recommended to confirm solderability before using Products of which storage time is exceeding the recommended storage time period.
3. Store / transport cartons in the correct direction, which is indicated on a carton with a symbol. Otherwise bent leads may occur due to excessive stress applied when dropping of a carton.
4. Use Products within the specified time after opening a humidity barrier bag. Baking is required before using Products of which storage time is exceeding the recommended storage time period.

Precaution for Product Label

QR code printed on ROHM Products label is for ROHM's internal use only.

Precaution for Disposition

When disposing Products please dispose them properly using an authorized industry waste company.

Precaution for Foreign Exchange and Foreign Trade act

Since concerned goods might be fallen under listed items of export control prescribed by Foreign exchange and Foreigntrade act, please consult with ROHM in case of export.

Precaution Regarding Intellectual Property Rights

1. All information and data including but not limited to application example contained in this document is for reference only. ROHM does not warrant that foregoing information or data will not infringe any intellectual property rights or any other rights of any third party regarding such information or data.
2. ROHM shall not have any obligations where the claims, actions or demands arising from the combination of the Products with other articles such as components, circuits, systems or external equipment (including software).
3. No license, expressly or implied, is granted hereby under any intellectual property rights or other rights of ROHM or any third parties with respect to the Products or the information contained in this document. Provided, however, that ROHM will not assert its intellectual property rights or other rights against you or your customers to the extent necessary to manufacture or sell products containing the Products, subject to the terms and conditions herein.

Other Precaution

1. This document may not be reprinted or reproduced, in whole or in part, without prior written consent of ROHM.
2. The Products may not be disassembled, converted, modified, reproduced or otherwise changed without prior written consent of ROHM.
3. In no event shall you use in any way whatsoever the Products and the related technical information contained in the Products or this document for any military purposes, including but not limited to, the development of mass-destruction weapons.
4. The proper names of companies or products described in this document are trademarks or registered trademarks of ROHM, its affiliated companies or third parties.

© 2016 ROHM Co., Ltd. All rights reserved.

General Precaution

1. Before you use our Pro ducts, you are requested to care fully read this document and fully understand its contents. ROHM shall not be in any way responsible or liable for failure, malfunction or accident arising form the use of any ROHM's Products against warning, caution or note contained in this document.

2. All information contained in this document not is current as of the issuing date and subject to change without any prior notice. Before purchasing or using ROHM's Products, please confirm the la test information with a ROHM sales representative.

3. The information contained in this document is provided on an "as in" basis and ROHM does not warrant that all information contained in this document is accurate and/or error-free. ROHM shall not be in any way responsible or liable for any damages, expenses or losses incurred by you or third parties resulting form inaccuracy or errors of or concerning such information.

© 2016 ROHM Co., Ltd. All rights reserved.

ESR01MZPF - Web Page

Buy

Distribution Inventory

Part Number	ESR01MZPF
Package	
Unit Quantity	10000
Minimum Package Quantity	10000
Packing Type	Taping
Constitution Materials List	inquiry
RoHS	Yes

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

ROHM:

RB706W-40TL SCT4013DRHRC15 2SA1036KT146Q 2SA2018E3HZGTL BA178M09FP-E2 HP8S36TB
BR24G16FVJ-3GTE2 BR24L01AF-WE2 DTC124EE3HZGTL EMX51T2R RB-D62Q1367TB32
BM2P121XH-Z YFZVFHTR6.8B DTA143XKAT146 KDZVTFTR5.6B KTR18EZPF4703 RB168VAM-40TR
RB751VM-40TE-17 SML-D12M8WT86C 2SC4102U3HZGT106R BZX84C3V9LYFHT116 ESD16VHYFHT116
RB541VM-30FHTE-17 2SC4081UBTLR 2SC4617EBTLQ DTA143ZCAHZGT116 YQ5RSM10SDTFTL1
BU28TD2WNVX-TL DTB523YE3TL HP8K22TB