

# Air solenoid valve
# VUVG-LK14-B52-T-G18-1R8L-S

Part number: 8042568






General operating condition

## Data sheet

| Feature | Value |
|---|---|
| Valve function | 5/2, bistable |
| Actuation type | Electrical |
| Valve size | 14 mm |
| Standard nominal flow rate | 660 l/min |
| Pneumatic working port | G1/8 |
| Operating voltage | 24V DC |
| Operating pressure | 0.15 MPa ... 0.7 MPa |
| Operating pressure | 1.5 bar ... 7 bar |
| Structural design | Piston slide with sealing ring |
| Certification | c UL us - Recognized (OL) |
| Certificate issuing authority | UL MH19482 |
| Degree of protection | IP65 |
| Exhaust air function | With flow control option |
| Sealing principle | Soft |
| Mounting position | Any |
| Manual override | Detenting<br>Non-detenting |
| Type of control | Pilot-controlled |
| Pilot air supply port | Internal |
| Flow direction | Non-reversible |
| Symbol | 00992897 |
| Lap | Overlap |
| Signal status display | LED |
| Max. switching frequency | 2 Hz |
| Changeover time | 8 ms |
| Duty cycle | 100% |
| Max. positive test pulse with 0 signal | 1600 µs |
| Max. negative test pulse on 1 signal | 3000 µs |
| Coil characteristics | 24 V DC: 0.8 W |
| Permissible voltage fluctuations | +/- 10 % |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Vibration resistance | Transport application test with severity level 1 as per FN 942017-4 and EN 60068-2-6 |
| Shock resistance | Shock test with severity level 1 as per FN 942017-5 and EN 60068-2-27 |
| Corrosion resistance class (CRC) | 0 - No corrosion stress |

| Feature | Value |
|---|---|
| LABS (PWIS) conformity | VDMA24364 zone III |
| Temperature of medium | -5 °C ... 50 °C |
| Pilot medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Ambient temperature | -5 °C ... 50 °C |
| Product weight | 85 g |
| Electrical connection | 3-pin<br>M8x1 A-coded as per EN 61076-2-104<br>Plug |
| Type of mounting | On terminal strip<br>With through-hole |
| Pneumatic connection 2 | G1/8 |
| Pneumatic connection 4 | G1/8 |
| Note on materials | RoHS-compliant |
| Seals material | HNBR<br>NBR |
| Housing material | Wrought aluminum alloy |

# Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

## FESTO:

VABM-B10-25S-G38-6 VABM-L1-14W-G14-4-GR DSBC-32-50-D3-PPVA-N3 DSBC-40-160-D3-PPSA-N3 DSBC-50-20-D3-PPSA-N3 DSBC-40-50-D3-PPSA-N3 NPQH-T-G38-Q8-P10 QS-G1/8-6-I QSL-12 SPTW-P16R-G14-A-M12 DSBC-32-40-D3-PPVA-N3 NPQH-D-Q14-E-P10 NPQP-D-R38-Q10-FD-P10 QSLV-G1/8-8 SEA-3GS-M8-S NPQH-D-S14-Q8-P10 QSL-1/4-4 QSLV-G1/4-6 DSBC-63-320-D3-PPVA-N3 NPQP-D-R14-Q10-FD-P10 VABM-B10-20S-G14-6 153034 QSLV-G1/2-12-I VABM-B10-25S-G38-4-P3 VABM-L1-10HW-G18-4-GR VABM-L1-18S-G38-10 DFM-63-100-P-A-KF HGL-1/8-B NPQH-D-Q12-Q8-P10 QS-G3/8-12