
NTMFS4936NCT1G

N-Channel Enhancement Mode MOSFET

Description

The NTMFS4936NCT1G uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with gate voltages as low as 4.5V. This device is suitable for use as a Battery protection or in other Switching application.




DFN5X6-8L

General Features

V_{DS} = 30V I_D =120A

$R_{DS(ON)}$ < 2.6mΩ V_{GS}=10V



N-Channel MOSFET

Application

Battery protection

Load switch

Uninterruptible power supply

Package Marking and Ordering Information

Product ID	Pack	Brand	Qty(PCS)
NTMFS4936NCT1G	DFN5X6-8L	HXY MOSFET	5000

Absolute Maximum Ratings (T_C=25°C unless otherwise noted)

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	30	V
V_{GS}	Gate-Source Voltage	±20	V
I_D@T_C=25℃	Continuous Drain Current, V_{GS} @ 10V	120	A
I_D@T_C=100℃	Continuous Drain Current, V_{GS} @ 10V	57	A
I_{DM}	Pulsed Drain Current	360	A
EAS	Single Pulse Avalanche Energy	125	mJ
P_D	Total Power Dissipation[4]	115	W
T_{STG}	Storage Temperature Range	-55 to 175	℃
T_J	Operating Junction Temperature Range	-55 to 175	℃
$R_{\theta JA}$	Thermal Resistance Junction-Ambient	62	℃/W
$R_{\theta JC}$	Thermal Resistance Junction-Case[2]	1.3	℃/W

Electrical Characteristics (T_J=25°C, unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
Off Characteristics						
BV_{DSS}	Drain-Sourtce Breakdown Voltage	V_{GS}=0V,I_D=250μA	30	---	---	V
I_{DSS}	Zero Gate Voltage Drain Current	V_{GS}=0V, V_{DS}=30V	---	---	1	μA
I_{GSS}	Gate-Source Leakage Current	V_{GS}=±20V, V_{DS}=0A	---	---	±100	nA
On Characteristics[3]						
$V_{GS(th)}$	GateSource Threshold Voltage	V_{GS}=V_{DS}, I_D=250μ A	1	1.6	2.5	V
$R_{DS(ON)}$	Drain-Source On Resistance[2]	V_{GS}=10V,I_D=20A	---	2.6	3.3	mΩ
		V_{GS}=4.5V,I_D=10A	---	3.8	5	
Dynamic Characteristics						
C_{iss}	Input Capacitance	V_{DS}=25V, V_{GS}=0V, f=1MHz	---	2218	---	pF
C_{oss}	Output Capacitance		---	480	---	
C_{rss}	Reverse Transfer Capacitance		---	340	---	
Switching Characteristics						
$t_{d(on)}$	Turn-On Delay Time [3,4]	V_{DD}=15V,I_D=15A, R_G=3.3Ω V_{GS}=10V	---	12.6	---	ns
t_r	Rise Time[3,4]		---	19.5	---	ns
$t_{d(off)}$	Turn-Off Delay Time [3,4]		---	42.8	---	ns
t_f	Fall Time[3,4]		---	13.2	---	ns
Q_g	Total Gate Charge [3,4]	V_{GS}=4.5V, V_{DS}=15V, I_D=20A	---	24	---	nC
Q_{gs}	Gate-Source Charge [3,4]		---	4.2	---	nC
Q_{gd}	Gate-Drain “Miller” Charge [3,4]		---	13	---	nC
Drain-Source Diode Characteristics						
V_{SD}	Source-Drain Diode Forward Voltage[3]	V_{GS}=0V,I_S=1A	---	---	1	V
IS	Continuous Source Current	V_G=V_D=0V , Force Current	---	---	120	A
ISM	Pulsed Source Current		---	---	360	A
Trr	Reverse Recovery Time	V_{GS}=30V,I_S=1A , di/dt=100A/μs T_J=25°C	---	258	---	NS
Qrr	Reverse Recovery Charge		---	324	---	NC

Notes:

1. Repetitive Rating : Pulsed width limited by maximum junction temperature.
2. V_{DD}=25V,V_{GS}=10V,L=0.1mH,I_{AS}=50A.,R_G=25Ω ,Starting T_J=25°C.
3. The data tested by pulsed , pulse width ≦ 300us , duty cycle ≦ 2%.
4. Essentially independent of operating temperature.

Typical Characteristics




Fig.1 Continuous Drain Current vs. T_C




Fig.2 Normalized RDSON vs. T_J




Fig.3 Normalized V_{th} vs. T_J




Fig.4 Gate Charge Waveform




Fig.5 Normalized Transient Impedance




Fig.6 Maximum Safe Operation Area




Fig.7 Switching Time Waveform





Fig.8 EAS Waveform

DFN5X6-8L Package Information



SYMBOL	MM			INCH		
	MIN	NOM	MAX	MIN	NOM	MAX
A	5.3	5.5	5.7	0.208	0.216	0.224
A1	5.1	5.2	5.3	0.2	0.204	0.209
D	5.98	6	6.02	0.235	0.236	0.237
D1	5.85	6.05	6.25	0.23	0.238	0.246
B	0.85	0.95	1.05	0.033	0.037	0.041
B1		0.254REF			0.010REF	
C	3.95	4	4.05	0.156	0.157	0.159
C1	0.35	0.4	0.45	0.014	0.016	0.018
C2		1.27TYP			0.5TYP	
θ1	8°	10°	12°	8°	10°	12°
L1	0.63	0.64	0.65	0.025	0.025	0.026
L2	1.2	1.3	1.4	0.047	0.051	0.055
L3	3.415	3.42	3.425	0.134	0.135	0.135
H	0.24	0.25	0.26	0.009	0.010	0.010

Attention

■ Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.

■ HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.

■ Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.

■ HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could
give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.

■ In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

■ No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.

■ Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

■ Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

HXY MOSFET:

HT7150 HT7540-1 HXY2101EI HXY8205ES IRLML6246PBF TPSMB100CA-VR HOPA2340UA
P6SMB200A SS10100 HAD8542ARZ HC3D10170A HC4D20120A HESDNC5VB1AF-B MAX487ESA
PESD5V0S1BB SS1045 BZT52C13 P6SMB36CA SQJA04EP-T1_BE3 TPSMB28A-VR DTC143ZE US2M
HMCP602-I/SN MMBT3904T SD15C SS5150B SS510C BZT52C3V3S HXY2300MI P6SMB33CA