
T-distributor
FCK-3-PK-9-KU

Part number: 6276



General operating condition

Data sheet

Feature	Value
Nominal width	8 mm
Mounting position	Any
Design	T-shape
Pack size	10
Operating pressure for entire temperature range	-0.095 MPa ... 1 MPa
Operating pressure for entire temperature range	-0.95 bar ... 10 bar
Operating pressure for entire temperature range	-13.775 psi ... 145 psi
Operating medium	Compressed air as per ISO 8573-1:2010 [7:-:-]
Information on operating and pilot media	Operation with oil lubrication possible
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	-10 °C ... 60 °C
Pneumatic connection 1	For barbed fitting, inside diameter 9 mm, with union nut
Pneumatic connection 2	for barbed fitting, inside diameter 9 mm, with nut
Material of union nut	POM
Note on materials	RoHS-compliant
Connector material	POM

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

CRVZS-0.4 DSBC-50-20-D3-PPSA-N3 N-1/8-P-6 QS-1/2-16 DSBC-32-50-D3-PPVA-N3 DSBC-80-320-D3-PPVA-N3 NPQP-Y-Q6-E-FD-P10 QSLL-1/4-4 DSBC-63-320-D3-PPVA-N3 NPQP-D-Q4-S8-FD-P10 DFM-63-100-P-A-KF VABM-L1-18W-G38-8-G SPTE-V1R-Q3-V-2.5K DSBC-32-40-D3-PPVA-N3 DSBC-80-250-D3-PPSA-N3 NPQP-Y-R12-Q12-FD QSML-6 NPQH-T-G38-Q8-P10 QSLV-G1/4-6 QSS-8-F SNC-63 NPQP-LQ-R18-Q4-FD-P10 VBQF-U-G14-E DSNU-12-60-P-A MSFW-110-50/60-DS NPQP-L-Q10-E-FD-P10 NPQP-LQ-R18-Q8-FD-P10 PUN-H-4X0,75-TBL QH-1 1/2 QSML-3