
Spec Sheet

Inductors

NRM6045T330MMRRV



Features

- Item Summary

  33uH±20%, 0.75A(⊿L=30%,⊿T=20℃),

  6.0x6.0x4.5mm
- Lifecycle Stage

  New PN available
- AEC-Q200 qualified
- Standard packaging quantity (minimum)

  Taping Embossed 1500pcs

Products characteristics table

Inductance	33 uH ± 20 %
Case Size (mm)	6.0x6.0
Rated Current (max)	0.75 A (⊿L=30%, ⊿T=20℃), 1.25 A (⊿L=30%, ⊿T=40℃)
Saturation Current (max)	1.75 A (⊿L=30%)
Saturation Current (typ)	1.95 A (⊿L=30%)
Temperature Rise Current① (max)	0.75 A (⊿T=20℃)
Temperature Rise Current① (typ)	0.95 A (⊿T=20℃)
Temperature Rise Current② (max)	1.25 A (⊿T=40℃)
Temperature Rise Current② (typ)	1.35 A (⊿T=40℃)
DC Resistance (max)	0.216 Ω
DC Resistance (typ)	0.18 Ω
LQ Measuring Frequency	100 kHz
Self Resonant Frequency (min)	7.5 MHz
Operating Temp. Range	-40 to +125 ℃ (Including-self-generated heat)
Temperature characteristic (Inductance change)	± 20 %
RoHS Compliance (10 subst.)	Yes
REACH Compliance (223 subst.)	Yes
Halogen Free	Yes
Soldering	Reflow


External Dimensions

Dimension L	6.0 ±0.2 mm
Dimension W	6.0 ±0.2 mm
Dimension H	Max 4.5 mm
Dimension e	1.65 ±0.3 mm
Dimension k (ref)	Min 0.3 mm

Recommended Land Patterns

【推奨ランドパターン】
実装上の注意
・実装状態を確認の上ご使用くださいますようお願いいたします。

【Recommended Land Patterns】
Surface Mounting
・Mounting and soldering conditions should be checked beforehand.
・Applicable soldering process to this products is reflow soldering only.





2022.06.02


The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
TAIYO YUDEN reserves the right to make change to the data at any time without notice.
Before making final selection, please check product specification.

NRM6045T330MMRRV









The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
TAIYO YUDEN reserves the right to make change to the data at any time without notice.
Before making final selection,please check product specification.

The products are tested based on the test conditions and methods defined in AEC-Q200.
Please consult with TAIYO YUDEN for the details of the product specification and AEC-Q200 test results,etc., and please review and approve TAIYO YUDEN's product Specification before ordering.

■Notice for TAIYO YUDEN Products

Please read this notice before using the TAIYO YUDEN products.

REMINDERS

- Please conduct validation and verification of our products in actual condition of mounting and operating environment before using our products.
- The product listed in this spec sheet is intended for use in general electronic equipment (e.g., AV equipment, OA equipment, home electric appliances, office equipment, information and communication equipment including, without limitation, mobile phone, and PC). Please be sure to contact TAIYO YUDEN for further information before using the products for any equipment which may directly cause loss of human life or bodily injury (e.g., transportation equipment including, without limitation, automotive powertrain control system, train control system, and ship control system, traffic signal equipment, disaster prevention equipment, medical equipment classified as Class I, II or III by IMDRF, highly public information network equipment including, without limitation, telephone exchange, and base station).
  Please do not incorporate our products into any equipment requiring high levels of safety and/or reliability (e.g., aerospace equipment, aviation equipment, medical equipment classified as Class IV by IMDRF, nuclear control equipment, undersea equipment, military equipment).
  When our products are used even for high safety and/or reliability-required devices or circuits of general electronic equipment, it is strongly recommended to perform a thorough safety evaluation prior to use of our products and to install a protection circuit as necessary.
  Please note that unless you obtain prior written consent of TAIYO YUDEN, TAIYO YUDEN shall not be in any way responsible for any damages incurred by you or third parties arising from use of the product listed in this spec sheet for any equipment requiring inquiry to TAIYO YUDEN or prohibited for use by TAIYO YUDEN as described above.
- Information contained in this spec sheet is intended to convey examples of typical performances and/or applications of our products and is not intended to make any warranty with respect to the intellectual property rights or any other related rights of TAIYO YUDEN or any third parties nor grant any license under such rights.
- Please note that the scope of warranty for our products is limited to the delivered our products themselves and TAIYO YUDEN shall not be in any way responsible for any damages resulting from a fault or defect in our products. Notwithstanding the foregoing, if there is a written agreement (e.g., supply and purchase agreement, quality assurance agreement) signed by TAIYO YUDEN and your company, TAIYO YUDEN will warrant our products in accordance with such agreement.
- The contents of this spec sheet are applicable to our products which are purchased from our sales offices or authorized distributors (hereinafter “TAIYO YUDEN’s official sales channel”). Please note that the contents of this spec sheet are not applicable to our products purchased from any seller other than TAIYO YUDEN’s official sales channel.
- Caution for Export
  The product listed in this spec sheet may require specific procedures for export according to “U.S. Export Administration Regulations”, “Foreign Exchange and Foreign Trade Control Law” of Japan, and other applicable regulations. Should you have any questions on this matter, please contact our sales staff.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TAIYO YUDEN:

JMK316BBJ107MLHT LCENA2520MKT1R0M0NK LCXND6060PKT150MMG LMK105BJ224KV-F MEKK2520T1R5M MSASE31LBB7226MTNA01 TMK105CBJ225KV-F JMK316ABJ476ML-T JMK325ABJ107MM-P LSXND4040MKL330MDG MSAST1L3YB5474MFNA01 UMK325B7105KNHT UMJ325AB7475KMHP UMK107BJ474KAHT FBMH1608HM471-T JMK316BJ476ML-T LSMGA160808T471RG NRS3015T4R7MNGH NS10155T3R3NNV8 NS12555T470MNV UMK107BBJ225KA-T HMK325AD7106KM-PE MCASL31LAB5226KTNA01 MCASU105SB7682KFNA01 NS10165T100MNVV LSMCC451611T111RG LSXND5050PKT220MMG MSASL32MAB5107MPNA01 NR4018T220M HMK316AC7225KL-TE