PT4800FE000F

Opaque Resin, Medium Directivity Angle, Thin Package Phototransistor

■ Features

1. Side view detection thin package
2. Plastic mold with opaque resin lens
3. Peak sensitivity wavelength: 860 nm (TYP.)
4. Medium directivity angle (Δθ ±35° TYP.)
5. Lead free and RoHS directive compliant

■ Agency Approvals/Compliance

1. Compliant with RoHS directive (2002/95/EC)
2. Content information about the six substances specified in “Management Methods for Control of Pollution Caused by Electronic Information Products Regulation” (popular name: China RoHS) (Chinese: 电子信息产品污染控制管理办法); refer to page 7.


■ Applications

1. Telecommunications equipment
2. Home Appliances
3. Office automation equipment
4. Audio visual equipment

Notice The content of data sheet is subject to change without prior notice.
In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc. Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.

Sheet No.: D1-A02201EN
Date: November 30, 2007
©SHARP Corporation

■ External Dimensions



Terminal connection

Pin Arrangement

No.	Name
①	Emitter
②	Collector

NOTES:
1. Units: mm
2. Unspecified tolerence: ±0.2 mm
3. ( ): Reference dimensions
4. Package: Black (visible light cut-off resin)
5. The thin burr thickness (0.05 mm MAX.) is not included in outline dimensions
6. Resin protrusion: 0.3 mm MAX.
7. However, the thin burr adhering to the lead is 1.8 mm MAX. from the resin.

■ Absolute Maximum Ratings

(Ta = 25°C)

Parameter	Symbol	Rating	Unit
Collector-emitter voltage	V_{CEO}	35	V
Emitter-collector voltage	V_{ECO}	6	V
Collector current	I_C	20	mA
Collector power dissipation	P_C	75	mW
Operating temperature	Topr	-25 to +85	°C
Storage temperature	Tstg	-40 to +85	°C
Soldering temperature *1	Tsol	260	°C

*1 3 s (MAX.) at 1.8 mm from resin edge.

■ Electro-optical Characteristics

(Ta = 25°C)

Parameter	Symbol	Conditions *1	MIN.	TYP.	MAX.	Unit
Collector current	I_C	Ee = 1 mW/cm^2, V_{CE} = 5 V	0.08	0.25	0.75	mA
Dark current	I_{CEO}	Ee = 0, V_{CE} = 20 V	–	–	100	nA
Collector-emitter saturation voltage	V_{CE}(sat)	Ee = 10 mW/cm^2, I_C = 0.5 mA	–	–	0.4	V
Collector-emitter breakdown voltage	BV_{CEO}	I_C = 0.1 mA, Ee = 0	35	–	–	V
Emitter-collector breakdown voltage	BV_{ECO}	I_E = 0.01 mA, Ee = 0	6	–	–	V
Peak sensitivity wavelength	λp	–	–	860	–	nm
Response time (Rise)	tr	V_{CE} = 2 V, I_C = 2 mA, R_L = 100 Ω	–	3.0	–	μs
Response time (Fall)	tf		–	3.5	–	μs
Half intensity angle	θ	–	–	±35	–	degrees

*1 Ee: Irradiance by CIE standard light source A (tungsten lamp)

■ Collector Current Ranking

Rank	Collector Current Ic (mA)
A	0.08 to 0.19
B	0.15 to 0.38
C	0.3 to 0.75

*1 Quantities and ratios of any one ranking in any one shipment are at the discretion of Sharp.

Fig. 1 Collector Power Dissipation vs. Ambient Temperature




Fig. 2 Spectral Sensitivity (TYP.)




Fig. 3 Collector Dark Current vs. Ambient Temperature




Fig. 4 Relative Collector Current vs. Ambient Temperature




Fig. 5 Collector Current vs. Irradiance




Fig. 6 Collector Current vs. Collector-Emitter Voltage




Fig. 7 Response Time vs. Load Resistance




Fig. 8 Test Circuit for Response Time




Fig. 9 Sensitivity vs. Axis




Fig. 11 Relative Output vs Distance





Fig. 10 Collector-to-Emitter Saturation Voltage vs. Irradience



Graph data is for reference only and is not guaranteed data.

■ Design Notes

1. This product is not designed to resist electromagnetic and ionized-particle radiation.

■ Manufacturing Guidelines

● Soldering Instructions

1. Sharp does not recommend soldering this part using preheat or solder reflow methods. Leads on this part are pre-coated with lead-free solder.
2. If hand soldering, use temperatures ≤260°C for ≤3 seconds.
3. When mounting this device, care should be taken to prevent any boundary exfoliation (pad lifting) between the solder, the pad, and the circuit board.
4. Do not subject the package to excessive mechanical force during soldering as it may cause deformation or defects in plated connections. Internal connections may be severed due to mechanical force placed on the package due to the PCB flexing during the soldering process.

● Cleaning Instructions

1. Confirm this device's resistance to process chemicals before use, as certain process chemicals may affect the optical characteristics.
2. Solvent cleaning: Solvent temperature should be 45°C or below. Immersion time should be 3 minutes or less.
3. Ultrasonic cleaning: The effect upon devices varies due to cleaning bath size, ultrasonic power output, cleaning time, PCB size and device mounting circumstances. Sharp recommends testing using actual production conditions to confirm the harmlessness of the ultrasonic cleaning methods.
4. Recommended solvent materials: Ethyl alcohol, Methyl alcohol, and Isopropyl alcohol.

■ Presence of ODCs (RoHS Compliance)

This product shall not contain the following materials, and they are not used in the production process for this product:

- Regulated substances: CFCs, Halon, Carbon tetrachloride, 1,1,1-Trichloroethane (Methylchloroform). Specific brominated flame retardants such as the PBBOs and PBBs are not used in this product at all.

This product shall not contain the following materials banned in the RoHS Directive (2002/95/EC).

- Lead, Mercury, Cadmium, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE).
- Content information about the six substances specified in “Management Methods for Control of Pollution Caused by Electronic Information Products Regulation” (Chinese: 电子信息产品污染控制管理办法)

Category	Toxic and Hazdardous Substances					
	Lead (Pb)	mercury (Hg)	Cadmium (Cd)	Hexavalent chromiun (Cr^{6+})	Polybrominated biphenyls (PBB)	Polybrominated diphenyl ethers (PBDE)
Photo Transistor	✓	✓	✓	✓	✓	✓


NOTE: ✓ indicates that the content of the toxic and hazardous substance in all the homogeneous materials of the part is below the concentration limit requirement as described in SJ/T 11363-2006 standard.

■ Packing Specifications

1. Parts are packed in a plastic zipper bag, with 1000 pieces per bag.
2. Bags are secured in a box as shown in Figure 12.
3. Product mass: 0.07 g (approximately)


Fig. 12 Packing Composition

Inner packing



NOTES:
1. Inner packing material : Plastic zipper bag (Polyethylene)
2. Quantity: 1000 pcs/bag

Outer packing



NOTES:
1. Outer material : Packing case (Corrugated cardboard),
   Cushioning material (Urethane), Cellophane tape
2. Quantity: 5000 pcs/box
3. Regular packaged mass: Approximately 460 g
4. Indication: Model No., Quantity, and Lot No.

■ Important Notices

· The circuit application examples in this publication are provided to explain representative applications of SHARP devices and are not intended to guarantee any circuit design or license any intellectual property rights. SHARP takes no responsibility for any problems related to any intellectual property right of a third party resulting from the use of SHARP's devices.

· Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device. SHARP reserves the right to make changes in the specifications, characteristics, data materials, structure, and other contents described herein at any time without notice in order to improve design or reliability. Manufacturing locations are also subject to change without notice.

· Observe the following points when using any devices in this publication. SHARP takes no responsibility for damage caused by improper use of the devices which does not meet the conditions and absolute maximum ratings to be used specified in the relevant specification sheet nor meet the following conditions:
(i) The devices in this publication are designed for use in general electronic equipment designs such as:
--- Personal computers
--- Office automation equipment
--- Telecommunication equipment (terminal)
--- Test and measurement equipment
--- Industrial control
--- Audio visual equipment
--- Consumer electronics

(ii) Measures such as fail-safe function and redundant design should be taken to ensure reliability and safety when SHARP devices are used for or in connection with equipment that requires higher reliabilty such as:
--- Transportation control and safety equipment (i.e., aircraft, trains, automobiles, etc.)
--- Traffic signals
--- Gas leakage sensor breakers
--- Alarm equipment
--- Various safety devices, etc.

(iii) SHARP devices shall not be used for or in connection with equipment that requires an extremely high level of reliability and safety such as:
--- Space applications
--- Telecommunication equipment (trunk lines)
--- Nuclear power control equipment
--- Medical and other life support equipment (e.g. scuba)

· If the SHARP devices listed in this publication fall within the scope of strategic products described in the Foreign Exchange and Foreign Trade Law of Japan, it is necessary to obtain approval to export such SHARP devices.

· This publication is the proprietary product of SHARP and is copyrighted, with all rights reserved. Under the copyright laws, no part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, in whole or in part, without the express written permission of SHARP. Express written permission is also required before any use of this publication may be made by a third party.

· Contact and consult with a SHARP representative if there are any questions about the contents of this publication.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

SHARP:

GP2S700HCP PC400J00000F PC410LENIP0F PC457L0NIP0F PC81712NSZ1B PC364NJ0000F PC817X2NIPW PC817X2YIPW PC123X2YSZ1B PC3H4J00001H PC3SF21YTZBH PC817X1CSP9F PC817X2YSZW GP1A51HRJ00F GP1S094HCZ0F GP2Y0A21YK0F PC357N1J000F PT481E00000F PC923LRYSZ0F GP1S53VJ000F PC123Y23SP9F PC357NJ0000F PC3SF11YTZBH PC817X2NSZ9F PT100MF0MP PC354N1J000F PC3SD11YTZCH PC817X2NIP1B PC355NJ0000F PC817X3NIP1B