PCB terminal block; 6 mm²; Pin spacing 7.5 mm; 5-pole; Push-in CAGE CLAMP®

Item No.: 2626-1105/020-000



PCB terminal block; 6 mm²; Pin spacing 7.5 mm; 5-pole; Push-in CAGE CLAMP®

Marking

RoHS ✓
Compliant

Business data

Supplier	*WAGO*
Item no.	*2626-1105/020-000*
GTIN / EAN	*4055143587129*
Content	*1*
Order amount	*60*
Customer item number	

Notes

Item description:PCB terminal blocks with Push-in CAGE CLAMP® connectionPush-in termination of solid and ferruled conductorsIdeal for panel feedthrough applications via operation parallel to conductor entryTesting can be performed both parallel and perpendicular to conductor entry

Technical data

Miscellaneous

Available upon request (depending on quantity required):	*Other pole numbers*
Packaging type	*BOX*
Ratings per	*IEC/EN 60664-1*


Technical data	
Rated voltage (III / 3) [V]	*800 [V]*
Rated impulse voltage (III / 3) [kV]	*8 [kV]*
Rated voltage (III/2) [V]	*1000 [V]*
Rated impulse voltage (III / 2) [kV]	*8 [kV]*
Rated voltage (II / 2) [V]	*1000 [V]*
Rated impulse voltage (II / 2) [kV]	*8 [kV]*
Rated current [A]	*41 [A]*
Legend (ratings)	*(III / 2) Overvoltage category III / Pollution degree 2*
No. of poles	*5*
Total number of connection points	*5*
Total number of potentials	*5*
Number of connection types	*1*
Number of levels	*1*
Connection technology	*Push-in CAGE CLAMP®*
Actuation type	*Operating tool*
Solid conductor	*0.2 … 10 mm² / 24 … 8 AWG*
Fine-stranded conductor	*0.2 … 10 mm² / 24 … 8 AWG*
Fine-stranded conductor with ferrule with plastic collar	*0.25 … 6 mm²*
Fine-stranded conductor with ferrule without plastic collar	*0.25 … 6 mm² / …*
Strip length	*13 … 15 mm / 0.51 … 0.59 Inch*
Pin spacing	*7.5 mm (0.295 in)*
Width	*39.3 mm / 1.547 Inch*
Height	*23.6 mm / 0.929 Inch*
Height from the surface	*19.6 mm / 0.772 Inch*
Depth	*24.2 mm / 0.953 Inch*
Solder pin length [mm]	*4 [mm]*
Solder pin dimensions	*1.5 x 1 mm*
Drilled hole diameter (tolerance) [mm]	*2(+ 0.1) [mm]*
Type of mounting	*Feed-through mounting*
PCB contact	*THT*
Solder pin arrangement	*over the entire terminal strip, staggered*
Number of solder pins per potential	*1*
Color	*gray*
Material group	*I*

Technical data	
Insulating material	*Polyamide 66 (PA 66)*
Flammability class per UL94	*V0*
Clamping spring material	*Chrome nickel spring steel (CrNi)*
Contact material	*Electrolytic copper (Ecu)*
Contact plating	*tin-plated*
Weight [g]	*19.79 [g]*
Limit temperature range	*-60 … 105 °C*
Pin spacing from [mm]	*7.5 [mm]*
Main product function	*PCB terminal block*
Product type	*PCB terminal blocks*

Images & drawings







Address

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Telefon: 0571/887-0
Fax: 0571/887-169
http://www.wago.com
© WAGO Kontakttechnik GmbH & Co. KG
Technische Änderungen und Irrtümer vorbehalten.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

WAGO:

2102-1204 2624-3502 759-302 852-1322 890-503 2002-1207 233-508 236-506 261-402 2636-1355 855-3001/250-001 260-105 2086-1107 750-1405/040-000 751-9301 769-131 2636-3108/020-000 859-798 235-502 769-428 2010-1205 207-4301 236-424 2624-1312 769-413 859-354 2606-3353 2787-2144 750-638/025-000 885-566