

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,- .
© COPYRIGHT - BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.


LOC	DIST
DW	—

REVISIONS


P	LTR	DESCRIPTION	DATE	DWN	APVD
	E	REVISED (ECR-13-000755)	18JAN13	JL	WK







RECOMMENDED PCB LAYOUT (THICKNESS: 1.6MM)
(TOP VIEW) (TOLERANCE: ±0.05)



		C	B	A	POS.	PART NUMBER
OBSOLETE ④	BLUE	38.4	35.00 ±0.20	40.0	15	3-1470224-5
		35.9	32.50 ±0.20	37.5	14	3-1470224-4
		33.4	30.00 ±0.20	35.0	13	3-1470224-3
		30.9	27.50 ±0.20	32.5	12	3-1470224-2
		28.4	25.00 ±0.20	30.0	11	3-1470224-1
		25.9	22.50 ±0.15	27.5	10	3-1470224-0
		23.4	20.00 ±0.15	25.0	9	2-1470224-9
		20.9	17.50 ±0.15	22.5	8	2-1470224-8
		18.4	15.00 ±0.15	20.0	7	2-1470224-7
		15.9	12.50 ±0.10	17.5	6	2-1470224-6
		13.4	10.00 ±0.10	15.0	5	2-1470224-5
		10.9	7.50 ±0.10	12.5	4	2-1470224-4
		8.4	5.00 ±0.10	10.0	3	2-1470224-3
		5.9	2.50 ±0.10	7.5	2	2-1470224-2
	IVORY	38.4	35.00 ±0.20	40.0	15	1-1470224-5
		35.9	32.50 ±0.20	37.5	14	1-1470224-4
		33.4	30.00 ±0.20	35.0	13	1-1470224-3
		30.9	27.50 ±0.20	32.5	12	1-1470224-2
		28.4	25.00 ±0.20	30.0	11	1-1470224-1
		25.9	22.50 ±0.15	27.5	10	1-1470224-0
		23.4	20.00 ±0.15	25.0	9	0-1470224-9
		20.9	17.50 ±0.15	22.5	8	0-1470224-8
		18.4	15.00 ±0.15	20.0	7	0-1470224-7
		15.9	12.50 ±0.10	17.5	6	0-1470224-6
		13.4	10.00 ±0.10	15.0	5	0-1470224-5
		10.9	7.50 ±0.10	12.5	4	0-1470224-4
		8.4	5.00 ±0.10	10.0	3	0-1470224-3
		5.9	2.50 ±0.10	7.5	2	0-1470224-2

NOTE:

1. MATERIAL:
   HOUSING: PA66, UL 94V-2, COLOR: SEE TABLE.
   CONTACTS: BRASS.

2. FINISH:
   CONTACTS: 1.27μm [50μ"] MIN. BRIGHT-TIN ON SOLDER TAIL, WITH ENTIREC CONTACT UNDERPLATED 0.381μm [15μ"] MIN. NICKEL.

3. WAVE SOLDER CAPABLE TO 240°C PER TE CONNECTIVITY TEST SPEC. 109-202, CONDITION A.

④ OBSOLETE PARTS: OBSOLETE CIS STREAMLINIING PER D.RENAUD/D.SINISI

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: MM

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± 0.5
1 PLC ± 0.25
2 PLC ± 0.15
3 PLC ± 0.05
4 PLC ± -
ANGLES ± - 3°

MATERIAL: SEE NOTE
FINISH: SEE NOTE

DWN	O. HU 19DEC2006
CHK	S. HOU 19DEC2006
APVD	W.J. KE 19DEC2006
PRODUCT SPEC	108-57175
QUALIFICATION TEST REPORT	501-57195
WEIGHT	--
CUSTOMER DRAWING	

TE Connectivity

NAME: 2.5mm PITCH EMIX POST HEADER, VERTICAL TYP

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C-1470224	—

SCALE	SHEET	REV
—	1 OF 2	E

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION –,– .
© COPYRIGHT – BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.


LOC	DIST
DW	—


REVISIONS


P	LTR	DESCRIPTION	DATE	DWN	APVD
		SEE SHEET 1.			

CARTON
340mm(L)X470mm(W)X158mm(H)
(FOR P/N 0–1470224–2~0–1470224–5)
340mm(L)X470mm(W)X316mm(H)
(FOR P/N 0–1470224–6~1–1470224–5)

POLY BAG







APQ (PCS/CARTON)	PPQ (PCS/BAG)	PART NUMBER	
		⚠4 OBSOLETE	
12,960	180	3–1470224–5	1–1470224–5
12,000	200	3–1470224–4	1–1470224–4
14,400	200	3–1470224–3	1–1470224–3
16,000	250	3–1470224–2	1–1470224–2
16,000	250	3–1470224–1	1–1470224–1
20,000	250	3–1470224–0	1–1470224–0
21,600	300	2–1470224–9	0–1470224–9
25,200	350	2–1470224–8	0–1470224–8
28,000	350	2–1470224–7	0–1470224–7
35,000	350	2–1470224–6	0–1470224–6
20,000	500	2–1470224–5	0–1470224–5
24,000	600	2–1470224–4	0–1470224–4
30,000	750	2–1470224–3	0–1470224–3
36,000	1000	2–1470224–2	0–1470224–2

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: MM

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± –
3 PLC ± –
4 PLC ± –
ANGLES ± –

MATERIAL –
FINISH –

DWN	O. HU	19DEC2006
CHK	S. HOU	19DEC2006
APVD	W.J. KE	19DEC2006
PRODUCT SPEC	—	
APPLICATION SPEC	—	
WEIGHT	–	

TE Connectivity

NAME
2.5mm PITCH EMIX POST HEADER, VERTICAL TYP

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C–1470224	—

CUSTOMER DRAWING | SCALE — | SHEET 2 OF 2 | REV E

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TE Connectivity:

2377783-2 3430B2F51RTDF 141991-2 2834055-1 ROX05SJ18R TE50BR39J CPF0402B37K4E1 MPT100C18RF RH73H2A40MKTN 1903112-2 2310537-1 2380312-2 936348-1 1-794222-0 1969656-1 3-1393225-0 SBCHE64R7K SMW73R0JT U5254-000005-030PA 1743455-2 1-962915-1 1393431-1 2-292161-3 650075-000 CRGCQ2010J3K3 SBCHE154R7K 175977-2 2005330-1 3631B101LL 917696-1