© 2016 TE Connectivity Ltd. family of companies. All Rights Reserved

HARNESSING

HEAT SHRINK BOOTS



✔ Active

TE CONNECTIVITY (TE)

202D121-4-0

Raychem | CAP , CRPS

202D121-4-0
TE Internal Number: 814406-000
Alias ID: 7-1196340-1

EU RoHS Compliant
EU ELV Compliant

Lipped Yes

Operating Temperature Range (°C) -55 – 135

Fluid/Chemical Resistance Suitable for occasional exposure to fluids

Adhesive Options S1006 Separate Adhesive, -55°C – 135°C (-67°F – 275°F), S1017 Separate Adhesive, -20°C – 60°C (-4°F – 140°F), S1030 Separate Adhesive, -80°C – 80°C (-112°F – 176°F), S1048 Separate Adhesive, -55°C – 105°C (-67°F – 221°F), S1125 Separate Adhesive, -75°C – 150°C (-103°F – 302°F)

Material Systems Code 10

PRODUCT DRAWING
English

DOCUMENTATION

Product Drawings

Boot, Straight, With Lips
PDF
English

Product Specifications

Product Specification

Thermofit Polyolefin Molded Components Flame-Retarded, Flexible, Heat-Shrinkable
PDF
English

Product Environmental Compliance

Downloaded from Arrow.com.

Safety Data Sheet

EPS Heat Shrinkable Polymeric Products

PDF

French

EPS Heat Shrinkable Polymeric Products

PDF

Italian

EPS Heat Shrinkable Polymeric Products

PDF

Dutch

EPS Heat Shrinkable Polymeric Products

PDF

Danish

EPS Heat Shrinkable Polymeric Products

PDF

English

EPS Heat Shrinkable Polymeric Products

PDF

German

EPS Heat Shrinkable Polymeric Products

PDF

Norwegian

EPS Heat Shrinkable Polymeric Products

PDF

Spanish

EPS Heat Shrinkable Polymeric Products

PDF

Swedish

FEATURES

Please review product documents or contact us for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Molded Part Type Molded Boot

Configuration Features

Lipped Yes

Body Features

Downloaded from Arrow.com.

Material Systems Code 10
Adhesive Pre-Coat No
Entry Size (Braided or Magneform Adapter) 10, 11, 4, 5, 6, 7, 8, 9
Entry Size (Solid or Fixed Adapter) 4 – 6
Material Modified Polyolefin
Entry Size (Tinel-Lock Adapter) 4, 5, 6, 7, 8
Entry Size (Spin Coupling Adapter) 4 – 10

Dimensions

Cable Diameter Range 5.6 – 12.4 mm [.22 – .488 in]
Wire/Cable Outside Diameter .236 in, .276 in, .3 in, .31 in, .35 in, .39 in, .43 in, .433 in, 10 mm, 11 mm, 6 mm, 7 mm, 8 mm, 9 mm

---

Usage Conditions

Operating Temperature Range (°C) -55 – 135

Operation/Application

Power Cable Accessory No

Industry Standards

Government Qualified No
Approved Standards SAE AS I 81765/1, Type II, UL 224, File E85381

Other

Fluid/Chemical Resistance Suitable for occasional exposure to fluids
Adhesive Options S1006 Separate Adhesive, -55°C – 135°C (-67°F – 275°F), S1017 Separate Adhesive, -20°C – 60°C (-4°F – 140°F), S1030 Separate Adhesive, -80°C – 80°C (-112°F – 176°F), S1048 Separate Adhesive, -55°C – 105°C (-67°F – 221°F), S1125 Separate Adhesive, -75°C – 150°C (-103°F – 302°F)
Adhesive Type Adhesive Purchased Separately

Statement of Compliance

Statement of Compliance
PDF

Downloaded from Arrow.com.