

RoHS 2011/65/EU | REACH compliant | Conflict minerals free


GEYER quartz technology

Clock Oscillator

+3,3V

model	KXO-V97T
frequency	65,0 MHz
frequency stability at -40° ~ +85°C	± 100 ppm
operating temperature	-40° ~ +85°C
storage temperature	-40° ~ +85°C
symmetry	50% ± 10% at ½ V_{DD} level
rise & fall time max.	5 ns
"O" level max.	+ 0,4V
"1" level min.	V_{DD} -0,5V
input voltage V_{DD}	+ 3,3V ± 10%
input current	9,0 mA typ., 16,0 mA max.
output load	30 pF
start up time max.	10 ms
tristate function	yes
disable delay time	100 ns max.
enable delay time	4 ms max.
random jitter	7ps max.
peak to peak jitter	40ps max.
contents of reel	1000 pcs.
part no.	12.92106


Dimensions (mm):




PIN	CONNECTION	
1	"L" (OV)	"H" or OPEN
2	GND	
3	Z	OUTPUT
4	V_{DD}	

Z: high impedance


Output waveform:




Reflow soldering condition:



Test circuit:




Tape specifications:



reel diameter 330 mm

Suggested soldering pad:



GEYER ELECTRONIC e.K. Lochhamer Schlag 5 82166 Gräfelfing/München
Tel. +49 89 546868-0 quartz@geyer-electronic.de www.geyer-electronic.de

Version 03.09.2015

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Geyer Electronic:

12.85526 12.87106 12.87174 12.89190 12.90329 12.95548 12.60113 12.60370 12.84812 12.88664
12.89020 12.89997 12.60146 12.87150 12.87165 12.88603 12.89495 12.95102 12.85562 12.86526
12.86533 12.90307 12.90325 12.86512 12.87148 12.95543 12.86564 12.94474 12.95542 12.89126