
THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,- .
© COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST
AD	39

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	H2	REVISED PER ECO-11-004587	11MAR11	RK	HMR



1 ASSEMBLIES MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS

2 TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADERS ARE HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD


△3 .000100-.000200 MATTE TIN-LEAD OVER .000050 NICKEL ENTIRE POST

△4 .000100-.000200 BRIGHT TIN OVER .000050 NICKEL ENTIRE POST

△5 PRELIMINARY PART - NOT RELEASED FOR PRODUCTION.

△6 HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR BLACK.

△7 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI



RECOMMENDED HOLE LAYOUT

△5	△4	1.584	1.500	15	16	4-103741-2
OBSOLETE	△4	1.384	1.300	13	14	4-103741-1
	△3	3.984	3.900	39	40	4-103741-0
OBSOLETE	△3	3.884	3.800	38	39	3-103741-9
△7	△3	3.784	3.700	37	38	3-103741-8
△7 SUPERSEDED BY 8-146282-7	△3	3.684	3.600	36	37	3-103741-7
	△3	3.584	3.500	35	36	3-103741-6
	△3	3.484	3.400	34	35	3-103741-5
	△3	3.284	3.300	33	34	3-103741-4
	△3	3.284	3.200	32	33	3-103741-3
	△3	3.184	3.100	31	32	3-103741-2
	△3	3.084	3.000	30	31	3-103741-1
	△3	2.984	2.900	29	30	3-103741-0
	△3	2.884	2.800	28	29	2-103741-9
OBSOLETE	△3	2.784	2.700	27	28	2-103741-8
	△3	2.684	2.600	26	27	2-103741-7
△7	△3	2.584	2.500	25	26	2-103741-6
	△3	2.484	2.400	24	25	2-103741-5
	△3	2.384	2.300	23	24	2-103741-4
	△3	2.284	2.200	22	23	2-103741-3
	△3	2.184	2.100	21	22	2-103741-2
	△3	2.084	2.000	20	21	2-103741-1
	△3	1.984	1.900	19	20	2-103741-0
	△3	1.884	1.800	18	19	1-103741-9
	△3	1.784	1.700	17	18	1-103741-8
	△3	1.684	1.600	16	17	1-103741-7
	△3	1.584	1.500	15	16	1-103741-6
	△3	1.484	1.400	14	15	1-103741-5
	△3	1.384	1.300	13	14	1-103741-4
	△3	1.284	1.200	12	13	1-103741-3
	△3	1.184	1.100	11	12	1-103741-2
	△3	1.084	1.000	10	11	1-103741-1
	△3	.984	.900	9	10	1-103741-0
	△3	.884	.800	8	9	103741-9
	△3	.784	.700	7	8	103741-8
	△3	.684	.600	6	7	103741-7
	△3	.584	.500	5	6	103741-6
	△3	.484	.400	4	5	103741-5
	△3	.384	.300	3	4	103741-4
	△3	.284	.200	2	3	103741-3
	△3	.184	.100	1	2	103741-2
	△3	.084	———	———	1	103741-1
PLATING	C	B	A	NO OF POS	ASSEMBLY PART NUMBER	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± .005
4 PLC ± -
ANGLES ± -

MATERIAL: PHOSPHOR BRONZE △6

FINISH: SEE TABLE

DWN L. RINGLEY 7-19-85
CHK R. ELICKER 7-19-85
APVD R. ELICKER 7-19-85
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT —

TE Connectivity

NAME
ASSEMBLY, MOD II, HEADER,
BREAKAWAY, SINGLE ROW, .100 C/L,
VERTICAL, WITH .025 SQ. POSTS

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C-103741	—

CUSTOMER DRAWING | SCALE 4:1 | SHEET 1 OF 1 | REV H2

103741

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TE Connectivity:

SBCHE154R7K 1-962915-1 1743455-2 3631B101LL 650075-000 936348-1 CRGCQ2010J3K3 1903112-2
2005330-1 ROX05SJ18R U5254-000005-030PA 175977-2 2310537-1 2834055-1 917696-1 TE50BR39J
2380312-2 3430B2F51RTDF MPT100C18RF SBCHE64R7K 1393431-1 1969656-1 1-794222-0
3-1393225-0 141991-2 SMW73R0JT 2-292161-3 2377783-2 CPF0402B37K4E1 RH73H2A40MKTN