XFCN兴飞连接器有限公司
CONNECTORS XFCN CONNECTORS CO., LTD.
TEL:0769-82001899 FAX:0769-87929170

# 产品规格书
# PRODUCT SPECIFICATION

This specification is referred to the 2.50mm series wire to board connector

## 索引【INDEX】

1. 适用范围 【Scope】

2. 规格与料号 【Spec and Part number】

3. 材质与表面处理 【Disposal of Material and surface】

4. 额定等级 【Ratings and applicable wires】

5. 性能 【 Performance 】

5-1. 电气的性能【Electrical Performance.】

5-2. 机械的性能【Mechanical Performance】

5-3. 环境性能及其它【Environmental Performance and Others】

6. 综合插入力及拔出力 【Insertion Force & Withdrawal Force】

| Product Specification [产品规格书]: | ISSUED BY: Engineering Dept | |
|---|---|---|
| Subject [主题]: 2.50mm Pitch 2501 Series Connector Specification | Date Issued | 2012/09/08 |
| | Date Revised | 2015/11/11 |

**【1.适用范围 Scope】**

此种规格包括 2.50mm Pitch 2501 Series 连接器规格说明.

This Specification Covers the 2.50mm Pitch 2501 Series Connector Specification.

**【2.规格与料号 Spec and Part number】**

| 规格内容 Specification | 产品料号 Production No. | 产品图示 Picture of Product |
|---|---|---|
| 端子/Terminal | T2501PS-2 | NONE |
| 胶壳/Housing | P2501-XX-XXX | NONE |
| 针座/Wafer | M2501V-XX-XXX<br>M2501R-XX-XXX | NONE |

**【3.材质与表面处理 Disposal of Material and surface】**

| 规格内容 Specification | | 材 质 Materials | 表面处理 Disposal of Surface |
|---|---|---|---|
| 端子/Terminal | | 磷铜/Phosphor Bronze<br>黄铜/ Brass | Tin Plated: Over 40μ′ .Nickel: Over 15μ′ . |
| 胶壳/Housing | | PA66 | UL 94V-0 |
| 针座/Wafer | Base | PA66 | UL 94V-0 |
| | PIN | 黄铜/Brass | Over Tin 70μ′ Plated ; Over 30μ′ Nickel |

**（上述参数请以工程图为准/Please Refer to the Project drawing for the above Specification）**

**【4. 额定等级 Ratings and applicable wires】**


| 项 目【Item】 | 规 格【Standard】 | |
|---|---|---|
| 额定电压 Rated Voltage (Max.) | 250V | [AC/DC] |
| 额定电流 Rated Current (Max.) | 3A | |
| 使用温度范围 Ambient temperature Range | -25℃~+85℃ | |
| 适用线径 Applicable wire insulation O.D | AWG 22#~30# Insulation O.D. 1.90mm(Max.) | |

【 *升温时含端子.Including terminal temperature rise. 】

| Product Specification [产品规格书]: | ISSUED BY: Engineering Dept | |
|---|---|---|
| Subject [主题]: 2.50mm Pitch 2501 Series Connector Specification | Date Issued | 2012/09/08 |
| | Date Revised | 2015/11/11 |




## 【5.性能 PERFORMANCE】

### 5-1. 电气的性能 Electrical Performance.


| 项 目 【Item】 | | 条 件 【Test Condition】 | 规 格 【Requirement】 |
|---|---|---|---|
| 5-1-1 | 接触阻抗 Contact Resistance | 公母配合,开放电压 20mV 以下,电流 10mA 检测连接器 A~B 区.<br>Mate connectors, measure by dry circuit, 20mV MAX, 10mA.<br>(Based upon EIA-364-06A).<br> | Initial:<br>10 milliohms Max.<br>After Test:<br>20 milliohms Max. |
| 5-1-2 | 绝缘阻抗 Insulation Resistance | 公母配合,在相邻端子,端子与地片之间,使用 500V 的直流电,检测连接器.<br>Mate connectors, apply 500V DC between adjacent terminal or ground.<br>(Based upon EIA-364-21B / MIL-STD-202 Method 302 Cond.B) | 1000 Megohms Min. |
| 5-1-3 | 耐电压 Dielectric Strength | 公母配合,在相邻端子,端子与地片之间,使用 1000V 的交流电 1 分锺,检测连接器.<br>Mate connectors, apply 1000V AC for 1 minute between adjacent terminal or ground.<br>(Based upon EIA-364-20A / MIL-STD-202 Method 301) | 不出现中断等情况<br>No Breakdown and Flashover |
| 5-1-4 | 铆线后端子接触阻抗 Contact resistance on crimped portion | 铆线后之端子,开放电压 20mV 以下,电流 10mA 检测连接器.<br>Crimp the applicable wire on to the terminal measure by dry circuit 20mV MAX, 10mA. | 10 milliohms Max. |

| Product Specification [产品规格书]: | ISSUED BY: Engineering Dept | |
|---|---|---|
| Subject [主题]: 2.50mm Pitch 2501 Series Connector Specification | Date Issued | 2012/09/08 |
| | Date Revised | 2015/11/11 |

**5-2. 机械的性能 Mechanical Performance.**

| 项 目 【Item】 | | 条 件 【Test Condition】 | 规 格 【Requirement】 |
|---|---|---|---|
| 5-2-1 | 插拔力 Insertion & Retention Force | 以每分锺 25.4±3mm 的速率插入和拔出. Insert and withdraw Connectors at the speed rate of 25.4±3mm/minute.   | 参照第 6 项 Refer to paragraph 6 |
| 5-2-2 | 端子保持力 Terminal/ Housing Retention Force | 以每分 25.4±3mm 的速率,将端子从 Housing 内轴向拔出的力量. Apply axial pull out force at the speed rate of 25.4±3mm/minute on the terminal assembled in the housing.   | 19.6N {2.0kgf} Min. |
| 5-2-3 | 端子插入力 Terminal Insertion Force | 铆线后之端子插入 Housing 所需最大力量. Insert the crimped terminal into the housing. | 14.7N {1.5kgf} Max. |
| 5-2-4 | Pin 针保持力 Pin Retention Force | 以每分 25.4±3mm 的速率,将 PIN 针从 Wafer 内轴向拔出的力量. Apply axial push force at the speed rate of 25.4±3mm/minute.  | 19.6N {2.0kgf} min. |

| Product Specification [产品规格书]: | ISSUED BY: Engineering Dept | |
|---|---|---|
| Subject [主题]: 2.50mm Pitch 2501 Series Connector Specification | Date Issued | 2012/09/08 |
| | Date Revised | 2015/11/11 |

| 项 目 【Item】 | | 条 件 【Test Condition】 | 规 格 【Requirement】 | | | | | |
|---|---|---|---|---|---|---|---|---|
| 5-2-5 | 端子压着强度 Tensile strength (Crimped connections) | 固定铆线后的端子，使电线与端子分离时所需的最小力量.<br>Fix the crimped terminal, apply axial pull out force on the wire. (Do not crimp insulation part). | AWG# | #22 | #24 | #26 | #28 | #30 |
| | | | Spec. .kgf. Min. | 5.0 | 3.0 | 2.0 | 1.0 | 0.5 |
| | |  | Note> As for unspecified wire sizes in this specification define values with clients | | | | | |

**5-3. 环境性能及其它 Environmental Performance and Others.**

| 项 目 【Item】 | | 条 件 【Test Condition】 | 规 格 【Requirement】 | |
|---|---|---|---|---|
| 5-3-1 | 重复插拔 Repeated Insertion/ Withdrawal | 以每分锺不超过 10 次的速率,将公母插拔 50 次.<br>When mated up to 50 cycles repeatedly by the rate of 10 cycles per minute. | 接触阻抗 Contact Resistance | 20 milliohms Max. |
| 5-3-2 | 温升测试 Temperature Rise | 公母对插后,在通过额定电流下,所测定的温度.<br>Carrying rated current load. (UL 1977) | 温升测试 Temperature rise | 30℃ Max. |
| 5-3-3 | 耐振动性 Vibration | 振幅: 1.5mm P-P<br>时间: 10~55~10 HZ in 1 minute<br>持续时间: 每轴向 2 小时<br>Amplitude: 1.5mm P-P<br>Sweep time: 10~55~10 HZ in 1 minute<br>Duration: 2 hours in each X.Y.Z axials.<br>(Based upon EIA-364-28B/MIL-STD-202 Method 213B Cond.A) | 外观 Appearance | 无异状 No Damage |
| | | | 接触阻抗 Contact Resistance | 20 milliohms Max. |
| | | | 瞬断 Discontinuity | 1 micro-second Max. |
| 5-3-4 | 耐冲击性 Shock | 在 X.Y.Z 上 6 个方向上,以 490m/s$^2$(50g 的力量)冲击下各 3 回.490m/s$^2${50G}, 3 strokes in each X.Y.Z. axes.<br>(Based upon EIA-364-27B/MIL-STD-202 Method 213B Cond.A) | 外观 Appearance | 无异状 No Damage |
| | | | 接触阻抗 Contact Resistance | 20 milliohms Max. |
| | | | 瞬断 Discontinuity | 1 micro-second Max. |

| Product Specification [产品规格书]: | ISSUED BY: Engineering Dept | |
|---|---|---|
| Subject [主题]: 2.50mm Pitch 2501 Series Connector Specification | Date Issued | 2012/09/08 |
| | Date Revised | 2015/11/11 |

| 项 目 【Item】 | | 条 件 【Test Condition】 | 规 格 【Requirement】 | |
|---|---|---|---|---|
| 5-3-5 | 耐热性 Heat Resistance | 85±2℃,96 hours.<br>(Based upon MIL-STD-202 Method 108A Cond.A) | 外观 Appearance | 无异状 No Damage |
| | | | 接触阻抗 Contact Resistance | 20 milliohms Max. |
| 5-3-6 | 耐寒性 Cold Resistance | -25±5℃,96 hours.<br>( Based upon EIA-364-105) | 外观 Appearance | 无异状 No Damage |
| | | | 接触阻抗 Contact Resistance | 20 milliohms Max. |
| 5-3-7 | 耐湿性 Humidity | 温度: 40±2℃<br>湿度: 90~95%(RH)<br>持续时间: 96 hours<br>Temperature: 40±2℃<br>Relative Humidity: 90~95%<br>Duration: 96 hours<br>(Based upon EIA-364-31A/MIL-STD-202 Method 103B Cond.B) | 外观 Appearance | 无异状 No Damage |
| | | | 接触阻抗 Contact Resistance | 20 milliohms Max. |
| | | | 耐电压 Dielectric Strength | Must meet 5-1-3 |
| | | | 绝缘阻抗 Insulation Resistance | 500 Megohms Min. |
| 5-3-8 | 温度变化 Temperature Cycling | 从-25℃持续 30 分锺升至+85℃持续 30 分锺, 循环 5 次.<br>5 cycles of: a) -25℃ 30 minutes.<br>b) +85℃ 30 minutes.<br>(Based upon EIA-364-32B) | 外观 Appearance | 无异状 No Damage |
| | | | 接触阻抗 Contact Resistance | 20 milliohms Max. |
| 5-3-9 | 盐水喷雾 Salt Spray | 在温度 35±2℃,盐水浓度 5±1%下,盐水喷雾 24±1 小时.<br>24±1 hours exposure to a salt spray from the 5±1% solution at 35±2℃.<br>(Based upon EIA-364-26A/MIL-STD-202 Method 101D Cond.B).<br>此项测试适用于 8821T-XSN 先冲后镀产品 | 外观 Appearance | 无异状 No Damage |
| | | | 接触阻抗 Contact Resistance | 20 milliohms Max. |
| 5-3-10 | 焊锡附着性 Solder-ability | 焊接时间: 3±0.5 秒.<br>焊接温度: 245±5℃.<br>Soldering Time: 3±0.5second.<br>Solder Temperature: 245±5℃.<br>(Based upon EIA-364-52) | Solder Wetting | 浸渍面积需 95%以上 95% of immersed area must show no voids, pin holes. |

| Product Specification [产品规格书]: | ISSUED BY: Engineering Dept | |
|---|---|---|
| Subject [主题]: 2.50mm Pitch 2501 Series Connector Specification | Date Issued | 2012/09/08 |
| | Date Revised | 2015/11/11 |

| 项 目 【Item】 | | 条 件 【Test Condition】 | 规 格 【Requirement】 | |
|---|---|---|---|---|
| 5-3-11 | 焊锡耐热性 Solder-Resistance | 焊接时间: 3~5 秒.<br>焊接温度: 250+5/-5℃.<br>Soldering time:3~5 sec solder.<br>Temperature:250+5/-5℃.<br>(Based upon EIA-364-56A) | 外观 Appearance | 无异状 No Damage |

**【6.综合插入力及拔出力 INSERTION/WITHDRAWAL FORCE】<Connector mating force>**

| PIN 数 No. of CKT | 初次插入力(最大值) First Insertion (kgf Max.) | 30 次拔出力(最小值) 30th Withdrawal (kgf Min.) | PIN 数 No. of CKT | 初次插入力(最大值) First Insertion (kgf Max.) | 30 次拔出力(最小值) 30th Withdrawal (kgf Min.) |
|---|---|---|---|---|---|
| Single | 1.00 | 0.20 | 09 | 6.50 | 1.20 |
| 02 | 3.00 | 0.60 | 10 | 7.00 | 1.40 |
| 03 | 3.50 | 0.80 | 11 | 7.50 | 1.40 |
| 04 | 4.00 | 0.90 | 12 | 8.00 | 1.60 |
| 05 | 4.50 | 0.90 | 13 | 8.50 | 1.60 |
| 06 | 5.00 | 1.00 | 14 | 9.00 | 1.80 |
| 07 | 5.50 | 1.00 | 15 | 9.50 | 2.00 |
| 08 | 6.00 | 1.20 | 16 | 10.00 | 2.60 |

注：以上插拔次数为 30 次　　Note：Insertion and Withdrawal for 30Cycles

# Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

## XFCN:

M2010V-04P TT44080080-0820 XF-P000159 XF-P00092 XF-P00115 XF-P000237 M2016V-05P PZ200V-11-05P XF-12571503P3 XF-P000141 XF-P000167 XF-P00099 XF-P00126 M2545V-02P PZ254V-11-11P XF-P00001 XF-P00014 XF-P00065 M2016V-08P XF-P000143 XF-P000223 F1001-T-16-25T-R M1250VS-05P P1257-05P PZ200V-11-08P F1003-ZV-26-25T-R M2010V-07P P1257-04P XF-2501L3003P3 T2026PS-2